



3200L 32" Interactive Digital Signage Touch Display

The 3200L Interactive Digital Signage (IDS) display combines precision Elo touch screen technology with a professional-grade, large format LCD panel. The 3200L offers System Integrators, Value-Added Resellers and Software Developers a high-performance touch solution for interactive digital displays in high traffic consumer environments.

The 32-inch 3200L is part of a new family of touch displays which bring interactivity to digital signage. The Elo TouchSystems 3200L features a seamless, zero-bezel design for an elegant appearance and a choice of the innovative Acoustic Pulse Recognition (APR) touch technology or IntelliTouch Plus for a responsive touch experience. The display is housed in a highly durable steel chassis for a long life of reliable and durable performance in almost any public-access location. Elo Zero-bezel APR technology recognizes touch on virtually the entire display surface, offering a full-screen interface for navigation regardless of how the display is touched—finger, prosthetic, stylus, card or pen—resulting in an efficient display canvas for almost any commercial application.

Optional high performance computer modules are well-suited for running interactive media and are available with a choice of two processing models: ECM1 with the Intel Celeron Dual-Core 2.2GHz and ECM2 with the Intel

Core 2 Duo 3.0GHz. The computer modules are field-installable, easily sliding into a dedicated bay behind the touch display and locking into place with two thumbscrews. These modules make the 3200L a reliable platform that is interoperable with content management servers and support optimal partitioning of locally cached and network stored content.

Benefits

- Professional-grade hardware provides improved durability withstands rigors of public use over “consumer-type” TV displays
- Advertising and content effectiveness measured in real-time with interactive feedback
- Edge-to-edge glass design facilitates easy care and cleaning, plus dust and liquid resistance
- Power and display control functions can be locked out to prevent tampering
- Built-in speakers provide audio expansion capabilities
- Reliable, resilient APR and IntelliTouch Plus technologies deliver an exceptional touch experience
- Landscape and portrait orientations allow flexible configurations to suit a variety of design layouts



3200L 32" Interactive Digital Signage Touch Display

Model	3200L
Useful screen area	Horizontal: 27.5" (698 mm); Vertical: 15.4" (392 mm)
Monitor dimensions (without stand)	Width: 31.4" (797 mm); Depth: 5.4" (136 mm); Height: 19.2" (487 mm)
Touch technology	Zero-bezel Acoustic Pulse Recognition (APR), IntelliTouch Plus
Speakers	A pair of 10 W stereo speakers facing down (in landscape mode)
Audio input connector	3.5 mm TRS jack
Audio input signal range	1 Vrms max stereo signal (standard PC line out)
Headphone output connector	3.5 mm TRS jack
Headphone output signal (for 1KHz signal)	Delivers 90 mW of power into a 32 ohm stereo load
LCD technology	Active matrix TFT LCD
Diagonal size	31.5"
Aspect ratio	16:9
On-screen display (OSD)	Controls: menu, up, down, select; settings: brightness, contrast, clock, phase, auto-adjust, H-position, V-position; maintain aspect ratio, sharpness, color temperature, OSD timeout, OSD language, mounting, OSD H-position, OSD V-position, volume, mute, recall defaults, video source, audio source; Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese; Lockouts: OSD, power; accessible through switches on the rear, or through the standard Elo OSD control box.
Stand options	Optional stand available, order Part Number E953908
Mounting options	VESA MIS-F, 600 x 200, Y, 6, 90
Native (optimal) resolution	1366 x 768 at 60 Hz
Other supported resolutions	640 x 480 at 60 Hz; 720 x 480 at 60 Hz; 800 x 600 at 56, 60 Hz; 1024 x 768 at 60 Hz; 1280 x 720 at 50, 60 Hz; 1280 x 960 at 60 Hz; 1280 x 1024 at 60 Hz; 1366 x 768 at 60 Hz; 1440 x 900 at 60 Hz; 1680 x 1050 at 60 Hz; 1920 x 1080 at 50, 60 Hz
Colors	16.7 million
Brightness (typical)	LCD panel: 450 nits; with APR: 405 nits; IntelliTouch Plus: 405
Response time (Tr + Tf) total (typical)	20 msec
Viewing angle (typical)	Horizontal: ±89° or 178° total; Vertical: ±89° or 178° total
Contrast ratio (typical)	3500:1
Input video format	Analog VGA, HDMI 1.3
Input video signal connector	Female DE-15 for Analog VGA; HDMI Type A receptacle for HDMI
Input frequency	Horizontal: 32-80 kHz; Vertical: 50-61 Hz
Power supply	Internal AC
Input voltage	100-240 VAC, 50/60 Hz
Power connector	IEC 60320 C14
Power consumption (typical)	Monitor only: ON, max. audio, 100 V/60 Hz: 111 W; SLEEP, 100 V/60 Hz: 12 W; OFF, 100 V/60 Hz: 11.5 W
Temperature	Operating: 0°C to 40°C (32°F to 104°F); Storage: -20°C to 50°C (-4°F to 122°F)
Humidity (non-condensing)	Operating: 20-80%; Storage: 10-90%
Weight	Actual: w/o Computer Module 46.3 lb (21.0 Kg); with Computer Module 52.0 lb (23.6 Kg) Shipping: 68.3 lb (31.0 Kg)
Shipping	TBD (Computer Module shipped separately)
Shipping box dimensions	37.0" (939 mm) x 11.0" (280 mm) x 25.0" (635 mm)
Warranty	3 years
Backlight lamp life (typical)	50,000 hours to half-brightness
MTBF	50,000 hours demonstrated
Agency approvals	Argentina S-mark; Australia C-Tick; Canada cUL; China CCC; Mexico NOM; Russia & CIS GOST; United States UL; Elo declarations; Europe CE; Canada IC; Japan VCC; United States FCC

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

800-ELO-TOUCH
Elo TouchSystems
301 Constitution Drive
Menlo Park, CA 94025-1110
Tel 1-650-361-4800
Fax 1-650-361-4722
customerservice@elotouch.com

Europe

Tel +32 (0)16 35 21 00
Fax +32 (0)16 35 21 01
elosales@elotouch.com

Asia-Pacific

Tel +81 (45) 478-2161
Fax +81 (45) 478-2180
www.tps.co.jp

Latin America

Tel 786-923-0251
Fax 305-931-0124
www.elotouch.com.ar



Tyco Electronics Corporation and its Affiliates in the TE Touch Solutions business unit of the TE Connectivity Ltd. family of companies (collectively "TE") reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Elo (logo), Elo TouchSystems, IntelliTouch, TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks of the TE Connectivity Ltd. family of companies.

Copyright 2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company. All rights reserved. 04/11

