

# Advanced Performance Line TouchBoard G80-11900

19" Compact keyboard with integrated touchpad



# Key benefits

- Cherry MX technology (single keys with Gold Crosspoint contacts)
- Expanded layout
- Integrated touchpad
- Programmable keys (only USB version)
- Space-saving (19") and ergonomic

# Touchpad

Touchpad with two additional keys; usable with standard mouse drivers of the operating system

Resolution: 1000 dpi

# Approvals

CE, VDE/ÜG, FCC DoC CI. B, cURus, C-Tick, VCCI CI. 2; Designed for MS Windows 2000 and XP

# System requirements

IBM- or compatible PC

PS/2 version: PS/2 plug for keyboard PS/2 plug for mouse

USB version: USB plug; USB supporting operating system; KeyM@n software for programming of keys usable under Win 98, ME, 2000, XP

# **Delivery volume**

Keyboard Printed quick-start instructions CD-ROM (USB version only)

# **Technical data**

### **Current consumption**

PS/2: 35 mA (keyboard), 3 mA (Touchpad) USB: max. 100 mA; USB 2.0 (low speed)

Number of keys 104/105 incl. Windows <sup>™</sup> keys

# **Operating life time of single key** > 50 million operations

Cable length

approx. 1.75 m (round cable non-coiled)

### Weight

approx. 1125 g (without packaging) approx. 1200 g (with packaging)

### Measurements

approx. 415 x 193 x 37 mm (keyboard) approx. 447 x 250 x 45 mm (packaging)

### Reliability

MCBF >  $10^9$  operations MTBF > 100 000 hours

#### Storage temperature -20 °C until 60 °C

**Operating temperature** 0 °C until 50 °C

### Packaging unit

72 keyboards per master carton 144 keyboards per pallet

**Guarantee period** 

2 years



The Cherry KeyM@n Software supports following keys (TouchBoard USB version only): Function keys F1 – F12; Insert ; Delete ; Home ; End ; Page Up ; Page Down ; PrtScr ; Break ; Numpad comma ; Numpad 0 These keys can be programmed in 3 layers freely (Standard; Control-layer; Shift-layer)

Special software configurations of the touchpad are not supported.

### **Order description**

| Order number     | Colour     | Connection<br>Keyboard | Connection<br>Touchpad | Adaptor  |
|------------------|------------|------------------------|------------------------|----------|
| G80-11900LUMxx-0 | light grey | USB *                  |                        |          |
| G80-11900LUMxx-2 | black      | USB *                  |                        |          |
| G80-11900LPMxx-0 | light grey | PS/2                   | PS/2                   |          |
| G80-11900LPMxx-2 | black      | PS/2                   | PS/2                   |          |
| G80-11900LTMxx-0 | light grey | PS/2 or DIN (AT)       | PS/2 or RS 232         | enclosed |
| G80-11900LTMxx-2 | black      | PS/2 or DIN (AT)       | PS/2 or RS 232         | enclosed |

\* One plug for keyboard and touchpad

The xx in the order description defines the country version.

- BE Belgium
- CH Switzerland
- DE Germany
- DK Denmark ES Spanish
- EU US English/ international with €
- FR France
- GB English (UK)
- IT Italy
- NO Norway
- PO Portugal
- SF Sweden/Finland
- US US-English

Other country versions upon request.

Cherry GmbH Cherrystrasse 91275 Auerbach/Opf. Germany Phone: +49 (0) 9643 18-0 Hotline: +49 (0) 9643 18-206 Fax: +49 (0) 9643 18-1545 Internet: www.cherry.de

The manufacturer accepts no liability for errors or nonavailability, and reserves the right to change specifications without prior notice.

Technical data relate to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2004 Cherry GmbH