



## KEY FEATURES

- Intel VIA® C7 2.0GHz w/ 128KB L2 Cache
- Microsoft® Windows XP or POS Ready
- 160GB SATA HDD
- 1GB DDR2 memory
- Durable 15" touch screen
- Energy efficient fan-free design
- Advance exchange (optional)
- Onsite Service (optional)
- Private label front bezel logo (option)

## KS6215 Series

### Posiflex Fan-Free KS6215 Series

The KS6215 is our fan-free, high performance POS terminal that is available at a very attractive price point that you will love. Not a limited offer, the KS6215 is a standard product featuring our patented aluminum chassis for maximum heat dissipation, a 2.0GHz CPU, Microsoft Windows XP or POS Ready or our special value bundle with Windows Embedded for Point of Service and a 2-track MSR. Available in a desktop configuration which easily converts to a wall mount solution. The KS6215 is ideally suited to end users looking for value and an attractive price with no compromise on quality. Call today and find out how the KS6215 can boost your sales and help GROW your bottom line.

**For more information call 800-354-9776 today!**



© 2010 Posiflex and the Posiflex logo is a trademark of Posiflex Business Machines, Inc. All other brand and company names are the property of their respective owners.

**POSIFLEX™**  
Be the Pioneer, Be the Leader



# Specifications

Function	KS6215
Processor	VIA C7 2.0GHz
Memory	Standard 1GB, DDR2 SDRAM SO-DIMM x 1
VGA Memory	16MB - 64MB (shared)
Power Supply	12V DC power adaptor, 80W
Housing	Aluminum die casting
Speaker	Built-in
OS Support	Microsoft® Win XP Pro / POS Ready / WEPOS
Safety Certifications	FCC-A, CE-A, RoHS WEEE
Display	
LCD	15" LCD, 200nits, 1024 x 768 XGA
Touch Sensor	Resistive
Touch Controller	USB interface mouse emulation
Tilt Adjustment	From 17.5° to 76.5°
Expansion	
Storage Device	160GB SATA HDD
Mounting Option	Desktop or wall mount (wall mount bracket sold separately)
Connectivity	
Audio Port	2 Watt audio output built-in
LAN Port	1 x 10/100 Base T Ethernet
Parallel Port	1 x SPP / EPP / ECP
Serial Port	2 x DB9, each with +5V
UPS Port	N/A
USB Port	4 x USB 2.0 + 1 proprietary port for SD-402
PS/2 Mouse Port	N/A
KB Port	N/A
CR Port	1 x, for single cash drawer, 12V DC
Environment	
Operation Condition	0°C ~ +40°C (32°F ~ +104°F), 20% RH ~ 80%RH, non-condensing max, wet bulb 26°C (78.8°F)
Storage Condition	20°C ~ +60°C (-4°F ~ +140°F), 10°C ~ 80°C non-condensing max, wet bulb 28.9°C (84.0°F)
Options	
2nd LCD Display	LM6101B
Customer Display	PD2501: 11mm, 2x20 VFD display, 5x7 dot matrix, RS232 interface PD2602: 9mm, 2x20 VDF display, 5x7 dot matrix, RS232 or USB interface PD305: 9mm, 2x20 LCD display, 5x7 dot matrix, RS232 or USB interface PD2604U00EFP: 2x20 VFD display, 9mm characters, USB (Rear Monitor Mount) PD3100X00EEP: 2x20 LCD display, 9mm characters, USB (Rear Monitor Mount)
SD-402 Magnetic Stripe Reader	Optional 2-track or 3-track MSR with/without Finger Print Sensor

## KS6215 Main Board Interface Diagram



## Customer Displays



## About Posiflex

Posiflex has four primary objectives - provide revolutionary technology, reliable quality, reasonable pricing and recognized service. As a 25 year design and manufacturer of Point-of-Service (POS) and industrial touch terminals, Posiflex has over 30 patents awarded for innovative design as a POS pioneer, and leader. In partnership with software application companies, Posiflex's products are sold worldwide through VARS and distributors to various vertical industries. Posiflex's comprehensive suite comprises of a wide range of peripherals, terminals ranging from small footprint electronic cash register replacements, to POS terminals, to robust back office file servers in our two ISO 9001/9002/ 14001 certified facilities.