

KEY FEATURES

- Intel® Atom™ 1.8GHz Dual Core w/ 1MB L2 Cache
- Die-Cast Aluminum Alloy Housing for maximum heat diffusion
- Operates in a wide range of environments and temperatures. 14° F ~ 122° F (-10° C ~ 50° C)
- Up to 4GB of DDR3 Memory
- Precisely designed, with strict revision control to maximize the system's lifecycle
- Liquid/Splash Resistant
- Optional RAID 1
- Stringent third party HALT / HASS tested for extensive temperature cycling, vibration, drop, shock, static electricity and emission tolerance



KS7200 Series

About Posiflex

Designer and manufacturer of Point-of-Service and industrial touch terminals

Revolutionary technology, reliable quality, reasonable pricing and recognized service

Delivers reliable terminals for maximum uptime and lower total cost of ownership

Comprehensive suite of peripherals and services

Over 25 years of excellence

Global presence

Over 30 patents for innovation

Two ISO 9001/9002/14001 Certified Facilities

Enhanced Power-Performer

Within the comprehensive KS family of fan free terminals, the new KS7200 offers a good combination of price and performance.

Featuring Posiflex's patented aluminum chassis for maximum heat dispersion, a 1.8GHz Dual Core CPU, and support of Win 7 Pro among other operating systems, the KS7200 offers great performance, reliability and compatibility.





Equipped with optional RAID 1, a valuable feature for a point-of-sale or business critical data collection, this redundancy safeguards your important data to ensure maximum uptime. Being fan-free, the KS7200 reduces energy consumption, and eliminates a potential point of mechanical failure, reducing service costs.

KS7200 is designed to deliver without compromising performance, aesthetics and quality. Adaptable, Scalable, Profitable – designed with your business in mind.

For more information call 888-968-1668 today!

Specifications

SPECIFICATIONS		KS7200	AVAILABLE SERVICES
Processor	Intel® Atom™ D525 1.8GHz Dual Core, 1MB L2 Cache		<ul style="list-style-type: none"> • Standard and Extended Warranty Extend your depot warranty up to 5 years. • Advance Exchange We ship overnight replacement equipment directly to your business. You return the faulty unit to Posiflex. • OnSite Service Expert technicians will efficiently handle the complete equipment swap and return process. • Regional Repair Depots Three regional depots assure fast turn-around time on repairs. • Post Warranty Support Spare parts, in addition to a flat rate repair program, for post warranty needs. • Installation Services Let our nationwide network of experts stage and install your equipment. • OEM Design and Integration Our Product Development Team helps design equipment, for custom hardware applications.
System Memory	DDR3 800 MHz, SO-DIMM socket x 1 (2GB Default)		
Maximum Memory	4GB		
Power Supply	12V DC Power adaptor, 60W		
Storage Device	2.5" SATA 160GB HDD or SSD Kit (optional)		
Supported OS	POSReady 7 (32 or 64 bit) / WinXP Pro / Win7 Pro (32 or 64 bit) / Linux		
DISPLAY			
LCD	(15") TFT LCD, 1024x768 (17") TFT LCD, 1280x1024		
Touch Function	5-Wire Resistive or Infrared, USB Interface		
Brightness Control	Digital Push Button		
Tilt Adjustment	15° to 70°		
PHYSICAL DIMENSIONS			
Dimensions (WxDxH)	(15") 14.76" x 15.20" x 15.55" (17") 16.14" x 14.92" x 11.77"		
Weight (Pounds)	(15") 17lbs (17") 20lbs		
CONNECTIVITY			
LAN Port	1 x RJ-45 10/100/1000 Base T-Ethernet		
Serial Port	2 x 9-pin male d-sub, 2 x RJ-50 (5V/12V support on COM1/COM2/COM3/COM4)		
Backup Battery	Optional		
RAID 1	Optional		
VGA Port	1 x 15-pin female d-sub RGB analog (12V support for Posiflex LCD Monitors)		
CR Port	1 x RJ-11 port controls 2 cash drawers (max)		
Standard USB Port(s)	6 x USB 2.0 Type A port, (4 x on I/O panel, 2 x in side cover)		
Parallel Port	Optional (with P/N 21862033420)		

PERIPHERALS			
Magnetic Stripe Reader - SD402 Biometric or Encrypted options 	Rear Mount Display - PD2604 2 x 20 Character VFD* 	Thermal Printer - PP8000 80mm Wide, Printing Speed: 220mm/second 	Cash Drawer - CR6300 Printer Driven and USB options available 

*Vacuum Fluorescent Display

See www.PosiflexUSA.com for a complete line of peripherals

POSIFLEX™
 Be the Pioneer, Be the Leader
 30689 Huntwood Avenue
 Hayward, CA 94544
 Toll-free: 888.968.1668
 Phone: 510.429.7097
 Fax: 510.475.0982
 E-mail: sales@posiflexusa.com
www.posiflexusa.com

