

MF-2350 Mobile Terminal

- All-in-one enterprise handheld solution
- WLAN, Bluetooth, and GPRS communication options
- Integrated thermal printer & magnetic card reader
- Built-in barcode scanner (option)
- Built-in RFID reader (option)
- Built-in IC smart card reader (option)
- Built-in fingerprint reader (option)
- Built-in camera (option)
- Built-in GPS (option)



MF-2350
Mobile Terminal
Grasp mobility
in your hand

MF-2350~Grasp mobility in your hand

MF-2350 is the new flagship all-in-one mobile POS from Partner Tech. MF-2350 is packed with features, and yet retains a slim body with ruggedized design.

Standard model includes 2" thermal printer, 3-track magnetic card reader, wireless 802.11b/g, and Bluetooth. Optional functions are IC card reader, barcode scanner, GSM/GPRS, camera with LED flash, RFID, GPS, and fingerprint scanner.

With such a complete feature set, MF-2350 is simply the best handheld for your business environment.



MSR IC card



2" Thermal printer with easy drop-in paper




Camera LED flash Barcode scanner



Fingerprint reader



Cradle with USB, RS-232, and spare battery charging slot



SIM card SAM slots microSD

CPU	Intel® Monahan™PXA320 624 MHz processor
Operating System	Microsoft®Windows™CE.NET 5.0
Display	3.5" TFT LCD with Touch Screen, 260k Color, 240*320
Memory	256MB Flash, 128MB SDRAM
Communication	WiFi 802.11b/g Bluetooth 2.0 class 2
Telecom standards(option)	Quad-band GSM/GPRS
Printer	2 inch (58mm) thermal printer, 600 dots/sec (75mm/sec), Roll φ 30, 10M
MSR	ISO7811 – Track 1,2,3 support (Bi-directional)
IC card (option)	ISO7816 – EMV2000 Level 1, 2 certified (1 * ID-1 full size card-slot, 3 * ID-000 SAM slots)
Barcode scanner (option)	1D Laser / 2D Imager
RFID (option)	13.56 MHz
GPS (option)	SiRF III
Camera (option)	2 Megapixel with LED Flash
Fingerprint sensor (option)	Swipe electric field sensor, 128x8 pixels at 500ppi
Extension slot	microSD card (supports SDHC)
Interface	USB 1.1 Host & Client
Other	Earphone / Microphone jack Speaker Integrated microphone Vibrator motor
Environmental	Operating temperature: 0 °C to 40 °C Storage temperature: -20 °C to 60 °C
Battery	Rechargeable Li-ion battery 7.4V 1800mAh
Power adaptor	Input: 100V to 240V AC 50/60Hz 1.2A Output : 9.5V DC 3A
Dimensions (WxLxH)	76.2 * 220 * 37 mm
Weight	Full feature model 545g (including battery)
Cradle	RS-232 Serial port USB port Spare battery charging slot
Accessories	Hand strap Leather carrying case with shoulder strap Car charger

*specification subject to change without prior notice

PARTNER
CARE · TRUST · RESPONSIBILITY

Partner Tech Corporation

Taiwan TEL:+886-2-29188500

FAX: +886-2-29153405

E-mail:sales@partner.com.tw

USA TEL:+1-949-598-1888

FAX: +1-949-598-0088

E-mail:sales@partnertechcorp.com

Europe TEL:+49 (0)40 450 635-0

FAX: +49 (0)40 450 635-130

E-mail:info@partner-tech.eu

UK TEL: +44 (0)1928 579 707

FAX: +44 (0)1928 571 308

E-mail:sales@partnertech-uk.com

China TEL: +86-21-67696667

FAX: +86-21-67696699

E-mail:sales@partnertech.com.cn

