



The Most Reliable Portable Printers.®

PrintPAD™ Portable Thermal Printer (Symbol®-compatible)

The PrintPAD portable thermal printer works in the most rugged environments to enable the production of hardcopy back-ups of digital information and signature printing, as well as the generation of receipts, tickets and labels for a variety of applications.

This innovative one-piece printer system consists of a 4.41 inch (11.2 cm) wide thermal printer in a rugged case and an embedded communications charging cradle designed for use in a number of different applications with a variety of Symbol hand-held computers.

Application Functions

Beverage & Food Sales: Generate up to 2,240 – 6" (15 cm) receipts with graphics and logos.

Field Service: Print work summary reports at the point-of-service.

Law Enforcement: Generate citations or tickets at the roadside.

Route Accounting & Direct Store Delivery (DSD): Print real-time information such as inventory-level data at the customer site or in the warehouse.

Rugged Mobile Point-of-Sale (POS): Scan items, take credit card payment and issue a customer receipt anywhere on the premises (requires optional insertion magnetic stripe card reader).

Proof of Delivery: Print high-resolution signatures.

Transportation & Logistics: Print compliance shipping and inventory labels.

Designed for Comfort and Ease of Use. The PrintPAD, with integrated carry strap, is designed for maximum user comfort. PrintPAD simply "wakes up" automatically when data is received so there are no buttons or switches required for operation. After printing, the PrintPAD returns to "sleep" mode to conserve battery life without any user intervention.

Mission-Critical, Global Mobility Solutions. Meet mobile application challenges with the PrintPAD Series one-piece printing solution. To ensure that the PrintPAD meets your language needs today and tomorrow, any international character set can be added.

Rugged and Reliable. With uncompromising standards, the PrintPAD was engineered throughout to withstand even the most punishing portable applications. It can take all the bumps and knocks inherent in the mobile workplace. Its rock solid print mechanism is proven to provide years of service where other printers fail. The full one year warranty, even on the printhead, offers peace of mind with our promise to stand behind every product we sell.



PrintPAD™

“Every one of the original O’Neil printers deployed six years ago is still out in the field. We’ve added units because we are growing, but we’ve never replaced any. That’s quite a testament.”

Mr. Bob Travatello
Chief Information Officer
Blue Rhino, Inc.

► PrintPAD™ for Symbol® MC 9000

The newest member of the PrintPAD Family is the 9000 model, which includes three important new features. DEX capabilities are available in the PrintPAD 9000, allowing the PrintPAD to communicate via DEX connections with no special software or mechanical switches. This elegant solution makes DEX communications fast and easy. The PrintPAD 9000’s external charge port allows the printer and the Symbol MC 9000 hand-held to be easily charged in the truck or settlement room, while the PrintPAD 9000’s external LEDs allow users to quickly determine the printer’s charge status.



Standard Features at a Glance

- Supports Symbol® SPT 1700, SPT 1800, PPT 2700, PPT 2800, PDT 8000, PDT 8037, PDT 8046, PDT 8056, PDT 8100 and MC 9000 (monochrome and color) hand-held computers.
- Prints 2,240 – 6" (15.2 cm) receipts on a single charge.
- Includes an 80-column font for invoice printing.
- Powered by two 2200 mAH-capacity Lithium-ion batteries with an optional AC or cigarette adapter for occasional simultaneous battery recharging in both the printer and mobile computer.
- Automatic and user-definable settings extend battery life.
- Supports international character sets, graphics and any Bitstream® font or language (for worldwide applications).
- Easy Print® protocol supports all popular bar codes, lines, boxes, graphics, system status, memory, formats and fonts.
- Supports the printing of 1D and 2D bar codes.
- Optional Insertion Magnetic Stripe and Smart Card Reader.



PrintPAD

Specification Highlights PrintPAD™ Portable Thermal Printer (Symbol®-compatible)

Physical Characteristics	
Dimensions	
PrintPAD for:	
1700/1800/2700/2800	13" x 8.25" x 2.125" (33 x 21 x 5.4 cm)
8000/8046	13" x 8.25" x 2.125" (33 x 21 x 5.4 cm)
8037/8056	13" x 8.25" x 2.125" (33 x 21 x 5.4 cm)
8100	13" x 8.25" x 2.125" (33 x 21 x 5.4 cm)
9000	13.375" x 9.75" x 3" (34 x 24.8 x 7.6 cm)
Weight	
PrintPAD for:	
1700/1800/2700/2800/8100	printer only: 28.16 oz (0.798 kg) with batteries & paper roll: 44.0 oz (1.247 kg)
8000/8046	printer only: 31.05 oz (0.880 kg) with batteries & paper roll: 43.02 oz (1.220 kg)
8037/8056	printer only: 28.6 oz (0.811 kg) with batteries & paper roll: 46.4 oz (1.315 kg)
9000	printer only: 40.1 oz (1.137 kg) with batteries & paper roll: 56.5 oz (1.602 kg)
Drop Specification	4 ft (1.2 m) (tested with terminal)
User Environment	
Operating Temperature	4° F to 122° F (-20° C to 50° C)
Storage Temperature	-40° to 158° F (-40° C to 70° C) (without hand-held computer)
Charging Temperature	41° F to 104° F (5° C to 40° C)
Relative Humidity	10% to 90% non-condensing
ESD Protection	8 kV Air, 4 kV contact
Communications	
Serial	RS-232, up to 38.4k baud
Cradle	Standard 1700/1800/2700/2800/8000/8037/8046/8056/ 8100/9000 interface connector
Print Technology	
Printhead	832 dots across, 203.2 dpi (8 dots/mm)
Printhead Life	400,000,000 dot lines @ 25%
Print Speed	Up to 2" per second
Media	
Type	Direct thermal paper, labels
Capacity	
1700/1800/2700/2800/8000/ 8037/8056/8046/8100	1.5" maximum roll diameter
9000	2.25" maximum roll diameter
Width	4.41" (11.2 cm)

Power Source	
Battery	7.2V Lithium-Ion (Li-Ion), 2200 mAh (two batteries for a total of 4400 mAh)
DC Input 1	(AC Adapter) 12-15V, built-in spike and surge protection
Battery Characteristics	
Type	7.2V Lithium-Ion (Li-Ion), 2200 mAh (two batteries for a total of 4400 mAh)
Endurance	13,440" or 2,240 – 6" invoices
Battery Life	56% of original capacity after 500 cycles
Printer Recharging	4-5 hours from AC adapter or cigarette lighter adapter
Hand-Held Recharging	Approximately 3 hours (depending on hand-held model) from AC adapter or cigarette lighter
Fonts & Languages	
Memory Capacity	Flash/RAM Memory: 4/1 Mbit
Standard Fonts	5.5CPI, 7.2CPI, 10.2 CPI, 10.7CPI, 15.6CPI, 18.5CPI, 20.4CPI, 22.6CPI & 34.0CPI (additional fonts available)
International Characters Available	Arab-T, Arab-S, Arab-E, Asian-A, Asian-B, shiftJIS, Greek, OCRA, OCRB, Unicode subset including Latin & Thai (additional international characters available)
Bar Codes	Prints 1D and 2D bar codes
Graphics	Supports storage of graphics/logos in Flash memory and transient "print once" graphics
Agency Approvals	
FCC B, CE, C-Tick, E-Mark	
Warranty	
1 year (including printer case and printhead*)	
Options / Accessories	
<ul style="list-style-type: none"> • 3" Spindle Bracket • AC Adapter • Battery • Cigarette Lighter Adapter • Cleaning Cards • Cleaning Kit • DB9 F Download Cable 	<ul style="list-style-type: none"> • DC Power Extension (not available for 9000) • DEX Cable (MC 9000 DEX Only) • Hand Strap • Magnetic Stripe/Smart Card Reader • Paper • Shoulder Strap

* When used with approved media grades.

PrintPAD™ and Easy Print® are trademarks of O'Neil Product Development, Inc.

Specifications are subject to change without notice. All product and company names are trademarks, service marks or registered trademarks of their respective owners.

Copyright 2005, O'Neil Product Development, Inc.
Part# 110171-001a Rev. 2 7/05 Made in the U.S.A.



email: info@oneilprinters.com

WWW.ONEILPRINTERS.COM

World Headquarters

O'Neil Product Development
8 Mason
Irvine, CA 92618-2705
Ph: 949.458.0500
Fx: 949.458.0708

AustralAsia

1/8 Railway Terrace
Dutton Park QLD 4102
Australia
Ph: +61 7 3255 3360
Fx: +61 7 3255 3365

EMEA

6 Joplin Court, Crownhill
Milton Keynes MK8 0JP
United Kingdom
Ph: +44 (0) 1908 635360
Fx: +44 (0) 1908 635361