

PT-5900 Special Feature

- Intel Atom CPU 1.8GHz
- Low power consumption
- 1GB DDR 2 memory support up to 4GB




PT-5900 Economic Touch Terminal

PT-5900 Touch Terminal

PT-5900 uses the latest ATOM technology to ensure high processing performance. It is equipped with top-rated and energy-efficient ATOM D425 CPU. With compact construction and elegant design, PT-5900 makes it perfect space-saving terminal. Integrated with 15" touch screen, it is the best choice for entry level POS terminal


PT-5900 is also practically in design, as the flexible monitor can be adjusted to meet the requirements of any workplace. The system can be easily match with specific needs of integrated peripherals such as Dual Screen, MSR, IC card reader, RFID reader, 2 x 20 rear customer display, iButton, KB-32 keyboard, and fingerprint reader.



15-90 degrees tilt angle



Support Dual Display
15" or 11.6"



Spill proof design



Support Pole mount Dual



Quick release latch design
for easy maintenance



2 x 20 VFD Rear Display

Item	PT-5900
CPU Type	Intel® Atom™ processor D425
Chipset	Intel® NM10 Express
LCD	15" Active TFT color LCD, resolution 1024 x 768
Touch	5-wire Resistive touch (USB Interface)
Memory	1GB DDRII 800/667 DIMM (up to 4 GB)
Ethernet	Gigabit 10/100/1000 Mb/s
Storage	2.5" Type SATA HDD 160GB
I/O Interface	3 * COM Ports 1 * DB-15 VGA Port 1 * DB-25 for LPT Port 1 * PS/2 Keyboard Port 1 * PS2 Mouse Port 1 * RJ-45 LAN Port with activity/ link and Speed LEDs 3 * Audio Ports (1 * Line-in, 1 * Line-out, 1 * MIC-in) 4 * USB 2.0 Ports 1 * DC +12V Power Adaptor Connector
Optional Peripherals	3 tracks magnetic reader Customer display module (2 x 20 VFD) Biometric Reader, Smart Card Reader, I-Button, RFID reader KB-32 (32-Keys Keypad)
Operation System	Windows 7, Windows XP, XPe, Linux (ubuntu, Fedora) , WEPOS, POSReady,
Power Supply	AC100~240V/DC12V, 7.5A, 90 watt power adaptor
Dimensions	360mm (W) x 246mm (D) x 315mm (H)
Operating Temp.	0°C ~ +45°C
Storage Temp.	-20°C ~ +60°C
Humidity	15%~80%
Certification	CE/FCC Class A, CB, VCCI, 3C, BSMI



Partner Tech Corporation

Taiwan	TEL:+886-2-29188500	FAX:+886-2-29153405	E-mail:sales@partner.com.tw
USA	TEL:+1-949-598-1888	FAX:+1-949-598-0088	E-mail:sales@partnertechcorp.com
Europe	TEL:+49 (0)40 450 635-0	FAX:+49 (0)40 450 635-130	E-mail:info@partner-tech.eu
UK	TEL:+44 (0)1928 579 707	FAX:+44 (0)1928 571 308	E-mail:sales@partnertech-uk.com
China	TEL:+86-21-67696667	FAX:+86-21-67696699	E-mail:sales@partnertech.com.cn
Korea	TEL:+82-2-2090-7559	FAX:+82-2-2090-7558	E-mail:adams_c@partnertech.com.cn

