

PT-6200 All-In-One POS Terminal Features:

- Elegant, compact and fanless design
- Choice of 10.4" or 12" touch screen
- Integrated Triple track MSR, Thermal Printer, 2x20 VFD Customer display
- Modular design for easy maintenance
- Base easy cable management
- Open architecture



**PT-6200 Series
All-In-One POS Terminal**



The complete POS answer for small to medium businesses

The Partner Tech PT-6200 Series All-In-One terminals are the complete solution for small to medium sized businesses. An affordable and user friendly integrated terminal, the PT-6200 Series terminals significantly simplifies the day to day workflow of busy service environments. The space saving compact base, embedded 80mm thermal printer, touch screen and integrated customer display combine to make a feature rich Point of Sale terminal suited for a space-conscious environment.

All-In-One

- Integrated VFD Customer Display
- Integrated Thermal Receipt Printer
- Integrated 3-Track MSR
- Touch Screen LCD



80mm Thermal receipt printer



Triple track MSR Reader



Rear VFD Customer Display



10.4" TFT Touch Screen



12.1" TFT Touch Screen



Modular Design for easy maintenance

PT-6200 Series Specifications

	PT-6200	PT-6212
Processor	Intel Celeron-M Processor @ 600MHz	Intel Celeron-M Processor @ 1GHz
Memory	512MB	1G
Display	10.4" TFT-LCD	12.1" TFT LCD
Resolution	800 x 600	800 x 600 or 1024 x 768
Touch Screen	5-wire Resistive touch	
LCD Brightness	250 nit (w/o touch)	
Network	10/100/1000Mbps onboard Ethernet controller	
Storage	SATA 3.5" 80GB hard drive	
I/O Interface	<ul style="list-style-type: none"> • 4 * COM ports • 1 * RJ11 port (+24V) • 1 * PS2 Keyboard port • 1 * RJ-45 LAN port • 4 * USB ports • 1 * DC +12V 	<ul style="list-style-type: none"> • 4 * COM ports • 1 * RJ11 port (+24V) • 1 * PS2 Keyboard port • 1 * RJ-45 LAN port • 4 * USB ports • 1 * DC +12V • 1 * VGA port
Operation System	WEPOS/POSReady/Windows 2000/CE. Net/Linux	
Power Supply	AC 100V~240V/DC12V/12.5A 150 watt power adaptor	
Temperature.	Operating Temperature: 0~40 degree C Storage Temperature: -20~60 degree C	
Humidity	Operating Humidity: 15% ~ 80% Storage Humidity: 15% ~ 80%	
Dimension	Physical: 328mm (W) x 289.3mm (D) x 246.8mm (H)	
Integrated Peripherals	<ul style="list-style-type: none"> • Triple track magnetic card reader • Customer display module • 80mm Thermal receipt printer with cutter and control board 	
Color	White or Dark Charcoal	
Option	4G uSSD	4G uSSD, RFID Reader, WLAN

Partner Tech USA Inc.
51 Parker
Irvine, CA 92618
Tel: (949) 598-1888
Fax: (949) 598-0088
www.PartnerTechCorp.com

