

PARTNER

CARE . TRUST . RESPONSIBILITY

SG 15+ and SG 20 Price Checkers

- Multifunctional information display point
- Optional colours
- Optional WiFi and Wireless



Scantech ID
Be prepared

Partner Tech UK Corporation
www.partnertech-uk.com

SG 15 +

The Shuttle SG-15 + is an entry level, small and attractive price checker with the latest technology. Interfacing is either through Wireless RF or hard wired Ethernet. The bright display has, depending on the font set, 3 or 5 lines and can display up to 20 characters per line. The design of this product makes it ideal for different environments. This flexibility of installation is enhanced by the optional Power-over-Ethernet.

Specification	
Physical Characteristics	95 (D) x 131 (W) x 181 (L) mm
Display	High-bright blue – white, 128 x 64 pixels
Interfaces	Ethernet 10/100 Base – T interface, PoE IEEE 802.3af (optional), 802.11 b/g/n using an optional mini-PCI card, WAP encryption (WPA – 1, WPA – 2 personal & enterprise) (optional)
Light source	650 nm visible laser diode or red LED
Depth of field	200 mm (= maximum reading distance)
Scan rate + pattern	Omni – directional laser scanner: 1350 scans/sec. CCD scanner: 270 scans/sec.
Barcode types	EAN/UPC/JAN + Add-on, Code 128, EAN 128, Code 39 (+ full ASCII), Code 93, Code 32, Codabar, Interleaved 2/5, GS1 Databar, ISBN
External connection	AUX port (RS-232) for connection of a handheld scanner
Audio	Speaker
Environmental	Operating Temperature: 0°C - 40°C Humidity: 20% - 95% (non-condensing)
Regularity of Compliance	CE, FCC, and RoHS
Colours	Black, Silver
Options	2D Scan engine, Exit Gate



SG 15+



SG 20

SG 20

The SG-20 is a multifunctional customer information terminal and guarantees exact product information. It provides an excellent scanning performance in combination with a large and full graphical LCD display to ensure an easy communication. The SG 20 helps to sustain the relationship with the customer and enables the retailer to effectively provide additional information. The customer can retrieve specific information on actual pricing of products, total sum of purchases, bonus points status, discounts and special offers.

Specification	
Physical Characteristics	298 (H) x 181 (W) x 100 (D) mm
Power Supply Voltage	100-240 V ac, 50/60 Hz
Display	Back Lit STN graphical 240x128 pixels
Interfaces	RS232, RS422, RS485 and optional Ethernet or WIFI
Light source	630 – 670 nm visible laser diode
Depth of field	250 mm (= maximum reading distance)
Scan pattern	Omnidirectional
Barcode types	EAN/UPC/JAN + Add-on, code 32 (Ital. Pharmacode) Code 128, EAN 128, Code 39 (+ full ASCII), Code 93, Codabar, Interleaved 2/5
Environmental	Operating Temperature: 0°C - 40°C Humidity: 20% - 95% (non-condensing)
Regularity of Compliance	CE, FCC, and RoHS
Laser Safety	IEC 825-1 (1993) Class I, U.S. 21CFR1040 Class IIA
Colours	Black, Silver, Red
Options	Separator Box, Exit Gate



Partner Tech Corporation

UK
T: +44 (0) 1928 579 707
F: +44 (0) 1928 571 308
E: sales@partnertech-uk.com

Taiwan
T: +886 2 291 88500
F: +886 2 291 53405
E: sales@partner.com.tw

USA
T: +1 949 598 1888
F: +1 949 598 0088
E: sales@partnertechcorp.com

Europe
T: +49 (0)40 450 635 0
F: +49 (0)40 450 635 130
E: info@partner-tech.eu

China
T: +86 21 676 9 6667
F: +86 21 676 9 669
E: sales@partnertech.com.cn