SOLUTIONS



TSP600 Thermal Printer



The NEW TSP600 thermal printer offers the latest technology advancements, with performance and features comparable to leading thermal products at an entry-level price.

New Features:

- Upgraded Cutter w/ Protective Brush
- Now Supports Star Ethernet v2.0 Interface
- Now Supports Mac OS X w/ USB
- Now Supports OPOS System w/ USB
- Resident Korean & GB Fonts
- USB as Serial (COM) Port Vendor Class Device

The TSP600 is the first low cost, high speed thermal printer to offer two color printing support, drop-in and print paper loading, LogoStore for internal graphics and coupon storage, PLUS recessed cable connectors and tear bar or automatic cutter options. And, it's all packaged in a small footprint. The TSP600 is ideal for POS, credit card and hospitality applications and is backed by our 3 year warranty.

Additional TSP600 features include standard 80 mm paper width (adjustable to 58 mm), dual cash drawer drivers with compulsion support, external power supply, paper near end and paper out sensors, auto printer status, serial, parallel, Ethernet and USB interface options.

Using the TSP600 with your application is quick and easy. Just select Star or ESC/POS™ command mode and watch the printer perform. Do you want to add graphics to your receipt? Enable Logo Printing to add your company brand, logo or advertisement banner to every receipt without changing your software.

For developers, Star Micronics also supports nearly every imaginable driver and POS software standard, including OPOS, JavaPOS and device drivers for open Linux systems. Plus! New high speed graphics drivers for Windows and legacy Windows printer drivers.

Star's revolutionary TSP600 printer – There has never been a better reason to upgrade.

TSP600 Printer Specifications

Print Speed 100 mm/sec, 4 inches/sec, 25 or 33 lines/sec

Resolution 203 dpi (8 dots/mm)

Paper Width Standard: 80 mm (3.15")
Adjustable: 58 mm (2.25")

Optional: 76 mm (3")

Print Width 80 mm paper – 72 mm print width (2.83")

76 mm paper – 72 mm print width (2.83")*
58 mm paper – 52 mm print width (2.05")

 No. of
 80 mm paper - 24, 48 (default), 64 (ESC/POS™)

 Columns
 58 mm paper - 17, 34 (default), 46 (ESC/POS™)

 Bar Codes
 UPC-A, UPC-E, JAN/EAN-8, JAN/EAN-13, ITF.

CODE39, CODE93, CODE128, CODABAR (NW-7)

Paper Paper Near End, Paper Out, Cover Open

Sensors

Reliability

Printer 60 Million Lines
Cutter 0.5 Million Cuts

Interface Serial, Parallel, USB, Ethernet, 9-Pin Serial

Cash Drawer2 drivers w/ compulsionEmulationStar and ESC/POS™

Drivers Windows 95,98,Me,NT, 2000 and XP, Raster Graphics, OPOS, JavaPOS™, Linux and Mac OS X

* Requires 76 mm Paper Adapter (Star Part No. 37995350)

