

Axiohm A470 Series Impact printers



Complete Family

Eight different models to handle receipt, journal and validation transactions.

Simplicity

Easy paper loading and snap-in ribbon cartridge insure fast, trouble free replenishment. Printer set up is through case bottom and requires no tools for access.

Versatility

Both RS232 and parallel interfaces are standard. Intelligent power supply automatically compensates for voltage and frequency changes. Flash Memory allows download of new software from the host.

Flexibility

Two cash drawer outputs with drawer open status are standard. Form stop is user adjustable and form-in delay is under host control. Standard commands for form eject and buffer clear streamline host commands and transactions.

Axiohm™

Compact Point-of-Sale, Banking And Data Logging Printer

The A470 series dot matrix printers are designed with today's need for speed, versatility and small footprint in mind. Ideal for any printing application requiring customer receipts or printing on inserted forms, these printers are available with journal take-up and validation capability, or with an integral

paper cutter. The A470 family prints four lines per second at any pitch, supports 1.2 or 3 ply roll paper and offers up to 17 lines of independent or concurrent multipart form validation. An intelligent power supply meets worldwide voltage and frequency requirements. The A470 Series is an enhancement of a widely

installed and field proven design. It offers a broad range of rugged, high performance printing solutions and unparalleled flexibility at a truly low price.

Axiohm A470 Series Specifications

Specifications subject to change without notice.

Dimensions	
Height	5.57" (141 mm)
Width	6.34" (161 mm)
Length	11.54" (293 mm) R/J/V models 8.3" (211 mm) R/V models
Weight	
	6.50 lbs. (2.95 kg) R/J/V
	5.75 lbs. (2.61 kg) R/V models
	1.12 lbs. (0.51 kg) Ext. Power Supply
Power Supply	
	External 90 to 264 VAC 47-63 Hz
Roll Paper	
Width	3.25" +/- .03" (82.55 mm +/- .76 mm)
Diameter	3.5" maximum (88.9 mm)
Plies	1, 2 or 3 carbonless
Thickness	.003" - .005" per ply (.076 - .127 mm)
Total	.012" maximum (.3048 mm)
Form	
Thickness	.020 maximum (.508 mm)
Total Media	
Thickness	.020 maximum (.508 mm)
Ribbon	
Cartridge Type	
Purple	4 million characters
Black	2 million characters
Interface	
	RS232C (RJ-45 Female Connector)
	Parallel (DB-25S Male Connector)
Baud Rates	
	300 to 19,200
Buffer	
	7 KB
Cash Drawer	
	2 (Separate RJ-11 Female Connectors) Drawer open sense on both
Print Speed	
	Up to 4.2 lines per second
Paper Feed	
	3.47 inches per second
Printhead	
	9 wire impact dot matrix
Graphics	
	Full 9 wire
Line Pitch	
	5.3, 6.0, 6.9, 8.0 LPI under host control
Character Pitch	
	14 pitches, 6 to 24 characters per inch, 16 to 66 characters per line
Character Sets	
	7 international character sets, 244 characters per set
Print Line	
	2.78"
Validation	
	Up to 17 lines on inserted form at 5.3, 6.0, 6.9, 8.0 LPI under host control
Cutter	
	Full cut rotary, 400,000 cut MTBF
Agency Listings	
	FCC Class A, UL, CSA, TUV, (G.S.), CE

Applications

The Axiohm A470 series printers offer a solution to any transaction printing requirement. Cash drawer outputs, flash memory and ease of use make these printers the perfect choice for any transaction application requiring a receipt, an audit trail, printing on a form, such as a cheque, voucher, credit slip or any combination of transaction requirements. The adjustable form stop and user controlled clamp delay lend themselves perfectly to customizing standard printers to meet specific application requirements. The intelligent power supply and selectable fonts are ideal for all international applications. For additional information about the A470 series and how they can increase your profitability, please call us.

Models

A470-4770	Receipt
A470-4771	Receipt/Independent Validate
A470-4772	Receipt/Concurrent Validate
A470-4773	Receipt Cutter
A470-4774	Validate only
A470-4710	Journal/Receipt
A470-4711	Journal/Receipt/ Independent Validate
A470-4712	Journal/Receipt/ Concurrent Validate



For Additional Information About Axiohm Products Contact the Addresses Below or Visit our Website at www.axiohm.com

France 1-9, rue d'Arcueil BP 675 92542 Montrouge Cedex Tel: (33) 1 47 46 78 00 Fax: (33) 1 46 55 13 44	USA 950 Danby Road Ithaca, NY 14850 Tel: (1) 800 732 8950 (1) 607 274 2500 Fax: (1) 607 274 2404	United Kingdom Atlantic Street Altrincham Cheshire WA14 5QJ UK Tel: (44) (0) 161 929 9933 Fax: (44) (0) 161 927 7664	Asia-Pacific PO Box 677 Level 3, 39 Leighton Pl. Hornsby NSW 2077 Australia Tel: (61) (0) 2 9477 1999 Fax: (61) (0) 2 9477 1453	Japan Daichi Tanaka Bilg 7F, 1-1, 2 Chome Yanagibashi Taito-Ku TOKYO 111 Tel.: (81) 338 629 880 Fax: (81) 338 629 770
------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------