

BP72V28RT-3U

External Battery Pack for UPS Systems

Model #: BP72V28RT-3U

- ▶ Extends the runtime of select compatible Tripp Lite UPS systems with 72VDC external battery connector
- ▶ Simple installation; 3U rackmount, tower and stack adaptable
- ▶ 2-year warranty

DESCRIPTION

BP72V28RT-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in rackmount or stacking applications using only 3 rack spaces (3U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy gauge cabling with high current DC connector for simple installation. Additional DC connector enables the daisy-chaining of multiple external battery packs for longer extended run capability. COMPATIBLE UPS SYSTEMS - SU3000RTXL3U, SUINT3000RTXL3U, SU3000XL, SU2200XL and other Tripp Lite UPS systems that specify the use of this battery pack.

KEY BUYING POINTS

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports upright tower installation with optional 2-9USTAND accessory (holds 3 battery packs in tower configuration)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty

TYPICAL APPLICATIONS

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

OPTIONS & ACCESSORIES

- Tower stands: 2-9USTAND
- Extended warranties: 3 Year WEXT3-BP72V, 5 Year WEXT5-BP72V

PACKAGE INCLUDES

- BP72V21RT-3U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

BATTERY

Expandable battery runtime:

Yes, DC connector accepts daisy-chaining of multiple external battery packs for extended runtime operation

DC system voltage: 72VDC
Typical battery lifespan: 4-6 years typical

PHYSICAL

Shipping weight (lbs): 203.9
Shipping weight (kg): 92.57
Unit weight (lbs): 166.45
Unit weight (kg): 75.57
Unit Dimensions (HWD/in): 5.25 x 17.5 x 25
Unit Dimensions (HWD/cm): 13.33 x 44.45 x 63.5
Shipping Dimensions (HWD/in): 11.25 x 23 x 31.5
Shipping Dimensions (HWD/cm): 28.58 x 58.42 x 80.01

Material of construction: Steel

Form factors supported: Supports 3U rackmount installation in 4-post rack enclosures. Compatible with 2 Post racks with optional 2POSTRMKITWM accessory. Upright tower compatible with optional 2-9USTAND accessory.

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2005 Tripp Lite. All Rights Reserved.