

Internet Office UPS System

Affordable full system protection for PCs and workstations



Cisco
Compatible

Cisco Systems Technology Developer Partner

Model #: INTERNET350U

- ▶ Ultra-compact standby UPS offers complete protection for PC and workstations
- ▶ 6 widely spaced outlets (3 UPS/surge, 3 surge-only)
- ▶ USB port, cabling and included PowerAlert monitoring software
- ▶ Single line TEL/DSL modem suppression
- ▶ \$100,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)
- ▶

DESCRIPTION

Tripp Lite's INTERNET350U standby UPS offers complete protection for PCs, workstations and other sensitive electronics in an attractive ultra-compact, mountable housing. Prevents data loss and system downtime by providing battery supported AC output during brownouts and blackout conditions. 6 widely spaced output receptacles accommodate large transformer plugs without blocking outlets. 3 outlets with full battery support and surge suppression protect computers, monitors and other vital system components from loss of power. 3 additional outlets with surge suppression-only are ideal for printers and other accessories not requiring battery support. Single line telephone suppression jacks protect a single directly connected modem, fax machine, cordless phone or other peripheral on a single standard dialup or DSL phone line connection. USB port with PowerAlert monitoring software and cabling enables safe unattended system shutdown in the case of extended power failure. Audible alarm and front panel LEDs offer status information regarding line and battery power operation. 350VA / 180 watt power handling ability supports entry-level PCs for up to 15 minutes during power failures. 2 year warranty. \$100,000 connected equipment Insurance (USA & Canada Only).

KEY BUYING POINTS

- INTERNET350U standby UPS offers complete protection from blackouts, brownouts and surges on both AC and TEL/DSL line connections
- 6 widely spaced outlets accommodate large transformer plugs without blocking outlets
- 3 battery supported outlets protect computer, monitor and vital system peripherals, plus 3 additional surge suppression-only outlets for printers and other system accessories not requiring battery support
- Provides battery derived AC output during blackouts and brownouts
- 350VA / 180 watt power handling ability supports a variety of PCs, workstations and other sensitive electronics
- Supports entry-level PC systems up to 15 minutes during blackout conditions
- Built-in single line TEL/DSL line surge suppression protects modems, fax machines or cordless phones on a single phone line connection
- USB port, PowerAlert software and cabling offer safe unattended shutdown without data loss during extended outages
- Supports Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications
- Hot swappable user battery replacement supported via battery access door
- Space saving, ultra-compact housing fits almost anywhere

TYPICAL APPLICATIONS

- Basic PCs for home / home-office use, network workstations, audio/video equipment, home entertainment systems and other sensitive electronic devices.

OPTIONS & ACCESSORIES

- Watchdog software: [WATCHDOGSW](#)

- USB Hubs: [U222-004-R](#), [U202-004-R](#), [U203-004-R](#), [U205-004-R](#)
- USB Extension Cables: [U004-006](#), [U004-006-R](#), [U004-010](#), [U004-010-R](#), [U005-010](#)
- Dataline protectors: [DNET1](#) [DTEL2](#), [DCATV](#)
- Circuit Tester: [CT120](#)
- Extended warranties: 3 Year [WEXT3-INTERNET](#), 5 Year [WEXT5-INTERNET](#)

PACKAGE INCLUDES

- INTERNET350U UPS System
- PowerAlert Software & USB cable
- Instruction manual with warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview: Ultra-compact standby UPS protects PCs, network workstations and other sensitive electronic equipment from blackouts, surges and line noise. Maintains AC output during blackouts and brownouts starting at 98V. Includes USB monitoring port with cabling, TEL / DSL line surge suppression, surge only outlets and LED indicators. PowerAlert software included.

Voltage compatibility: 120VAC

Frequency compatibility: 60Hz

OUTPUT

Output volt amp capacity (VA): 350

Output watt capacity (watts): 180

Output nominal voltage: 120VAC

Output voltage regulation: BATTERY MODE: PWM sine wave output 115V +/-5%

Output frequency regulation: LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz

Outlet quantity / type: 6 NEMA 5-15R output receptacles (3 with UPS and surge suppression / 3 with surge suppression only)

INPUT

Maximum input amps: 12A / 1440 watts

Input connection type: NEMA 5-15P

Input cord length: 6 ft., 16 gauge

Recommended electrical service: 15A 120V

BATTERY

Full load runtime: 4 minutes (350VA)

Half load runtime: 12 minutes (175VA)

DC system voltage: 12 VDC

Typical battery lifespan: 3-6 years, depending on usage

Battery recharge rate: 2-4 hours to 90%

LEDS ALARMS & SWITCHES

Front panel LEDs: 2 LEDs indicate line power, battery power status

Alarms: Audible alarm beeps at regular intervals to indicate battery backup operation. Alarm also sounds during self-test operation.

Switches: Combination power off / on / self-test push button switch

SURGE / NOISE SUPPRESSION

AC surge suppression:	1170 joules
AC suppression response time:	Instantaneous
Dataline suppression:	Single line TEL/DSL surge suppression with RJ modular connectors (center 2 wires protected, 260V clamping). 1 input jack and 1 output jack. Includes 1 phone cable.
EMI / RFI AC noise suppression:	Yes, >40dB @ 1 MHz

PHYSICAL

Shipping weight (lbs):	10
Shipping weight (kg):	4.5
Unit weight (lbs):	7.7
Unit weight (kg):	3.5
Unit Dimensions (HWD/in):	3 x 10.5 x 5
Unit Dimensions (HWD/cm):	7.6 x 26.7 x 12.7
Shipping Dimensions (HWD/in):	4.5 x 12.5 x 7.75
Shipping Dimensions (HWD/cm):	11.4 x 31.8 x 19.7
Material of construction:	ABS
Form factors supported:	Ultra-compact desk/floor mount
Battery Access:	Hot-swappable batteries are accessible via battery door

ENVIRONMENTAL

Operating Temperature:	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature:	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity:	0 to 95%, non-condensing
Line mode BTU/hr. (Max.):	15.7
Battery mode BTU/hr. (Max.):	53.2

COMMUNICATIONS

Network monitoring port:	Single built-in USB port supports on battery, low battery and power restored messaging. Interface supports timed inverter shutoff after unattended shutdown. Compatible with Tripp Lite's PowerAlert and Watchdog service software
Software and cabling included:	Includes USB cable and PowerAlert UPS monitoring software
WatchDog compatibility:	Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications

LINE / BATTERY TRANSFER

Transfer time from line power to battery mode:	2-4 milliseconds
Low voltage transfer to battery power:	Switches to battery power as line voltage decreases to 98 volts or less. Resets back to line power mode as line voltage increases to 103V or higher.
High voltage transfer to battery power:	Switches to battery power as line voltage increases to 147V or higher. Resets back to line power as line voltage decreases to 143V or less.

CERTIFICATIONS

Certifications:	UL1778 (USA), cUL (Canada), FCC Class B (Emissions), NOM (Mexico), FCC Part 68 / Industry Canada (telecommunications)
------------------------	---

WARRANTY

Optional coverage:	Optional 3 and 5 year on site or factory warranties available for select opportunities, contact Tripp Lite for more information
---------------------------	---

Product warranty: 2 years

Connected equipment insurance (USA and Canada Only): \$100,000 connected equipment insurance (USA and Canada only)

SPECIAL FEATURES

Cold Start: Yes, inverter can be "cold started" to enable temporary AC output during a power failure

Appearance: Attractive black ultra-compact housing

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2005 Tripp Lite. All Rights Reserved.