

Vertical Kit



Vertical Stand



Splash Guard



Buzzer

FAST

The TSP650 has a print speed of 30 RPM (150mm/second)

RELIABLE

Features Reliable Guillotine Cutter. The TSP650 adapted the super reliable mechanism and cutter from the unbreakable TSP100 family

INTEROPERABILITY

Available in Serial, Parallel, Ethernet, and USB.
Works in the following environments: WindowsTM, XPTM, VistaTM, Linux, Mac OSX, OPOS, JavaPOSTM, ESC/POS[®]









TSP650 - Best Value-Driven Printer

Star Micronics has decided to further enhance one of its legacy value-driven thermal printers by introducing the NEW TSP650.

The TSP650 features the best of both worlds by coupling the comfort of legacy products with the speed and connection options demanded today in hospitality environments. The TSP650 has all the new features of the TSP100 series, such as low cost and high performance combined with the ability to work effectively in any environment. Out of the box, the TSP650 can easily be configured in Star Line or ESC/POS® emulation mode and features all interface options including USB and Ethernet due to its plug-in modules. New vertical mounting stand and splash proof cover options help make it one of the most reliable POS printers in the world.

The TSP650 ships with Installation CD (Printer Driver / Manuals), setup guide, wall mount bracket, vertical mount pads, 58mm paper guide, power switch cover and start-up paper roll. With its "drop in and print" paper loading, small footprint and reliable guillotine cutter, the TSP650 is a welcomed addition to POS systems.

In addition, the TSP650 comes with Star's 3-year Limited Warranty, plus optional Extended Services Agreement Policies (Extend-A-Star and Swap-A-Star).

The TSP650 is ideal for retail establishments and restaurants. Demand everything from your receipt printer.

Visit www.starmicronics.com to learn more.





TSP650 Specifications

	The Complete POS Solution!	
Features	Hardware Fast: 30 Receipts per Minute (30RPM, 150mm/sec) "Drop-In & Print" Clamshell Design Reliable Guillotine Cutter Small Footprint Two Color Print Capable Swappable Communication Interface Horizontal & Vertical Use Recessed Cable Connections ESC/POS® emulation supported	Software Logo Utility (Store Logos, Coupons, and Graphics) Memory Switch Configuration Setup Utility Ethernet Interface Setup Utility Virtual Serial Port for legacy applications
Connectivity Note: Connections in bold are supported; grayed-out connection types may be supported by special demand.	9-pin serial 25-pin serial Parallel USB Powered USB Dual 9-PinSerial/USB Ethernet Wi-Fi	Virtual Serial Port to USB Virtual Serial Port to Ethernet
Drivers Note: Drivers in bold are immediately available; grayed-out operating systems may be supported on request.	Windows 98, ME NT 4.0 WEPOS 2000, XP CE XP Embedded VISTA	OPOS Java POS Linux CUPS Mac OSX CUPS
What's Included	Cutter or Tear Bar printer model Installation CD (Printer Driver / Manuals) Setup Sheets Wall Mount Bracket 58mm Paper Guide Power Switch Cover Start up Paper Roll Vertical Kit	
Optional Accessories	External Power Supply (PS60A) Putty or Gray Color Housing Splash Proof Cover (SPC-T100) Integrated Buzzer (BU01-24-A) Vertical Stand (VS-T650)	
Technical Specifications	Print Method: Direct Thermal Print Speed: Print Speed: 30 Receipts per Minute (30RPM, 150mm/sec) Paper Width: 80mm / 58mm Paper Thickness: 0.065 – 0.085mm Paper Diameter: Max 83mm Emulation: Star Line Mode, ESC/POS®	Power: DC24V Resolution: 203 dpi MCBF: 60 Million Lines Cutter: 1 million cuts Dimensions: W=142mm, H=132mm, D=202mm
Warranty	For US and Canada: 3-year Limited Warranty, plus optional Extended Services Agreement Policies (Extend-A-Star and Swap-A-Star)	
For Further Information	Sales: 1-800-782-7636 x107 Technical Support: 1-800-782-7636 x105	Web: http://www.starmicronics.com

