



The SCANTEAM<sup>®</sup> 6100 Series contact bar code scanner is available with Visible Red illumination, optics and housings.

For applications from office automation to shop floor data collection, the SCANTEAM Series wand scanners are the most reliable, cost effective solution to bar code data collection.

# Features & Benefits

# Lightweight, Easy to Hold

Extended use without operator fatigue

# Large Depth of Field

Excellent reading at large tilt angles and through laminates

# **Rugged Construction**

Durable under the most demanding applications

# Visible Red Illumination

Meets requirements for a wide range of bar code labels

# Strong, Flexible Cord

Durable cord that does not interfere with scanning

# SCANTEAM® 6100

### Performance

Output:	Black high; TTL open collector
Aperature:	6 mil, 8 mil
Light Source:	660nm Visible Red LED
Tilt Angle:	0°-35° typical
Depth Of Field:	0.065 in. (1.6mm)
Scan Speed:	2-50 in./sec. (5-127 cm/sec)
Minimum Reflectance Difference (MRD):	37%

# Mechanical/Electrical

Dimensions	
Weight:	3.53 oz. (0.1kg) with standard 6 ft. (1.8m) coiled cord
Length:	7.5 in. (19.1cm)
Diameter:	0.50 in. (1.3cm)-metal
Scanner Tip:	Field replaceable sapphire tip

# **Power Requirements**

Humidity:

Mechanical Shock:

Operating Voltage:	4.5 to 6.0 VDC; up to 100mV peak to peak max	
Operating Current:	35mA typical; optional 16mA typical	
Electrical Connections:	Red Wire - <u>±</u> 5VDC White Wire-Common Braid - Shield (EMI/RFI) Black Wire - Digital Signal Output	
Connector:	9 pin D squeeze-to-release standard; other terminations available	
Cord:	Standard 6 ft. coil cord (1.8m). Longer length coil cords available	
Environmental		
Operating:	-4°F to 122°F (-20°C to 50°C)	
Storage:	-40°F to 158°F (-40°C to 70°C)	

95% Maximum non-condensing

Functions normally after fifty 3 foot drops onto a concrete surface

# Worldwide Offices

Offices Serving North America Skaneateles Falls, NY Tel: (315) 685-8945 Fax: (315) 685-3172 Charlotte, NC Tel: (704) 537-1444 Fax: (704) 532-4191

# Offices Serving Europe, Middle East, and Africa Europe Tel: Int +31 (0) 40 24 24 486 Fax: Int +31 (0) 40 24 25 672 United Kingdom Tel: Int +44 (0) 1 925 240055 Fax: Int +44 (0) 1 925 631280 France Tel: Int +33 (0) 1 461 04111 Fax: Int +33 (0) 1 461 04120

Germany Tel: Int +49 (0) 7 477 151377 Fax: Int +49 (0) 7 477 151378 Offices Serving Asia and the Pacific Rim Hong Kong Tel: Int +852 2511 3050/2511 3132 Fax: Int +852 2511 3557 Japan Tel: Int +813 52127392 Fax: Int +813 32617372 **Offices Serving Latin America** Naples, Florida Tel: (941) 263-7600 Fax: (941) 263-9689

Web Site Address www.handheld.com

Welch Allyn Data Collection, Inc. and Hand Held Products, Inc. ("Hand Held Products") <sup>©</sup>1999-2000, Hand Held Products. All rights reserved. Printed in the U.S.A. Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.