



KEY FEATURES

- Intel Celeron® M 1.86GHz w/ 1MB L2 Cache
- Microsoft® Windows XP or POS Ready
- 160GB SATA HDD
- 2GB DDR2 RAM standard
- CF Memory (option)
- Superior fan-free reliability
- Rugged design for harsh environments
- 15" and 17" models
- Wall mount solutions available
- Energy saving "green" footprint

KS7300 Series

Posiflex KS7300 Series

The KS7300 series offers a powerful, industry-leading, Intel 1.86GHz Celeron M CPU with 1MB L2 cache. This latest addition to the popular fan-free KS Series family combines optimal performance, low power consumption and heat output with ease of maintenance. The "green" footprint allows companies or divisions to meet corporate mandates related to the development of energy saving systems and devices. The KS7300 is available in 15" and 17" resistive or infrared touch options. Both models are configurable to wall mount solutions and are optimized for retail, quick service, full service hospitality, grocery and specialized markets.

For more information call 888.968.1668 today!

Specifications

Function	KS7315	KS7317
Processor	Intel Celeron® M - 1.86 GHz (1MB L2 Cache)	
System Memory	DDR2 667MHz SODIMM x 1, max 2GB	
Default Memory	2GB	
Video Memory	Dynamic video memory up to 224MB	
Power Supply	12V DC power adaptor, 80W	
Housing	Aluminum Alloy	
Speaker	Built-in	
Base Stand	Gen 5	Gen 6
OS Support	Microsoft® Win XP Pro / WEPOS / POS Ready	
Safety Certifications	FCC-A, CE-A, RoHS	
Display		
LCD	15" LCD, 1024 x 768 (XGA)	17" LCD, 1280 x 1024 (SXGA)
Touch Sensor	Resistive or Infrared (Special Order)	
Touch Controller	USB or RS232 interface for IR touch	
Brightness Control	Hardware push button switch control or software control	
Tilt Adjustment	From 15° to 70°	
Expansion		
Storage Device	2.5" 160GB HDD SATA HDD in base or 2.5" 160GB SATA HDD in main unit	
Mounting Option	Desktop or wallmount (wallmount bracket sold separately)	
Connectivity		
Audio Port	2 Watt audio amplifier with internal speaker Mic. in/line out ports	
LAN Port	1 x 100 Base-TX / 1000 Base-T Ethernet	
Parallel Port	1 x SPP / EPP / ECP	
Serial Port	4 x DB9, each with +5V power supply	
UPS Port	1 x, battery health auto-check	
Standard USB Port	6 x, USB 2.0, 4 in I/O panel, 2 in side cover	
Proprietary USB Port	1 x, for side mount option such as SD404	
VGA Port	1 x, sub D 3 x 5 pins, RGB analog	
CR Port	1 x, controls 2 cash drawers (max)	
Environment		
Operation Condition	5°C ~ +40°C (41°F ~ +140°F) 20% RH ~ 80%RH, non-condensing max, wet bulb 26°C (78.8°F)	
Storage Condition	20°C ~ +60°C (4°F ~ +140°F) without UPS battery, -20°C ~ +40°C (-4°F ~ +104°F) with UPS battery, 10%RH ~ 80%RH, non-condensing max, wet bulb 28.9°C (84.0°F)	
Options		
2nd HDD	Yes	
2nd LCD Display	LM6101 Series	N/A
Rear Base Displays	PD2602: 9mm, 2x20 VFD display, 5x7 dot matrix, RS232 or USB interface PD305: 9mm, 2x20 LCD display, 5x7 dot matrix, RS232 or USB interface	
Rear Mount Displays	PD2604: 9mm, 2x20 VFD display, USB PD3100: 9mm, 2x20 LCD display, USB	
SD-404 Magnetic Stripe Reader	Optional 2-track or 3-track MSR with/without Finger Print Sensor	
UPS Battery	2.3 Ahr / 12V, in base stand	
KS7315 Main Board Interface Diagram		

OPTIONS	
	MSR w/ DigitalPersona Fingerprint Biometrics (for 15" & 17")
	Convenient Connectivity - 2 add'l USB ports and brightness control in covered side panel
	PD305B Rear Base Display (for 15" only)
	PD2602 Pole Display (for 15" only)
	LM6101B 2nd LCD Display (for 15" only)
	PD2604 (VFD) or PD3100 (LCD) Rear Mount Display (for 15" & 17")

About Posiflex

Posiflex has four primary objectives - provide revolutionary technology, reliable quality, reasonable pricing and recognized service. As a 25 year design and manufacturer of Point-of-Service (POS) and industrial touch terminals, Posiflex has over 30 patents awarded for innovative design as a POS pioneer, and leader. In partnership with software application companies, Posiflex's products are sold worldwide through VARS and distributors to various vertical industries. Posiflex's comprehensive suite comprises of a wide range of peripherals, terminals ranging from small footprint electronic cash register replacements, to POS terminals, to robust back office file servers in our two ISO 9001/9002/ 14001 certified facilities.

POSIFLEX™

Be the Pioneer, Be the Leader
 30689 Huntwood Avenue
 Hayward, CA 94544
 Toll-free: 888.968.1668
 Phone: 510.429.7097
 Fax: 510.475.0982
 E-mail: sales@posiflexusa.com