

0700L 7-inch LCD

Touchscreen Monitor





Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The Elo 0700L 7-inch widescreen touchscreen monitor is designed to serve as a multifunctional unit with cost and space savings in mind. Whether used as a stand-alone or secondary display attached to a larger device, the 0700L can be applied to any environment, especially where a small screen is required. The 0700L is available with AccuTouch* five-wire resistive touch technology. Utilizing DisplayLink™ technology, the 0700L allows for power, video and touch signal through a single USB cable.

The optional web camera and three-track magnetic stripe reader (MSR), programmable to either HID or keyboard emulation (USB only) offer easy installation by the user, providing an elegant, integrated solution.

Available with AccuTouch five-wire resistive

IPX1 rated as resistant to dripping water; IP54 rated as resistant to particles and liquids

VESA mounting options

0700L 7-inch LCD Touchscreen Monitor

Specifications			
Case/Enclosure/Bezel Color	Black		
Active Display Area	6.1" x 3.4" (154mm x 87mm)		
Dimensions	7.3" x 4.9" x 1.2" (187mm x 126mm x 31mm)		
LCD Technology	Active matrix TFT LCD		
Display Size	7" diagonal		
Native Resolution	800 x 480		
Aspect Ratio	16:9		
Number of Colors	16.7 million		
Number of Touches	Single-touch and non-touch		
Brightness (typical)	LCD Panel: 200 nits; with AccuTouch: 160 nits		
Response Time (Tr + Tf) (typical)	25 msec		
Viewing Angle (typical)	Horizontal: ±70° or 140° total; Vertical: +50° to -60° or 110° total		
Contrast Ratio (typical)	500:1		
Video	USB on Mini-B receptacle		
Input Video	Horizontal Sync frequency: 30KHz; Vertical Sync (frame rate) frequency: 60Hz		
Power	Monitor input power connector: USB Mini-B receptacle; Monitor input power signal specifications: 5V ±5%		
	Power Consumption (Typical): ON (monitor only): 4.5W; SLEEP (monitor only): 2.59W; OFF (monitor only, backlight off): 2.59W		
Mounting Options	VESA 4-hole 75mm mounting interface on rear of unit		
Weight	Unpackaged: 1.3lbs (0.59kg); Packaged: 1.9lbs (0.87kg)		
Shipping Dimensions	8.9" x 6.5" x 3.1" (225mm x 165mm x 80mm)		
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 60°C)		
Humidity (non-condensing)	Operating: 20% to 80%; Storage: 10% to 90%		
Regulatory Approvals and Declarations	RCM; cUL, IC; CE; VCCI; NOM CoC; UL, FCC; CB; RoHS, WEEE; BSMI; KCC		
Warranty	3 years standard		
MTBF	50,000 hours demonstrated		
Other Features	IP1X drip-proof rating; IP54 rated for dust and water protection		
What's in the Box	USB Mini-B receptacle, User Manual CD, Quick Install Guide		

Ordering Information

п	Model	Part Number	Technology	Interface	Surface Treatment	Availability
	0700L	E791658	AccuTouch	USB	Antiglare	Worldwide

Optional Peripherals / Accessories

Part Number	Description
E039290	Magnetic Stripe Reader (MSR)
E548382	Desktop Stand
E160104	Table top stand for 0700, 1002L and I-Series 10-inch
E412148	Bracket Kit for MSR
E750095	Mounting Bracket for Display compatible with the C-Series Touchcomputer
E332358	Mounting Bracket for 0700L as Rear-Facing Display
E075614	CABLE-KIT-2.5 Meter Y-Cable for the 0700L

Extended Warranty Options

Part Number	Description
758588-000	1 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor
930057-000	2 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor
E67295-000	Elo Advance Unit Replacement for Touchmonitors

To find out more about our extensive range of Elo touch solutions, go to **elotouch.com**, or call the office nearest you.

North America Tel +1 408 597 8000

Tel +1 408 597 8000 Fax +1 408 597 8050 elosales.na@elotouch.com Europe

Tel +32 (0)16 70 45 00 Fax +32 (0)16 70 45 49 elosales@elotouch.com **Asia-Pacific**

Tel +86 (21) 3329 1385 Fax +86 (21) 3329 1400 www.elotouch.com.cn **Latin America**

Tel +1 786-923-0251 Fax +1 305-931-0124

elosales.latam@elotouch.com

