

HCH-3010E-CHG Ethernet Charger

Charger Specifications:

Dimensions:

Length: 127.0 mm
 Width: 152.0 mm
 Height: 108.0 mm
 Weight: 400.0 g

Temperature:

Operating (low): 0.0°C 32.0 F
 Operating (high): 40.0°C 104.0 F

Storage (low): -10.0°C 14.0 F
 Storage (high): 50.0°C 122.0 F

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



GTS Batteries

HMC3X00-Li(S) and HMC3X00-Li(H)

Charger Features:

- USB 2.0 port for high speed wired connectivity
- 10/100 Ethernet Port to connect to Local Area Network
- DB9 RS232 full duplex serial port
- Compatible with all protocols supported by the handheld devices MC3000/3100 Series
- No additional driver installation

Trademarks are the sole property of their respective owners.

14.03.21

Single Bay Ethernet Charger for MC3000/MC3100 Series devices and batteries

Designed for users who do not need a second battery: Holds and charges one device.

Supports Lithium Ion and Lithium Polymer chemistries.

Total emulation of the OEM Ethernet multi-slot charger for seamless integration.

Hassle-free mounting: Utilizes same mounting brackets as OEM chargers for easy wall mounting.



Ethernet Connective Port

Made of highly rugged aerospace grade aluminum housing.

Includes power supply and cable.

Can easily be customized to meet your customer's needs.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
 550 Cochituate Road Framingham, MA 01701
 US: 1.800.267.2711 ■ EU: 00800.5390.5390
www.GTSpower.com @GTSpower1

