

# HCH-3060-CHG

## Charger Specifications:

### Temperature Limits:

Operating Range: 0°C to 40°C  
32°F to 104°F

Storage Range: -10°C to 50°C  
-14°F to 122°F

### Dimensions:

Length: 630 mm  
Width: 160 mm  
Height: 108 mm  
Weight: 2500 g

### Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



## Compatible Batteries

HMC3X00-Li(S) GTS Battery  
HMC3000-LAS-Li GTS Battery

- Highest quality cells used
- Longer cycle life
- Extremely rugged
- Rigorous testing



Trademarks are the sole property of their respective owners.

14.05.16

## Maximize the performance with GTS 6-Bay Cradle Charger for the Motorola® MC3000/MC3100 Devices

Made of highly rugged aerospace grade aluminum housing.


Includes power supplies and cable.

Dual-chemistry charger Supports Li-Ion and Li-Polymer chemistries.



More efficiency in less space Charges 50% more batteries in same space as OEM chargers.

Tri-color charging indications A charging LED indicates charging status.



Hassle-free mounting Utilizes same mounting bracket as Symbol® chargers for easy wall mounting.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.  
550 Cochituate Road Framingham, MA 01701  
US: 1.800.267.2711 ■ EU: 00800.5390.5390

[www.GTSpower.com](http://www.GTSpower.com) @GTSpower1

