

# HCH-7003-CHG

## Charger Specifications:

### Temperature Limits:

Operating Range: 0°C to 40°C  
32°F to 104°F

Storage Range: -40°C to 85°C  
-40°F to 185°F

### Dimensions:

Length: 102 mm  
Width: 160 mm  
Height: 56 mm - without  
batteries or devices  
inserted  
Weight: 310 g

### Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



## GTS Batteries

HMC70-Li(22) / HMC70-Li(36) /  
HMC70-Li(38) / HMC70-Li(48)

- Highest quality cells used
- Longer cycle life
- Extremely rugged
- Rigorous testing



Trademarks are the sole property of their respective owners.

14.03.11

## Three-Bay MC70-Li Battery Charger



**Dual-chemistry charger**  
Supports Li-Ion and Li-Polymer chemistries.

**Hassle-free mounting**  
Utilizes same mounting bracket as Symbol® chargers for easy wall mounting.

Made of highly rugged aerospace grade aluminum housing.

Includes power supplies, cables & in vehicle mounting kit.

**Dual-color charging indications**  
A charging LED indicates charging status.



### For Pricing or Additional Information Contact:

Global Technology Systems, Inc.  
550 Cochituate Road Framingham, MA 01701  
US: 1.800.267.2711 ■ EU: 00800.5390.5390  
[www.GTSpower.com](http://www.GTSpower.com) @GTSpower1

