

HCH-7006-CHG

Charger Specifications:

Temperature Limits:

Operating Range: 0°C to 40°C
32°F to 104°F

Storage Range: -40°C to 85°C
-40°F to 185°F

Dimensions:

Length: 165 mm
Width: 159 mm
Height: 66 mm
Weight: 0.54 kg

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



GTS Batteries

HMC70-Li(22) / HMC70-Li(36) /
HMC70-Li(48)

- Highest quality cells used
- Longer cycle life
- Extremely rugged
- Rigorous testing



Trademarks are the sole property of their respective owners.

14.03.12

Six-Bay MC70-Li Battery Charger



Dual-chemistry charger
Supports Li-Ion and Li-Polymer chemistries.

Made of highly rugged aerospace grade aluminum housing.

Hassle-free mounting
Utilizes same mounting bracket as Symbol® chargers for easy wall mounting.

Tri-color charging indications
A charging LED indicates charging status.



More efficiency in less space
Charges 50% more batteries in same space as OEM chargers.

Includes power supplies and cable.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
550 Cochituate Road Framingham, MA 01701
US: 1.800.267.2711 ■ EU: 00800.5390.5390
www.GTSpower.com @GTSpower1

