

HCH-9030-CHG

Charger Specifications:

Temperature Limits:

Operating Range: 0°C to +40°C

Storage Range: -10.0°C to +50°C

Dimensions:

Length: 348 mm

Width: 160 mm

Height: 89 mm

Weight: 900 g

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



Compatible Batteries

HMC9000-Li(24) Honeywell® Battery

- Highest quality cells used
- Longer cycle life
- Extremely rugged
- Rigorous testing



Trademarks are the sole property of their respective owners. The Honeywell® Trademark is used under license from Honeywell® International Inc.

13.06.19

3 Bay Cradle Charger

Made of highly rugged aerospace grade aluminum housing.

Includes power supplies and cable.

Dual-chemistry charger Supports Li-Ion and Li-Polymer chemistries.



More charging in less space Charges 50% more batteries in same space as OEM charger.

Tri-color charging indications A charging LED indicates charging status.



Hassle-free mounting Utilizes same mounting bracket as Symbol® chargers for easy wall mounting.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
550 Cochituate Road Framingham, MA 01701
US: 1.800.267.2711 ■ EU: 00800.5390.5390
www.GTSpower.com

