

HCH-9033-CHG

Charger Specifications:

Temperature Limits:

Operating Range: 0°C to 40°C
 32°F to 104°F
 Storage Range: -10°C to 50°C
 14°F to 122°F

Dimensions:

Length: 420 mm
 Width: 159 mm
 Height: 89 mm
 Weight: 1150 g

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



GTS Battery

HMC9000-Li(24)

- Highest quality cells used
- Longer cycle life
- Extremely rugged
- Rigorous testing



Trademarks are the sole property of their respective owners.

Battery & Cradle Charger for MC9000 Series Devices

Dual-chemistry charger
 Supports Li-Ion and Li-Polymer chemistries.

More efficiency in less space
 Charges three spare batteries plus the batteries in three devices simultaneously and fast

Made of highly rugged aerospace grade aluminum housing.

Includes power supplies and cable.

Tri-color charging indications
 A charging LED indicates charging status.

Hassle-free mounting
 Utilizes same mounting bracket as Symbol® chargers for easy wall mounting.

Can easily be customized to meet your customer needs.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
 550 Cochituate Road Framingham, MA 01701
 US: 1.800.267.2711 ■ EU: 00800.5390.5390
www.GTSpower.com @GTSpower1

