

Android Terminal

T1 Mini 11" with Integrated Printer

The T1 Mini is an 11" wedge style all in one terminal designed from the ground up for simple setup and operation. A built in printer and customer display simplify installation to a single power cable. With its low profile and lightweight design, the T1 Mini is a perfect solution for temporary or seasonal deployments.



ANDROID MARSHMALLOW

Android 6.0 with Google Play services ensure compatibility with your application right out of the box



SPACE SAVING DESIGN

It's low profile design gets out of the way for face to face customer interaction



CLOUD DEVICE MANAGEMENT

Fully customize your user's out of box experience with custom boot screens and pre-installed apps



BUILT IN PRINTER

A built in printer provides quick, accurate receipt prints and easy, single cable setup



PART NUMBER	AND-T1M-2A	AND-T1M-3A	AND-T1M-3B	AND-T1M-3C
CPU	Qualcomm Snapdragon 615 Octa-core			
OS	Android 6.0			
Memory	1GB RAM			
Storage	8GB eMCP Storage			
Expandable Storage	1 x Micro SD, up to 64GB			
Display	11.6" Multi-Touch Capacitive Touch			
Display Resolution	HD 1366 x 768 IPS			
Customer Display	Integrated, 128 x 40 monochrome dots			
Wireless LAN	2.4g 802.11 b/g/n			
Wired LAN	1 x RJ45 Ethernet 100 Mbit/s			
Bluetooth	2.1/3.0/4.0 and BLE			
Speakers	1 @ 1.2W			
Integrated Printer	2" (58mm) Thermal with Tear Bar, 2.8"/sec (70mm/sec)	3" (80mm) Thermal with Auto Cutter, 6.3"/sec (160mm/sec)		
Cellular Radio	N/A		3G GSM (850/900/1900/2100)+WCDMA (850/1900/2100)	
NFC	N/A		Yes, Customer Facing	
Camera	N/A		Yes, Customer Facing	

PORTS	
USB	4 x USB Type A, 1 x Micro USB (Debugging only)
Serial	1 x RJ11
Cash Drawer	1 x RJ12
Audio	1 x 3.5mm Headphone
Power	1 x 4 Pin DIN Locking Connector

PHYSICAL	
Dimension (WxDxH)	11.4" x 11.4" x 3.9" (290mm x 290mm x 100mm)
Weight	4.6 lb (2.1Kg)
Color	Black and Orange
Electrical	AC 100 ~ 240V 1.7A (input) DC 24V / 2.5A (output)

WARRANTY EXTENSION AND UPGRADES	
ZWE-TPC	2-Year warranty extension
ZOE-TPC3	**Next business day protection
ZOE-TPC5	**2-Year warranty extension + Next business day protection

ENVIRONMENTAL	
Temperature	Operating: 32°F to 104°F (0°C to 40°C) Storage: -4°F to 140°F (-20°C to 60°C)
IP Rating	IP54, Splashing Water and Dust Resistant
Humidity	10% to 90% non condensing
Warranty	1-year warranty
Certifications	FCC, CE, CCC

*Actual formatted space will be less, OS and built in apps require space

**Available in USA and Canada.