

## Receipt Printer

## *EVO HiSpeed Thermal*

The EVO HiSpeed Thermal Receipt Printer sets the bar in both speed and reliability. Engineered to operate day-in and day-out in the harshest of environments, the EVO HiSpeed provides the steadfast performance you need. Perfect for high-volume retail and hospitality operations, the EVO HiSpeed features lightning quick receipt printing, JamFree Autocutter Technology, and is backed by the best warranty in the industry.



### Key Features



**Print Speed**

300mm/sec



**Accessories Included**

Power supply and interface cables included



**Paper Loading**

Drop-in easy thermal paper loading



**AutoCutter**

JamFree AutoCutter technology



**Multiple Interfaces**

USB, Parallel, Serial, Ethernet



**Emulation**

ESC/POS and OPOS compatible



**Wall-Mountable**

Convenient mounting capabilities

PART NUMBER	EVO-PT3-1HU	EVO-PT3-1HUP	EVO-PT3-1HUS	EVO-PT3-1HUE
<b>INTERFACE SPECIFICATIONS</b>				
Interfaces	USB	USB/Parallel	USB/Serial	USB/Ethernet
Interface Details	USB 2.0	USB 2.0/IEEE-1.284	USB 2.0/RS232C	USB 2.0/(10/100)
Emulation	ESC/POS Command Compatible			
Print Method	Direct Thermal			
Printing Speed	11.81"/sec (300mm/sec)			
Print Resolution	180 DPI x 180 DPI			
Printing Direction	Unidirectional with Friction Feed			
Sensors	Cover Open, Paper Low, Paper End			
Cash Drawer Port	1 Port, 2 Internal Circuits (24 V, 1 A max)			
Reliability	TPH Life 99.42 miles (160Km) MCBF 60,000,000 Lines			

<b>PAPER</b>	
Type	Thermal Paper
Width	1.9" (50mm) - 3.15" (80mm)
Thickness	0.002" (0.06mm) - 0.0035" (0.09mm)
Roll Diameter	Max 3.27" (83mm)
Roll Core Inner Diameter	0.492" (12.5mm) ± 0.019" (0.5mm)
Character Set	Alpha Numeric Character 95 Extended Graphics 128 x 18 page (1 space per page) International Characters 14
Character/Line	Font A (12 x 24) 42 columns Font B (9 x 17) 56 columns
Barcodes Supported	EAN-8, EAN-13, CODE 39, ITF, UPC-A, CODABAR, CODE 93, CODE 128, PDF 417(2D)

<b>AUTO CUTTER</b>	
Type	JamFree auto-retracting guillotine
Life	1,500,000 Cuts
Cutting Method	Full/Partial Cut

<b>OPTIONAL ACCESSORIES</b>	
EVO-PT3-1CARDS	Serial Interface Card for EVO HiSpeed
EVO-PT3-1CARDP	Parallel Interface Card for EVO HiSpeed
EVO-PT3-1CARDE	Ethernet Interface Card for EVO HiSpeed

<b>PHYSICAL</b>	
Dimension (WxDxH)	6.1" x 8" x 6.1" (155mm x 203mm x 155mm)
Weight	3.7 lbs (1.7 kg)
Color	Black
Electrical	100–240 VAC 50/60 Hz (input) 24 VDC/1.5 A (output)

<b>ENVIRONMENTAL</b>	
Temperature	41°F to 104°F (5°C to 40°C) operating -4°F to 140°F (-20°C to 60°C) storage
Humidity	35% to 80% non condensing (operation) 10% to 90% non condensing (storage)
Warranty	5-year warranty with free *2-day Advance Exchange Service
Certifications	FCC, MIC, UL, CE, CCC, RoHs, NOM
Operating System	WIN XP, VISTA, Win 7, WIN 8, WIN 10, OPOS drivers available

<b>WARRANTY EXTENSION AND UPGRADES</b>	
ZOE-CRW3	*3-Year Overnight Exchange
ZOE-CRW5	*5-Year Overnight Exchange

\*Available in USA and Canada