

Touchscreen Monitor

EVO TM4 TruFlat

The EVO TM4 TruFlat touchscreen monitor features state-of-the-art TruFlat resistive or projected capacitive (PCAP) technology. The zero-bezel design eliminates the frame found on traditional monitors, creating a seamless, smooth surface. The screen is easy to clean and is resistant to water, dust, grease, and food buildup, making it the ideal choice for retail or restaurant settings. The TM4's aluminum alloy frame and stand can withstand the harshest of environments.



Shown with optional MSR

Key Features



Touchscreen

15" (381mm) zero bezel, 5-wire resistive or PCAP touchscreen technology



Touches

Rated at 50 million touches per location



Built In Cable Management

Keeps cords out of sight



Wall Mountable

VEESA mountable for convenient mounting capabilities



IP54 Rating

Resistant to dust buildup and splashing water



Sturdy Die-Cast Aluminum Alloy Frame

Provides bump-free operation



Optional Accessories

Optional integrated MSR, customer display, rear LCD, or biometric reader

DISPLAY

Panel Size	15.0" (381mm) TFT Active Matrix Display
Bezel Type	TruFlat
Touchscreen	EVO-TM4C: 5-Wire Resistive, 50 millions taps per location EVO-TM4D: PCAP ; USB Interface
Max Resolution	1024 x 768
Video Interface	Analog RGB (VGA)
Brightness	250 nits
Colors	16.7 million colors
Controls	Power on/off, auto adjustment (±)
Viewing Angle	160°
Housing	Die-Cast Aluminum

PHYSICAL

Housing	Die Cast Aluminum
Dimensions (w/base) (WxDxH)	14.21" x 9.76" x 13.27" (361mm x 248mm x 337mm)
VESA Wall Mountable	3.9" x 3.9" (100mm x 100mm)
Tilt Angle	0° – 90°
Housing Color	Black
Bezel	TruFlat Zero Bezel
LCD Display	15" (381mm) LED LCD
Touch Technology	Projected Capacitive (P-CAP)

*Available in USA and Canada.

ELECTRICAL

Adapter Output 36W, 12V, 3A

ENVIRONMENTAL

IP Rating	IP54 - Resistant to dust buildup and splashing water
Operating Temperature	41°F to 95°F (5°C to 35°C)
Humidity	5% to 95% non-condensing
Warranty	3-year warranty with free *2-day Advance Exchange Service
Certifications	FCC Class A, CE, LVD, RoHs, NOM

OPTIONAL ACCESSORIES

EVO-MR4	3-Track MSR with USB interface
EVO-RD4-LCD8	Integrated Rear Display, 8.4" (213mm) LCD, VGA
EVO-RD4-LCD8TM	TM4C / LCD8 Conversion Pack with 6' (1.83m) VGA Cable
EVO-RD4-VFD	Integrated Rear Display, VFD
EVO-BR4	Integrated Bio Reader
EVO-XZ4-M100	Universal VESA mount for all POS Terminals and Monitors

WARRANTY EXTENSION AND UPGRADES

ZWE-TPC	2-Year Warranty Extension
ZOE-TPC3	*3-Year Overnight Exchange
ZOE-TPC5	*5-Year Overnight Exchange