

The EVO-MR6 3-track Magnetic Stripe Reader (MSR) is the universal choice for reading magnetically encoded cards. Featuring an integrated gold contact USB interface, the EVO-MR6 is ready to go out of the box. Smooth bi-directional operation ensures a high success rate with every swipe.



Key Features



Strip Reader

Reads card tracks 1, 2, and 3



USB

USB interface



Mounting

Fully integrates to the EVO TP6



Easy Install

Plug'n'play operation

PERFORMANCE

Interface	Cable-free USB
Media Formats	ISO 7811, AAMVA, and other F2F formats
Media Thickness	0.015" - 0.045" (0.38mm - 1.1mm)
Slot Width	0.050" (1.3mm)
Swipe Speed	3 to 60 inches (76 to 1524mm) per second, bi directional
Indicators	Tri-colored LED
Head Life	1,000,000 card swipes

ELECTRICAL

Power	+5V VDC \pm 10%, 50mV ripple max
-------	------------------------------------

ENVIRONMENTAL

Temperature Operating	32° F to 131° F (0°C to 55°C)
Temperature Storage	-22° F to 158° F (-30°C to 70°C)
Humidity	Max 95% non-condensing
Warranty	3-Year Limited
Certifications	ISO 9001, ROHS