

Barcode Scanner

ION Short Range

The ION Short Range is a member of the cost-effective, high performance POS-X ION Series. This barcode scanner is designed to provide an exceptional decoding solution at an extremely low price. The ION Short Range scans most popular 1D barcode symbologies and has a rugged design with no moving parts to withstand daily use. Engineered to be extremely lightweight with a low profile, the ION Short Range is the clear choice for the budget-minded consumer.



Key Features



Decode Capabilities

Reads all standard linear 1D barcodes

٢	
L	
L	
L	
L	
L	

Scan Rate

Reads up to 200 scans/second



Reading Distance 0" to 4" (0mm to 101mm)



Great Entry Level Scanner Cost-effective



Barcode Scanner

ION Short Range

PERFORMANCE

Light Source	Red LED 660 nm CCD
Visual Indicators	Blue LED: decoding successful
System Interface	USB
Depth of Field	0" to 1.2" (0mm to 30mm) 13 mil code
Resolution	4 mil
Scanning Angle	45°
Scanning Distance	0" to 4.0" (0mm to 101mm)
Scan Rate	200 scan lines/second
Print Contrast	Minimum 45% contrast
Light Levels	1000 LUX-5000 LUX

ELECTRICAL		
Input	5 DC ± 5%	
Current	100-120mA	

ENVIRONMENTAL

Temperature	32°F to 122°F (0°C to 50°C) operating -15°F to 140°F (-26°C to 60°C) storage
Humidity	10% to 90% relative humidity, non-condensing
Shock Resistance	Withstands multiple drops from 5' (1.5m)
Warranty	3-year warranty with free *2-day Advance Exchange Service
Certifications	FCC Class-A, CE/ UL, RoHS, NOM

FEATURES

Decode Capabilities	Reads all standard 1D symbologies
Programmable Features	Prefix Code, Length Code, Barcode Type, ISBN/ISSN/CLSI/UK Plessey Conversion, Scanning Mode, Time Out, Baud Rate

WARRANTY EXTENSION AND UPGRADES

ZWE-BMP	2-Year Warranty Extension
ZOE-BMP3	*3-Year Overnight Exchange
ZOE-BMP5	*5-Year Overnight Exchange

*Available in USA and Canada

PHYSICAL

Dimension (LxWxH)	6.3" x 3.2" x 2.0" (160mm x 80mm x 50mm)
Weight	0.2 lb (90 g)
Color	Black
Housing	ABS
Interface Cable	5' USB Interface Cable (included)