

Barcode Scanner

ION Wireless

The ION Linear Wireless is part of the cost-effective, high performance POS-X ION Series. The ION Linear Wireless is equipped with wireless technology that has lower interference rates, and uses less energy than other wireless technologies; therefore, the barcode scanner has a longer battery life between charges. The ION Linear Wireless incorporates a convenient USB dongle for a clean wireless connection, a sleek, shatter-resistant ergonomic housing, and an industry leading warranty and support package, which comes standard with every POS-X product.



Key Features



Decode Capabilities

Reads all standard linear 1D barcodes



Scan Rate

Reads up to 270 scans/second

٢	
l	VI
L	T

Reading Distance From 1.2" to 7.8" (30mm to 200mm)



Receiver Compact USB dongle



Wireless Technology Up to 328 feet



Operating Time Approximately 70,000 scans/charge



Barcode Scanner

ION Wireless

PERFORMANCE

Light Source	630 nm ±20 nm CCD
Visual Indicators	Blue LED: decoding successful
System Interface	USB
Depth of Field	1.2" to 17.8" (30.5mm to 200mm)
Resolution	4 mil (0.1mm)
Scanning Angle	65°
Scan Rate	270 scans per second
Print Contrast	Minumum 45% contrast
Light Levels	3000 LUX-8000 LUX

FEATURES

Decode Capabilities	Reads all standard 1D symbologies
Programmable Features	Prefix Code, Length Code, Barcode Type, ISBN/ISSN/CLSI/ UK Plessey Conversion, Scanning Mode, Time Out, Baud Rate

WIRELESS TECHNOLOGY

Radio Frequency	2.4GHz-2.5GHz
Range	Up to 328 ft. (100m) line of sight

PHYSICAL

Dimension (LxWxH)	7.3" x 2.6" x 3.6" (186mm x 67mm x 91mm)
Weight	.22 lb (180g) w/cable
Color	Black
Housing	ABS

ELECTRICAL Power Input 5 VDC ± 5% (scanner) 5 VDC ± 5% (dongle) Current 70mA BATTERY Battery Type Rechargeable Polymer Battery Capacity 1200mAh Recharge Time 4 to 5 hours via 5V USB Operating Time Approximately 70,000 scans/charge **ENVIRONMENTAL** Temperature 32°F to 104°F (0°C to 40°C) (operating) 68°F to 149°F (20°C to 65°C) (storage) Humidity 5% to 95% relative humidity, non-condensing Shock Resistance Withstands multiple drops from 3.9' (1.2m)

Warranty	3-year warranty with free *2-day Advance Exchange Service, 1-year warranty on battery
Certifications	CE, UL, SELV, CSA, FCC Class-A, ROHS, NOM

OPTIONAL ACCESSORIES

ION-SP1-ASTAND ION Barcode Scanner stand

WARRANTY EXTENSION AND UPGRADES

ZWE-BMP	2-Year Warranty Extension
ZOE-BMP3	*3-Year Overnight Exchange
ZOE-BMP5	*5-Year Overnight Exchange

*Available in USA and Canada

