

Cube POS Printer

SLK-CB125

Product Design



Product Design



Product Design



Front



Back

Product Design



LED ON

LED OFF

Key Features

- **250mm/sec of Great Printing Speed**
- **203dpi of High Resolution**
- **Paper Width up to 82mm**
- **Triple Interface as Standard**
 - >> *USB (A type) + Serial (RS-232C 9pin) + Ethernet*
- **Triple Standard Interface + Bluetooth and/or, Wi-Fi**
 - >> *Bluetooth Ver. 5.0 and/or, Wi-Fi (a/b/g/n)*
- **Flexible display**
 - >> *Paper - Front & Top Exit available*
- **Rear housing designed to hide cables**
 - >> *Keep the checkout clean and well organized*
- **User Friendly Design**
 - >> *Easy release from paper jam*
- **Movable/adjustable Paper-Near-End sensor**
 - >> *makes available to set the timing to alarm for media change*

Key Features

- The most compact POS printer in a cube shape : 125 x 131.5 x 125 mm (W x D x H)



>> Suitable as M.POS Solution

- Automatic power-on when power supply is connected



>> Suitable for Kiosk (unmanned) solutions

Key Features

- Intuitive status check about wireless connection status : *through LED indicator*






- Rear housing designed to hide cables : *keep the checkout clean and well organized*



- Designed for easy release when there is paper jam



Comparison Chart

Image		 go to link	 go to link
Manufacturer	SEWOO	EPSON	STAR
Model	SLK-CB125	TM-M30	mCP31L
Key Features	<ul style="list-style-type: none"> • The lightest weight. • Jam free & Toolless design. • Paper front/top exit available. • LED indicator about wireless connection 	<ul style="list-style-type: none"> • Sleek design, Breakthrough modular case • Vertical and horizontal Print Direction 	<ul style="list-style-type: none"> • Sleek, Compact • Unique Print Flat technology feature • Easy to integrate through CloudPRNT • IPX2 splash-proof design • Fast charge and communication via USB-C power delivery port (mCP31C/CB)
Printing Method	Direct Thermal	Direct Thermal	Direct Thermal
Emulation	ESC/POS	ESC/POS	StarPRNT
Print Speed	250mm/sec	200mm/sec	250mm/sec
Resolution	203dpi	203dpi	203dpi
Paper Width	82.5mm (2-inch Paper Guide included)	79.5mm (3.12-inch)	58mm / 80mm (Paper Guide)
Paper Roll Diameter	Max. ø 83mm	83mm	83mm
Reliability: MCBF	80 Million lines		60 million lines
Reliability: TPH	150km	15 million printing lines	150km
Reliability: Auto-cutter	1.5 million cuts	1.5 million cuts	2 million cuts
Interface	Standard : USB(B type)+Serial(RS-232C_9pin)+Ethernet Built-in Option : Bluetooth Smart Ready (Bluetooth5.0+BLE) or, WiFi(802.11 a/b/g/n)	USB+Ethernet, USB+Bluetooth+ Ethernet, USB+Wi-Fi+Ethernet	USB-B (MCP31C : USB-C®) USB-A (for Lightning) Ethernet Bluetooth* (LB Model) (MCP31C : CB Model) LAN (Local, WebPRNT, and CloudPRNT)
Sensor	Paper end, Cover open, Paper low	Paper End, Cover Open	Near End, Paper End
Power	24V, 2.5A	24V, 1.5A	
Dimensions(WxDxH, mm)	125 x 131.5 x 125 mm	127 x 127 x 127 mm	132 x 140 x 125 mm
WEIGHT (KG)	T.B.D.	1.2KG	Approx. 1.3 kg (excluding roll paper)
Other options	White, Black	White, Black External buzzer	White, Black Print Flat Technology Splash-Proof Insect-Proof Star Micronics Service : Cloud Ready (Device Management, Digital Journal, PromoPRNT, etc.)
Operating Temperature	0° C - 45° C	5° C - 45° C	5° C - 45° C

2024 Product Roadmap

 **Cube POS Printer**



2-in Mobile Printer

May. 2024

Dec. 2024

1Q

2Q

3Q

4Q

Jan. 2024

Oct. 2024

**Cost-effective POS Printer
(Product upgrade)**



T/T Desktop Label Printer

- Simple and sleek design
- High speed printing at 9.8ips (250mm/sec)
- Wheel-type paper jam control
- Visible wireless connectivity status
- Ideal for top exit printing with wall mount
- Easy & simple replacement of components (TPH, Motor, Cutter, PCB etc.)