# **Black Series**

55 Inch Touch Display **BKT551** 





2.6 inches (66 mm)

50.4 inches (1280 mm)





29.5 inches (749 mm)







Rugged Metal Construction



Anti-Fingerprint





### **Display Specifications**

Commerical Grade LCD Panel

3 Year Extended Warranty

Edge-to-Edge Sealed and Thermally Strengthened Safety Glass

Dual Fan Adaptive Cooling and Filtered Intake for Extended Lifespan

**VESA Compatible Mounting** 

Removable Handles

Included IR Remote

### **Touch Performance**

Ultra Fast Precision Touch Response Using Projected Capacitive Technology

Requires Human Intentional Touch (HIT)

Touch Operation Virtually Unaffected by Contaminants

Ten Point Multi-Touch Accepting Input from Finger, Capacitive Stylus, Nitrile / Latex / Vinyl Gloves

USB HID Compliant & Driver Free Installation

No Calibration Required

## **Optional Models**

| Type     | Additonal Features | SKU        |
|----------|--------------------|------------|
| Standard | -                  | BKT551     |
| UHD      | UHD/4K             | BKT551-UHD |









VIDEO























## **Technical Specifications**

|                      | FHD Model   | UHD/4K Model           |  |
|----------------------|---|------------------------|--|
| Viewable Image Size  | 55.0"   |                        |  |
| Touch Technology     | PCAP 10 Point, PCT/Anti-Fingerprint                                       |                        |  |
| Cooling              | Adaptive Dual Fan Cooling with Filter and Heat Dissipation                |                        |  |
| Aspect Ratio         | 16:9  |                        |  |
| Native Resolution    | 1920 x 1080   | 3840 x 2160            |  |
| Refresh Rate         | 60  | Нz                     |  |
| Pixel Pitch          | 630 µm  | 315 μm                 |  |
| per inch             | 40 @ Native Resolution  | 80 @ Native Resolution |  |
| Brightness (Typ.)    | 700 cc  | d / m²                 |  |
| Response Time (Typ.) | 6.5 ms  | 8.5 ms                 |  |
| Viewing Angle (Typ.) | 178°  |                        |  |
| Contrast Ratio       | 4000:1  |                        |  |
| Supported Colors     | 8 bit + FRC (1.07 Billion)  | 10 bit (1.07 Billion)  |  |
| Speakers             | Two Acoustically Tuned  | d Multimedia Speakers  |  |
| Inputs               | DisplayPort, HDMI, VGA , and DVI  |                        |  |
| Measurements         | 1   |                        |  |
| Power Consumption    | 89 W  |                        |  |
| in Power Saving Mode | 0.03 W  |                        |  |
| Dimensions           | 50.4 x 29.5 x 2.6 in.   |                        |  |
| Weight               | 85.5 lbs.   |                        |  |
| Operation            |   |                        |  |
| Operating Conditions | 0° to 40° C (32° to 104° F)   |                        |  |
| Humidity             |   |                        |  |
| Altitude             | 5,486 m (18,000 ft.)  |                        |  |
| Storage Conditions   |   |                        |  |
| Humidity             | 10 - 90%  |                        |  |
| Altitude             | 12,192 m (40,000 ft.)   |                        |  |
| VESA Configuration   |   |                        |  |
| Marrantu             | Warranty 3 Years Parts and Labor Including Backlight and Touch Components |                        |  |
| vvaridilly           | *Optional Advanced Replacement Service                                    | e                      |  |

# **Technical Support**

Customer and technical support is available 24/7. Call 888-623-2004 or visit www.TechGlobal.com/support

For more information on other products including touchscreen monitors,
large format displays, and custom touchscreen solutions visit www.TechGlobal.com

Tech Global reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.



