



T1/PRI Modules

ATLAS 550 Modules

Product Features

- One, two, or four T1/PRI interfaces
- Built-in CSUs
- Configurable for DS-1, PRI or DSX-1 operation
- Maximum distance 6,000 ft
- AT&T 54016, 62411 and ANSI T1.403 compliant
- D4 and ESF framing formats
- AMI and B8ZS line coding
- D-channel to robbed bit signaling conversion
- ESF performance monitoring
- Local and remote loopback support
- Generates and detects QRSS test pattern
- Supports PRI circuits on Lucent 4ESS/5ESS, Nortel DMS100 and National ISDN
- Lightning protection
- Hot swappable
- Standard five-year warranty

The T1/PRI modules are used in the ATLAS™ 550 to implement a variety of WAN access products, including a T1 Bandwidth Manager, an ISDN Switch, a Digital Access Cross-Connect System (DACS), and a Frame Relay Switch. These modules provide either one, two, or four ports, each of which can be independently configured to operate in T1 (DS-1 or DSX-1) or Primary Rate ISDN (PRI) modes.

The ATLAS 550 can perform T1 or PRI conversion, translating between the robbed-bit signaling presented in a channelized T1 circuit and the D-channel signaling of a PRI circuit. When using the T1/PRI modules, ATLAS can also operate in a DACS mode supporting DSO time slot interchange and DSO grooming while preserving robbed bit signaling. ATLAS can be fully populated with T1/PRI modules to support a pure DACS application of 18 T1/FT1 circuits or 18 PRIs.

T1/PRI modules can be used to interface with both the public network and end-user equipment. The single T1/PRI module can only be used in the Network Interface slot, while the Dual and Quad T1/PRI modules can be used in any of the four User slots of the ATLAS 550.

Configuration of the T1/PRI module can be accomplished through a variety of mechanisms, including Telnet or VT100 emulation. SNMP management is supported for alarm and event reporting.

Extensive T1 circuit monitoring is standard with the T1/PRI modules, including the ability to detect, store, and report all performance parameters specified in AT&T Technical Reference 54016. The module detects and reports alarm conditions associated with the circuit, including Loss of Signal, Red Alarm, Blue Alarm, Yellow Alarm, and for PRI circuits, D-channel synchronization.

The T1/PRI modules respond to standard loopback commands from the telephone company central office, both in-band commands and those sent through the Facilities Data Link. In addition, local and remote loopbacks (both line and payload) can be initiated from ATLAS. When testing the T1 circuit, the T1/PRI modules allow the user to select from a variety of test patterns, including all 1's, 0's, as well as a standard QRSS pattern. When sending the QRSS pattern, the T1/PRI modules record and report the results of the testing to the user.



ADTRAN, Inc.

Attn: Enterprise Networks
901 Explorer Boulevard
Huntsville, AL 35806

P.O. Box 140000
Huntsville, AL 35814-4000

256 963-8000 voice
256 963-8699 fax
256 963-8200 fax back

General Information
800 9ADTRAN
info@adtran.com
www.adtran.com

Pre-Sales Technical Support

800 615-1176 toll-free
application.engineer@adtran.com
www.adtran.com/support

Where to Buy

877 280-8416 toll-free
channel.sales@adtran.com
www.adtran.com/where2buy

Post-Sales Technical Support

888 423-8726
support@adtran.com
www.adtran.com/support

ACES Installation & Maintenance Service

888 874-ACES
aces@adtran.com
www.adtran.com/support

International Inquiries

256 963 8000 voice
256 963-6300 fax
international@adtran.com
www.adtran.com/international

For the regional office nearest you, visit:

www.adtran.com/where2buy



I.S. EN ISO 9001
ADTRAN is a
ISO 9001 registered company.



TL 9000
ADTRAN is a
TL 9000 registered company.

Printed in the U.S.A.
61200314L1-8D April 2003
Copyright © 2003 ADTRAN, Inc.
All rights reserved.

T1/PRI Modules

ATLAS 550 Modules

Product Specifications

Physical Interface

- 8-pin Modular RJ-48C

Line Rate

- 1.544 Mbps

Framing

- D4, ESF

Line Coding

- AMI, B8ZS

Line Length

- 6,000 ft 24 gauge (DS-1) 655 ft (DSX-1)

Diagnostics

- Local Loopback-Line and Payload
- Remote Loopback-Line and Payload

Test Patterns

- QRSS, All 1's, All 0's

Alarms

- Loss of Signal, Red, Yellow, Blue, D-channel

Performance Monitoring

- ES, BES, SES, SEFS, LOFC, CSS, UAS, LCV, PCV, LES

Signal Monitoring

LBO

- 0,7,5,15,22.5 dB
- 266,399,533,655 ft

System Timing

- Network, Internal, External

Robbed Bit Signaling

- E&M Immediate, E&M Wink, Ground Start, Loop Start, Feature Group D

Conversion

- Robbed Bit Signaling to ISDN D-channel, AMI to B8ZS, D4 to ESF

Switch Compatibility

- **PRI Mode:** Lucent 4ESS/5ESS, Nortel DMS-100, National ISDN

Switch Evaluation

- **PRI Mode:** Lucent 4ESS/5ESS, Nortel DMS-100, National ISDN

Agency Approvals

- FCC Part 15, Class A, UL, and Canadian UL (CUL)

Environment

- **Operating:** 0° to 45°C (32° to 113°F)
- **Storage:** -20° to 70°C (-4° to 158°F)
- **Relative Humidity:** Up to 95%, non-condensing

Power

- 2 Watts

Product Includes

- RJ-48 cable(s) (15 ft)
- RJ-48 to RJ-48 Crossover cable(s) (15 ft)
- Quick Start Guide

Ordering Information

Equipment	Part #
T1/PRI Network Module	1200307L1
Dual T1/PRI User Module	1200314L1
Quad T1/PRI User Module	1200755L1



Specifications subject to change without notice. ADTRAN and ATLAS are trademarks of ADTRAN, Inc. All registered trademarks and trademarks mentioned in this publication are the property of their respective owners.