## Advantage LX Desktop Thermal Printer



#### **Barcode Label Printers**

# Advantage LX

#### Mission-critical desktop printer.

CognitiveTPG's most popular desktop label printer, the Advantage LX (formerly known as the Blaster or Blazer), is still the preferred industry choice for mission-critical desktop printer applications. It remains a much beloved printer by both its users and our resellers.

#### Programming

CognitiveTPG's advanced firmware command language, CPL, is so easy to use that programming it into any application is a snap.

#### Upgrading

The use of flash memory allows for easy firmware upgrades to get you the latest features available for your printers.

#### Capacity

Store hundreds of objects with our expanded memory. With 4 MB of flash memory in every printer, you have plenty of room to add fonts, graphics, and programming.

#### Size

Why settle? Now you can save valuable time and space with high-performance printing in a small footprint.

#### **Durability**

The Advantage LX is the only desktop thermal printer that has a full metal mechanism and a proven track record. As one of the most rugged printers in the marketplace, the Advantage LX thrives in the harshest environments where others have failed.

#### Reliability

A good, simple design and strong foundation make our printers some of the most reliable in the field. When productivity is critical, you can count on the Advantage LX.

## COGNITIVETPG

800.732.8950 sales@CognitiveTPG.com www.CognitiveTPG.com

### Advantage LX Mission-Critical Desktop Printer

#### 2" AND 4" MODELS

#### **Technical Specifications**

	2″ Model	4" Model	
PRINT			
Method	Direct Thermal or Thermal Transfer	Direct Thermal or Thermal Transfer	
Width (max)	2.2" (56 mm)	4.1" (104 mm)	
Length (max)	40" (1,016 mm)	20" (513 mm)	
Speed (max)	3 ips (76 mm/sec)	3 ips (76 mm/sec)	
Resolution	203 dpi (8 dpmm)	203 dpi (8 dpmm)	
MEDIA			
Width	1" - 2.4" (25 mm - 61 mm)	2" - 4.3" (50mm - 109mm)	
Roll Diameter	4.7" (119 mm)	4.7" (119 mm)	
Ribbon Length (TT models only)	3150" (80 m)	3150" (80 m)	
Indexing	Black bar, notch, and gap	Black bar, notch, and gap	
BAR CODES	21 standard bar codes, including Add2, Add5, Codabar, Code39, Code93, Code 128A/B/C, D2of5, 2of5, S2of5, EAN8/8+, EAN13/13+, EAN128, Maxicode, MSI/I1, PDF417, Plessey, Postnet, UPCA/A+/E/E1		
FONTS			
Bitmapped	7 styles with up to 10x10 magnification, variable boldno	ess and spacing	
International	Sans serif font in 7 pt. sizes, up to 4x4 magnification, variable boldness and spacing		
Scalable Smooth Fonts	3 Ultra Font styles for smooth characters in any size and boldness		
Rotataions	0, 90, 180, 270 degrees		
GRAPHICS	PCX and BMP formats	PCX and BMP formats	
MEMORY*	RAM - 8 MB, Flash - 4 MB	RAM - 8 MB, Flash - 4 MB	
COMMUNICATIONS	Serial (DB9)	Serial (DB9), Parallel (1284B)	
	Parallel (1284B)	Serial (DB9), Parallel (1284B), Ethernet	
	Serial (DB9), Ethernet		
ELECTRICAL*	Auto-ranging 100-240VAC, 50-60 Hz, 24 VDC Output	Auto-ranging 100-240VAC, 50-60 Hz, 24 VDC Output	
ENVIRONMENTAL	Operates at 41°F to 104°F (5°C to 40°C)	Operates at 41°F to 104°F (5°C to 40°C)	
DIMENSIONS			
Width	5.0" (127 mm)	6.8″ (173 mm)	
Height	6.1" (155 mm)	6.1" (155 mm)	
Depth	9.4" (238 mm)	9.4" (238 mm)	
-			
WEIGHT (DT / TT)	3.1 lbs. (1.41 kg) / 3.9 lbs. (1.77 kg)	3.9 lbs. (1.77 kg) / 4.4 lbs. (2.0 kg)	
ACCESSORIES			
Standard	Quick Start Guide, power supply and cord (cord included only in LBxxx-2xx3-01x models)		
Downloads from Web site	Windows drivers, programmer's guide, NiceLabel design software, and User's Guide		
Optional		Communications cables, label (peeler) dispenser, Ethernet, real-time clock	
WARRANTY			
WARRANTY Printer	24 months from date of purchase (requires registration	and excludes printhead)	

\*specifications for Advantage LX printers with S/N's starting with "L"

# COGNITIVETPG

**CognitiveTPG, LLC** 950 Danby Road, Suite 200, Ithaca, NY 14850 Toll Free: 800.732.8950 Phone: 607.274.2500 Fax: 607.274.2449 www.CognitiveTPG.com Copyright 2012 CognitiveTPG. All Rights Reserved.

280-0005-01-1108 Rev. C