

Intercoms



CM200X, CM206M, CM211M

Bogen's CM-Series of intercoms are ideal for interoffice communications. They provide a separate, direct communications link to other individuals in an organization. Systems can be configured as all-master systems which allow access to any station in the system, or as master/remote systems in which remote stations can be restricted to communicating only with specific stations.

Product Features:

- 6- or 11-station capacity
- All-master system or any combination of masters and remotes
- Multiple simultaneous conversations – up to 5 in an 11-station system
- Selective electronic tone calling (masters only)
- Masters can call any station in system
- Remote stations can only call its associated master station
- Privacy button on stations to prevent eavesdropping
- Conference calling between stations
- Push-to-talk operation
- Talk-lock button for dictation (masters only)
- Station busy indicator (masters only)
- Volume controls for speech level and annunciator tone
- Easy installation using supplied junction boxes
- Desk or wall-mountable
- One power supply runs entire system

Power Requirements: 12V DC @ 1A (not included)

Model	Station Type	Station Capacity	Dimensions	Shipping Weight
CM206M	Master	Up to 6 stations	10" W x 2-1/8" H x 6" D	2 lb.
CM211M	Master	Up to 11 stations	10" W x 2-1/8" H x 6" D	2 lb.
CM200X	Remote	As needed	6-3/4" W x 2-1/4" H x 6" D	2 lb.

Three System Setups

The CM-Series provides intercom functionality for small offices, warehouses, and small stores that do not have an internal phone system. There are three basic setups available:

1) All-Master Stations: Every station in the system is a master station. Any station can call any other station.

2) Single-Master System: The system only has one master station. All remote stations can only call the master station. The master station can call any of the remote stations.

3) Mixed Master/Remote System: The system has more than one master station. The master stations can call any of the other master stations and any of the remote stations associated/wired to it. Remote stations can only call the master station associated/wired to it.

Hands-Free Communication

When a master station calls a remote station, the remote station can speak and listen hands-free. When a remote station calls its associated master station, the master station can speak and listen hands-free. The master stations also have a talk-lock button for dictation to a remote station, or to monitor a quiet or critical area.

Accessories



RF12A
12V DC Power Supply



TP6AP, TP12AP Interphones

The TP-Series of interphones are an ideal way of providing simple telecommunications between different areas in a facility. Simple to install and operate, these phones provide system-wide paging as well as telephonic communications.

Product Features:

- 6- or 12-station capacity
- Telephonic communication between stations
- Common talk path with selective ringing
- Electronic tone annunciation
- Simple installation and operation
- 600-ohm output
- Built-in all-station paging
- Paging can be defeated at individual stations
- Conference call capability
- Ringer volume control at each station
- Connections for external loudspeaker for high volume paging, overhead paging, or background music
- One power supply runs entire system

Power Requirements: 24V DC @ 1A (not included)

Dimensions: 4-3/8" W x 8-1/2" H x 2-1/2" D

Shipping Weight: 2 lb. each

Built-In Paging System

If a small paging system is more desirable than selective handset calling, an external loudspeaker may be connected at each station. Pages to an external loudspeaker are made via handset simply by pressing a button and then making the desired page into the handset.

Accessories



IH8A
Horn Loudspeaker,
8-ohms, 15W



RF24A
24V DC Power Supply



TB10A
Paging Adapter