

Cisco Wireless LAN Controller Modules

Simple and secure wireless deployment and management for small and medium-sized businesses (SMBs) and enterprise branch offices

Product Overview

Cisco® Wireless LAN Controller Modules (WLCMs), shown in Figure 1, supported on the Cisco Integrated Services Routers (ISR), provide an easy to deploy, cost-effective branch office or Small to Medium Business wireless solution. As a component of the Cisco Unified Wireless Network, the Cisco WLCMs give network administrators the visibility and control necessary to effectively and securely manage business-class wireless LANs and mobility services, such as enhanced security, voice, guest access, and context aware mobility or location services. WLCMs work in conjunction with Cisco lightweight access points and the Cisco Wireless Control System (WCS) to provide centralized wireless LAN management and monitoring.

Cisco is delivering higher scalability for the WLCMs. The modules manage 6, 8, 12 or 25 Cisco Aironet® lightweight access points and are supported on Cisco 2800 and 3800 Series Integrated Services Routers.

Figure 1. Cisco Wireless LAN Controller Module



Cisco Wireless LAN Controllers

The Cisco WLCMs are models in the Cisco Wireless LAN Controller family, which includes standalone controllers, integrated controllers, and modular wireless LAN controllers that work in conjunction with Cisco switches and routers.

Because the Cisco Wireless LAN controller modules support 802.11 a/b/g and the IEEE 802.11n draft 2.0 standard, organizations can deploy the solution that best meets their individual requirements. Organizations can offer robust coverage with 802.11 a/b/g or deliver unprecedented reliability using 802.11n and Cisco's Next-Generation Wireless Solutions.

Features and Benefits

Table 1 lists the features and benefits of the Cisco WLCMs.

Table 1. Features and Benefits of Cisco WLCMs

Feature	Benefits
Supports 6, 8, 12 or 25 access points	Provides choice of capacity to optimize total cost of ownership
Provides integrated controller module	Provides simplified deployment for branch and small offices
Part of the Cisco Integrated Services Router family of empowered wireless branch-office platforms	Intelligently embeds data, security, voice, and wireless services into a single, resilient system for fast, scalable delivery of mission-critical business applications
Supports all mobility services and runs same software found in all Cisco Unified Wireless Network controllers	Supports all mobility services, including voice and location, and builds on the ongoing investment in new functions for the Cisco Unified Wireless Network

Product Specifications

Table 2 lists the product specifications for the Cisco WLCMs.

Table 2. Product Specifications for Cisco WLCMs

Item	Specification
Wireless	Access points supporting IEEE 802.11a, 802.11b, 802.11g, 802.11d, 802.11h, and 802.11n
Wired and Switching	Several Ethernet switching modules and Power-over-Ethernet (PoE) options are supported on Cisco 2800, and 3800 Series routers
Data RFCS	<ul style="list-style-type: none"> • RFC 768 UDP • RFC 791 IP • RFC 792 ICMP • RFC 793 TCP • RFC 826 ARP • RFC 1122 Requirements for Internet Hosts • RFC 1519 CIDR • RFC 1542 BOOTP • RFC 2131 DHCP
Security Standards	<ul style="list-style-type: none"> • Wi-Fi Protected Access (WPA) • IEEE 802.11i (WPA2 and Robust Security Network [RSN]) • RFC 1321 MD5 Message-Digest Algorithm • RFC 2104 HMAC: Keyed Hashing for Message Authentication • RFC 2246 Transport Layer Security (TLS) Protocol Version 1.0 • RFC 3280 Internet X.509 public key infrastructure (PKI) certificate and certification revocation list (CRL) profile
Encryption	<ul style="list-style-type: none"> • WEP and Temporal Key Integrity Protocol Message Integrity Check (TKIP-MIC): RC4 40, 104, and 128 bits (both static and shared keys) • Secure Sockets Layer (SSL) and TLS: RC4 128-bit and RSA 1024- and 2048-bit • AES: Counter Mode with CBC-MAC (CCM) and Counter Mode with Cipher Block Chaining Message Authentication Code Protocol (CCMP)
Authentication, Authorization, and Accounting (AAA)	<ul style="list-style-type: none"> • IEEE 802.1X • RFC 2548 Microsoft Vendor-Specific RADIUS Attributes • RFC 2716 PPP EAP-TLS • RFC 2865 RADIUS Authentication • RFC 2866 RADIUS Accounting • RFC 2867 RADIUS Tunnel Accounting • RFC 2869 RADIUS Extensions • RFC 3576 Dynamic Authorization Extensions to RADIUS • RFC 3579 RADIUS Support for EAP • RFC 3580 IEEE 802.1X RADIUS Guidelines • RFC 3748 Extensible Authentication Protocol • Web-based authentication

Item	Specification
Management	<ul style="list-style-type: none"> • Simple Network Management Protocol (SNMP) Versions 1, 2c, and 3 • RFC 854 Telnet • RFC 1155 Management Information for TCP/IP-Based Internet • RFC 1156 MIB • RFC 1157 SNMP • RFC 1213 SNMP MIB II • RFC 1350 Trivial File Transfer Protocol (TFTP) • RFC 1643 Ethernet MIB • RFC 2030 SNTP • RFC 2616 HTTP • RFC 2665 Ethernet-Like Interface Types MIB • RFC 2674 Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering, and Virtual LAN Extensions • RFC 2819 RMON MIB • RFC 2863 Interfaces Group MIB • RFC 3164 Syslog • RFC 3414 User-Based Security Model (USM) for SNMPv3 • RFC 3418 MIB for SNMP • RFC 3636 Definitions of Managed Objects for IEEE 802.3 Media Attachment Units (MAUs) • Cisco private MIBs
Management Interfaces	<ul style="list-style-type: none"> • Web-based: HTTP/HTTPS • CLI: Telnet and Secure Shell (SSH) Protocol
Physical and Environmental	<ul style="list-style-type: none"> • Dimensions (W x D x H): 1.55 x 7.10 x 7.2 in. (3.9 x 18.0 x 18.3 cm) • Weight: 0.86lb (0.39Kg) • Temperature: <ul style="list-style-type: none"> ◦ Operating: 32 to 104°F (0 to 40°C) ◦ Storage: -13 to 158°F (-25 to 70°C) • Humidity: <ul style="list-style-type: none"> ◦ Operating humidity: 10 to 95% noncondensing ◦ Storage humidity: Up to 95%
Regulatory Compliance	<ul style="list-style-type: none"> • CE Mark • Safety <ul style="list-style-type: none"> ◦ UL 60950-1:2003 ◦ EN 60950:2000 • EMI and susceptibility (Class A) <ul style="list-style-type: none"> ◦ United States: FCC Parts 15.107 and 15.109 ◦ Canada: ICES-003 ◦ Japan: VCCI ◦ Europe: EN 55022, EN 55024
Product Compatibility	<ul style="list-style-type: none"> • Routers: Cisco 2800, and 3800 Series (excluding Cisco 2801 Integrated Services Routers) • Access points: Cisco Aironet 1000, 1130 AG, and 1200 Series lightweight access points • Management: Cisco WCS • Location tracking: Cisco 2700 Series Wireless Location Appliance • Wireless LAN controllers: Cisco 2106 and Cisco 4400 Series Wireless LAN Controllers and Cisco Catalyst® 6500 Series Wireless Services Module (WiSM)
Software Compatibility	Routers: Cisco IOS Software Release 12.4(15)T or later for on Cisco NME-AIR-WLC6-K9(=), NME-AIR-WLC8-K9(=), NME-AIR-WLC12-K9(=), & NME-AIR-WLC25-K9(=)

Ordering Information

Table 3 provides ordering information for the Cisco WLCMs. To place an order, visit the Cisco Ordering Website: <http://www.cisco.com/en/US/ordering/index.shtml>

Table 3. Ordering Information for Cisco WLCMs

Part Number	Product Name
NME-AIR-WLC6-K9	Cisco Wireless LAN Controller Module for managing up to 6 lightweight access points (when sold as part of ISR system)
NME-AIR-WLC6-K9=	Cisco Wireless LAN Controller Module for up to 6 lightweight access points (spare, ordered as an individual unit)
NME-AIR-WLC8-K9	Cisco Wireless LAN Controller Module for managing up to 8 lightweight access points (when sold as part of ISR system)
NME-AIR-WLC8-K9=	Cisco Wireless LAN Controller Module for up to 8 lightweight access points (spare, ordered as an individual unit)
NME-AIR-WLC12-K9	Cisco Wireless LAN Controller Module for managing up to 12 lightweight access points (when sold as part of ISR system)
NME-AIR-WLC12-K9=	Cisco Wireless LAN Controller Module for up to 12 lightweight access points (spare, ordered as an individual unit)
NME-AIR-WLC25-K9	Cisco Wireless LAN Controller Module for managing up to 25 lightweight access points (when sold as part of ISR system)
NME-AIR-WLC25-K9=	Cisco Wireless LAN Controller Module for up to 25 lightweight access points (spare, ordered as an individual unit)

Service and Support

Cisco offers a wide range of services programs to accelerate customer success. These innovative services programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you protect your network investment, optimize network operations, and prepare your network for new applications to extend network intelligence and the power of your business. For more information about Cisco services, visit [Cisco Technical Support Services](#) or [Cisco Advanced Services](#).

For More Information

- For more information about the Cisco WLCM, visit: <http://www.cisco.com/en/US/products/ps6730/index.html> or contact your local account representative
- For more information about the Cisco Unified Wireless Network, visit: <http://www.cisco.com/go/unifiedwireless>
- For more information about the Cisco Integrated Services Routers, visit: <http://www.cisco.com/go/isr>



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCENT, Cisco Eos, Cisco Lumin, Cisco Nexus, Cisco StadiumVision, Cisco TelePresence, the Cisco logo, DCE, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn and Cisco Store are service marks; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0807R)

Printed in USA

C78-388782-06 08/08