

Product profile

CN50

Mobile Computer



- The industry's most advanced rugged mobile computer
- High performance communication and computing in a small and lightweight ruggedized design that is optimized for highly mobile field workers
- 3.75G wireless WAN technology supports both voice and high-speed uplink and downlink data exchange to help improve worker productivity
- Flexible Network™ radio lets you deploy a single hardware solution on the wireless network that offers the best geographic coverage and lowest cost
- Enhanced Mobile Document Imaging (eMDI) option enables users to capture high quality document images while on their route to help streamline back office operations and improve cash flow
- Integrated digital compass and GPS radio provides instantaneous and real-time directional information to improve navigation for both pedestrian and vehicle-based applications
- Built-in accelerometer senses position of the device to trigger display rotation
- Standard features include both a high performance 3 MP color camera and an area imager for responsive 1D and 2D barcode reading
- Choice of area imagers – EA11 optimized for scan intensive applications, EA21 optimized for document imaging with the capability to scan 1D/2D barcodes
- Bluetooth® v2.1 EDR radio provides secure wireless connectivity to headsets, mobile printers and other Bluetooth compatible devices for simple and convenient connectivity
- Wi-Fi certified 802.11 radio enables fast and secure voice communications or end-of-day synchronization with your enterprise network
- Integrated cell phone provides high quality voice communications eliminating the need to carry a separate device
- Windows Mobile 6.1 operating system promotes ease of integration and intuitive use by developers and users
- Standard 256MB RAM and 512MB Flash Memory allows you to run multiple simultaneous applications – fast
- Available in QWERTY or numeric keyboards
- Medallion® Complete service provides protection against unbudgeted and rising repair costs

The Intermec CN50 is the only 3.75G wireless mobile computer that combines a small and lightweight form factor with a rugged design to deliver the most advanced, high performance voice and data communication solution specifically designed for the highly mobile field worker.

With the class leading capabilities of the CN50 in their mobile workers' hands, enterprises can improve their business processes, expand their service offerings and reduce the cost and complexity of a field mobility solution.

As the first device in the industry to offer a 3.75G wireless WAN Flexible Network™ Radio, the CN50 allows enterprises to finally standardize on a single hardware platform that can be configured for either CDMA or UMTS wireless networks. This gives enterprises the flexibility to choose the network that provides the best geographic coverage and the lowest cost.

With a single hardware solution to deploy, enterprises can simplify application development, lessen verification complexity, reduce deployment costs, and dramatically lower overall cost-of-ownership. As your business needs change or coverage options evolve, the Flexible Network Radio can be re-provisioned to a different carrier network.

Intermec®

CN50 Supporting Field-based Applications



Designed specifically for the “hold and carry” activities of the postal, field service, transportation, and commercial delivery worker tasked with delivering high levels of customer service all day long, the lightweight, multi-function CN50 eliminates the need to carry and manage different devices such as cell phones, digital cameras and document scanners reducing operational costs, and improving service quality, accuracy and responsiveness.

The CN50 has the latest 3.75G wireless WAN radio to deliver the fastest data and voice communications available on both CDMA and UMTS wireless networks. With high speed uplink packet access (HSUPA) technology, the CN50 provides fast and reliable data connectivity for uploading large documents, real-time images or synchronization with your enterprise data base. Compared with previous 2.5G radio technology, the CN50 provides improved productivity today, and allows enterprises to realize future benefits as the network capabilities continue to improve.

The CN50 is built on a unique multi-processor architecture with dedicated ARM and DSP processors to deliver robust application processing with nearly instantaneous response, all at the lowest levels of power consumption. The standard

battery is suitable for uninterrupted full shift use in most applications. For extreme-duty applications, the extended-life battery provides ample power to drive consistent, full-featured functionality without compromise to the compact and lightweight design.

The EA11 imager provides a familiar “laser-like” aimer and scanning performance that is optimized for scan intensive applications, including small or damaged barcodes. The EA21 imager provides great performance for 1D/2D barcodes as well as Intermec document imaging.

The CN50 with EA21 imager, features an optional imaging application called Intermec Enhanced Mobile Document Imaging (eMDI) which gives mobile workers a fast and reliable way to convert paper documents into electronic files. eMDI helps streamline back office operations and improves cash flow by reducing time-to-payment for services rendered because delivery confirmations can be imaged in the field and sent wirelessly to the home office. Customer service and other staff gain real-time access to document images, via the enterprise systems, which can be used to answer customer queries, issue invoices, and update records.

The integrated digital compass provides a real-time indication of directional heading to enhance the functionality of the GPS radio. By improving the accuracy of the turn-by-turn directions, mobile workers are able to deliver better customer service and improve on-time delivery.

A built-in accelerometer allows the CN50 to rotate the display based on the orientation of the device, improving worker efficiency and the user experience during signature capture or similar operations. A bright 3.5” QVGA display provides exceptional viewing in full sunlight.

The CN50 features a Bluetooth® v2.1 EDR radio which provides secure wireless connectivity to headsets, Intermec mobile printers and other Bluetooth compatible devices for simple and convenient connectivity. The Wi-Fi certified 802.11 radio enables fast and secure voice communications or end-of-day synchronization with your enterprise network.

With industry-leading cell phone technology at its core, the small and lightweight CN50 bridges the gap between a mobile computer and a traditional cell phone to provide high-quality voice communications without the expense of deploying and maintaining a separate device.

The no compromise design includes both a high performance 3 MP color camera with auto-focus and flash, and a dedicated area imager for responsive 1D and 2D barcode reading.

The industry standard platform in the CN50 includes Microsoft® Windows Mobile 6.1 which enables the device to integrate quickly and easily with existing systems and provides familiar operation for end users. Windows Mobile 6.1 provides integrated support for Systems Center Mobile Device Manager (SCMDM), allowing enterprise IT Managers to securely provision, configure, and deploy application software, device settings, and policies for populations of CN50 devices from the convenience of their management consoles.

Developers can access a comprehensive software toolkit through the Intermec Developer Library to simplify application development and shorten time to deployment.

Intermec SmartSystems™ software simplifies remote device management, by automatic staging, applying periodic system and software updates, as well as configuration changes, to keep on-going system maintenance costs low, and your CN50s performing in top condition.

The Intermec CN50 mobile computer is designed specifically for on-the-go field mobility customer service operations that need to be completed faster using only a single device that combines robust application processing, automated barcode data scanning and document capture, digital camera functionality, and 3G wireless WAN voice and data communication in a rugged compact package necessary to achieve better customer service and bottom line results, now and in the future.

Physical Characteristics

Dimensions with either standard or extended battery: 15.4 x 7.4 x 2.8 cm (6.05 x 2.93 x 1.09")
Weight:
With standard battery: 310 gm (11 oz)
With extended battery: 340 gm (12 oz)

Environmental

Operating Temp: -10° C to +50° C (14° F to +122° F)
Storage Temp: -20° C to +70° C (-4° F to +158° F)
Charging Temp: +5° C to +30° C
Relative Humidity: Non-condensing, 95%
Rain & Dust Resistance: IP54
Drop Spec: 26 drops from 1.5m (5 ft) to concrete across the operating temperature range per MIL-STD 810G
Tumble Spec: 1,000 0.5 m (1.6 ft) tumbles at room temperature
Electrostatic Discharge: +/- 15kV air discharge, +/- 8kV direct discharge

Power

Standard Battery Pack: 3.7V, 1950 mAh;
Extended Battery Pack: 3.7V, 3900 mAh;
Batteries are IEEE 1725 compliant, Li-Ion, removable, rechargeable.

Operating system

Window Mobile 6.1
Getting started information located at www.windowsmobile.com/getstarted

Microprocessor

Qualcomm MSM 7600, 528 MHz ARM 11

Memory and Storage

Memory: 256 MB RAM
(approx 150MB available for user applications)
ROM: 512 MB Flash
(approx 350 MB available for user applications)
Customer-accessible micro-SD slot for removable memory cards up to 32 GB

Display

- 3.5", 240 x 320 pixel (QVGA) trans-reflective TFT-LCD display
- 65,536 (16bit RGB) colors
- LED backlight
- Touch screen

Standard Communications

USB - High Speed 2.0

Software

Device Management: Contains Intermec Smart Systems Client and is compatible with most popular 3rd party device management solutions
Application Development: Support Windows APIs and Intermec Developer Libraries

Integrated Radios

Wireless WAN: (Contains the Flexible Network™ radio that can be reprogrammed to convert between the UMTS and CDMA radio formats)
• 3.75G UMTS / HSUPA
• 3.5G CDMA: 1xEV-DO Rev. A
UMTS Frequencies Supported - MHz: 850, 1700, 1900, 2100
GSM/GPRS Frequencies Supported - MHz: 850, 900, 1800, 1900
Technology Class UTM5: 3.75G HSUPA
Max Speeds: Uplink - 2.0 Mbps; Downlink - 7.2 Mbps
Technology Class CDMA: 3.5G EV-DO Rev A
Max Speeds: Uplink - 1.8 Mbps; Downlink - 3.1 Mbps
Antenna: Internal

Wireless LAN: IEEE®802.11 b/g

Data rates: 1, 2, 5.5, 11, 6, 9, 12, 18, 24, 36, 48 and 54 Mbps
Operating channels: 1 to 13 (2412-2472 MHz) and 14 (2484 MHz)
Regulatory compliance: As per IEEE® 802.11d
Antenna: Internal
Security: WiFi Certified for WPA/WPA2 operation.
Authentication: PEAP/MS-CHAPv2, EAP-TLS
Encryption: WEP (64 or 128 bit), AES, TKIP

Wireless PAN: Integrated Bluetooth Class II, Ver 2.1+EDR

Operating channels: 0 to 78 (2402-2480 MHz)
Data Rates: 1, 2, 3 Mbps
Antenna: Internal

Global Positioning System and Digital Compass

12 channel Integrated GPS; Supports Autonomous mode with extended ephemeris data; Supports assisted operation via WAN Carrier; Network independent; <3m accuracy.

Integrated, independent Digital Compass provides directional information based on earth's magnetic field.

Accelerometer

Embedded accelerometer enables automatic or application specific features such as "screen rotation" or system suspend/resume

Audio Support

Support for VoIP / Speech recognition / PTT applications; Front and rear speakers; rear speaker has >70dB at 40cm (15.7 in); Front panel microphone for voice communication; Wireless Bluetooth headset support

Integrated Scanner

EA11 Imager with "laser like" linear line aimer that is capable of scanning 5 mil 1D and 5 mil 2D barcodes

EA21 Imager with 1 megapixel area imager with laser aimer/framer, 8 bit grayscale, capable of scanning 6 mil 1D and 10 mil 2D barcodes. Supports Enhanced Mobile Document Imaging (eMDI) - optional Intermec software application

Integrated Camera

3.1 Megapixel color camera with autofocus; includes flash

Keypad Options

Numeric or QWERTY with backlit keypad

Intermec Global Services Support :

www.intermec.com --> Support --> Knowledge Central
Telephone support available in the USA & Canada (1-800-755-5505). Outside of this area, contact your local representative.
Medallion Maintenance contracts available at many locations world wide. Current listing of service locations can be found at:
www.intermec.com --> Support --> Returns and Repairs --> Repair Locations

Accessories

Desktop AC adapter/Comm adapter (with USB port); Vehicle power adapter; Vehicle holder; RAM mount; Single dock, USB Host/Client (optional Ethernet module); Quad battery charger; Four-bay multi-docks (charge only or charge and Ethernet); Magnetic stripe reader (snap-on)

Regulatory Approvals and Compliance

Safety: cULus Listed, CDRH, D, CE, NOM

EMC: Class B - FCC/ICES/CE

Radio: FCC ID, Industry Canada TAC, CE0984, A-tick (AU), C-tick (NZ), NCC, OFTA, IDA

HAC: FCC

Others: HKSI, BSMI, ICASA, POSTEL, NTC, ETA, GOST, SIRIM, ANATEL, EU Directives - WEEE, RoHS, Batteries & Accumulators, Packaging & Waste Packaging

Intermec
SmartSystems™



SAP® Certified
Integration with SAP NetWeaver®

North America

Corporate Headquarters

6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348-2600
Fax: (425) 355-9551

North Latin America

Headquarters Office
Mexico
Phone: +52 55 52-41-48-00
Fax: +52 55 52-11-81-21

South Latin America

Headquarters Office

Brazil
Phone: +55 11 5502.6770
Fax: +55 11 5502.6780

Europe/Middle East & Africa

Headquarters Office
Reading, United Kingdom
Phone: +44 118 923 0800
Fax: +44 118 923 0801

Asia Pacific

Headquarters Office

Singapore
Phone: +65 6303 2100
Fax: +65 6303 2199

Internet

www.intermec.com
Worldwide Locations:
www.intermec.com/locations

Sales

Toll Free NA: (800) 934-3163
Toll in NA: (425) 348-2726
Freephone ROW:
00 800 4488 8844
Toll ROW: +44 134 435 0296

OEM Sales

Phone: (425) 348-2762

Media Sales

Phone: (513) 874-5882

Customer Service and Support

Toll Free NA: (800) 755-5505
Toll in NA: (425) 356-1799



Copyright © 2010 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611952-01H 11/10

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.