



PROFESSIONAL-GRADE CAPTURE FOR HIGH-VOLUME ENVIRONMENTS

Versatile, integrated solution

The Datacard SecureCapture solution includes everything users need to capture large volumes of high-resolution images.

- **Datacard SecureCapture tower.** The secure enclosure houses an 8 megapixel digital camera and high-intensity flash capable of 250,000 uses.
- **Datacard Tru Photo software.** This intuitive software application automates capture and cropping processes.
- **Accessories.** The solution comes with a backdrop, stand and frame, so you can start capturing images immediately.

The Datacard® SecureCapture™ solution offers exceptional speed, quality and ease of use for moderate to high-volume image capture. This professional-quality solution is the right choice for secure ID applications in a wide range of government, education and corporate facilities.

- **Secure, durable design.** The sleek, attractive tower integrates an 8 megapixel digital camera and high-powered flash. This rugged enclosure keeps the camera and flash in proper alignment and helps reduce the risk of damage and theft. The camera head is easily adjustable, and the flash eliminates shadows and ambient light in virtually any environment. Four bolt holes in the base enable secure mounting on a countertop or desktop.
- **Fast, easy operation.** Datacard® Tru™ Photo software automatically adjusts camera settings and manages lighting, cropping and other time-consuming tasks. No panning, tilting or zooming is required. Operators simply point and click once to capture, crop and save an image — all in less than seven seconds.
- **High-quality images.** The high-intensity flash allows you to capture crisp, high-resolution images with no shadows or bright spots. It is designed to maintain quality even in environments where lighting conditions change constantly. Plus, pre-set crop ratios help ensure image uniformity.



The Datacard® SecureCapture™ solution offers a fast, easy way to capture images with exceptional quality in high-volume applications.

DATACARD® SECURECAPTURE™ SOLUTION

SecureCapture Solution Components

Datacard SecureCapture tower with 8.0 megapixel camera and high-powered flash
Datacard Tru Photo software
Accessories (backdrop, stand and frame)

SecureCapture Tower Specifications

Flash life
Designed for 250,000 flashes
Flash recycle time
5-second maximum for retakes,
20-second enrollment cycle
Effective flash distance
6 to 15 feet
Effective side illumination suppression range
6 to 10 feet using 50,000 lux
Flash head tilt range
±30°
Vertical flash head adjustment
10 inches
Camera resolution
8 megapixels
Non-skid base surface
Security mounting at base of unit for bolting to countertop or desk
Power source
100/120 VAC 60 Hz
Connectivity
USB 2.0 high-speed compatible
1 external connector (Style B) for PC connection
2 external connectors (Style A) for external device connection
Physical dimensions
Tower: 13.0 in. x 8.0 in. x 32.0 in.
(33.02 cm x 20.32 cm x 81.28 cm)
Base plate: 8.0 in. x 8.0 in. (20.32 cm x 20.32 cm)

Weight
22.0 lbs (10.0 kg)
Operating conditions
60°F to 95°F (15°C to 35°C)
20% to 80% relative humidity (non-condensing)
Storage conditions
5°F to 140°F (-15°C to 60°C)
10% to 90% relative humidity (non-condensing)
Safety
National Recognized Test Lab (NRTL) for U.S.
Safety Council for Canada

Tru Photo Software

Auto capture
Operator clicks once in the image field and photo is immediately captured
Manual capture/live video
Provides live video for the operator to confirm positioning and facial expression
Auto crop
Image is automatically cropped to pre-defined ratio without operator intervention
Manual crop
The captured image can be resized by the operator by moving and sizing the boundaries of the cropping frame
White balance
Settings can be selected to capture the most realistic colors for your lighting environment

System Requirements

Operating system
Microsoft® Windows® 2000, XP Professional or XP Home Edition with latest service packs
Web browser
Microsoft® Internet Explorer 6.0 or later
Processor
500 MHz Intel® Pentium® II processor or faster
Memory
128 MB RAM (256 MB or more recommended)
Disk space
300 MB (at least 450 MB recommended)
Screen resolution
800 x 600 or higher
Peripherals
CD-ROM drive
1 available USB 2.0 port (high-speed certified cable recommended)

DatacardGroup

11111 Bren Road West

Minnetonka, MN 55343-9015

+1 952 933 1223

+1 952 931 0418 FAX

www.datacard.com

Datacard, SecureCapture and Tru are registered trademarks, trademarks and/or service marks of DataCard Corporation in the United States and/or other countries. Microsoft and Windows are registered trademarks of Microsoft Corporation. Intel and Pentium are registered trademarks of Intel Corporation. Names and logos on sample cards are fictitious. Any similarity to actual names, trademarks or tradenames is coincidental.

©2007 DataCard Corporation. All rights reserved.
Specifications subject to change without notice.

DC7-7009