

Magellan® 8200

High Performance Scanner and Scanner/Scale



Features:

- FirstStrike™ Advanced Decoding Software
- Multiple interface solution supports all popular host interfaces
- Enhanced All-Weights™ Platter
- Optional Productivity Index Reporting™ (PIR)
- Flash Memory for easy, low cost upgrades
- Powered auxiliary RS232 port for easy integration of a handheld scanner
- Optional RSS decoding capability
- Optional EAS functionality

The Performance Tool For High Volume Point-Of-Sale (POS)

The Magellan® 8200 scanner and Magellan® 8200 scanner/scale are members of PSC's high-performance Magellan® line for large volume, point-of-sale applications. It features PSC's patented 360-degree scan pattern for ergonomically correct scanning when seated or standing. Select from five different Magellan® 8200 models to fit your particular application and checkstand designs.

Every Magellan® 8200 also includes FirstStrike™, PSC's advanced decoding software for reading torn, poorly printed and disfigured labels of all types. FirstStrike has the ability to autodiscriminate all supported symbologies for added flexibility and features optional support for Reduced Space Symbology (RSS).

Smart Technology For Your Business

The Magellan® 8200 has a powered auxiliary RS232 port for integrating a PSC handheld scanner for those large or heavy items that are often left in the shopping cart. This port can also be used to update the scanner's software in Flash Memory. Additionally, the Magellan® 8200 can be equipped for full electronic article surveillance (EAS) functionality, including Interlock, for one step scanning and security tag deactivation.

Adding even more value to the POS environment, the Magellan® 8200 features optional productivity enhancement software. Productivity Index Reporting™ (PIR), will automatically monitor the bar codes being scanned and will alert management to items that are consistently slowing down the checkout process.

Seamless Integration

Since the Magellan® 8200 is from PSC you can count on easy installation and years of worry free operation. The Magellan® 8200 has the same familiar form factor as the Magellan SL® so it installs easily into both new and existing point-of-sale configurations. It also supports industry standard host terminal interfaces right out of the box, including RS232, IBM 46XX, and IBM USB. In addition, the Magellan® 8200 is compatible with OPOS and JavaPOS systems allowing for even greater integration flexibility at the point-of-sale.

"Nothing Beats a Magellan®"



Specifications

Magellan® 8200

PRODUCT

Mechanical

Length & Weight

Model 8200 (short scanner)
13.9" / 35.3 cm & 13.0 lbs. / 5.9 kg
Model 8201 (medium scanner)
15.7" / 39.9 cm & 15.0 lbs. / 6.9 kg
Model 8202 (medium scanner/scale)
15.7" / 39.9 cm & 18.0 lbs. / 8.2 kg
Model 8203 (long scanner)
20.0" / 50.8 cm & 15.0 lbs. / 6.9 kg
Model 8204 (long scanner/scale)
20.0" / 50.8 cm & 20.0 lbs. / 9.1 kg

Width: 11.5" / 29.2 cm

Depth (below counter): 4.0" / 10.0 cm

Height (above counter): 5.1" / 13.1 cm

Scale Capacities

Capacity: 30.0 lbs. / 9.99 kg or 15 kg
(host dependent)
Minimum increment: 0.01 lb. / 0.005 kg
Vibration immunity: 4 programmable
filter settings
Maximum static weight: 150 lbs. / 68 kg
Adjustments required: Calibration only

Optical

Scan lines: 48
Motor speed: 6,000 rpm
Scan rate: 4,800 lines/sec.
Scan zone: 360°
Sides read: 5
Read height: 6.0" / 15.2 cm

Environmental

Temperature rating

Operating: 50° to 104° F / 10° to 40° C
Storage: -40° to 158° F / -40° to 70° C

Humidity: 5 to 95% NC

Electrical

AC Power requirements:

100-250 VAC, 50-60 Hz; 14 Watts (nominal),
18 Watts (maximum), 8 Watts (sleep mode)

Decoding Capability

*The Magellan® 8200 autodiscriminates between
the following supported symbologies:*

UPC Versions A & E
UPC Supplementals (Bookland & Coupon Code)
UPC Add-ons (sub 2 or P2, sub 5 or P5 & C128)
Plural Stage Dual UPC
Reduced Space Symbology – *Optional*
(RSS-14, expanded and stacked)
EAN 8, 13
JAN 8, 13
UCC/EAN 128
Code 39 (with full ACCIII)
Code 128
Code 93
12 of 5
Italian Pharmacode
Codabar/NW7
MSI/Plessey

Communications

Host: All Magellan® 8200 models support –
IBM 46XX, RS232, and IBM USB

Other: Powered RS232 auxiliary port;
scale host port; remote scale display port;
EAS interlock port

Safety / Regulatory

Electrical: Resolution No. 92/98 (Argentina);
AS 3260 (Australia); C22.2 No. 1950 (Canada);
EN60 950 (TÜV Europe); MITI T-Mark (Japan);
UL 1950 (USA)

Emissions: FCC part 15 subpart j, Class A (USA);
AS/NZS 3548 (Australia/New Zealand);
EN 55022-B (Europe); VCCI-B (Japan);
CISPR 22-B

Laser safety: Class IIa Laser Product



(CAUTION: Laser Light – do not
stare into beam); IEC 825 Class 1,
EN60 825 Class 1 (Europe)

Weights and measures: Australia; Canada;
90/384/EEC (Europe); Mexico; New Zealand;
Puerto Rico; USA (NIST Handbook 44)
*Contact your PSC representative for certification
schedule and additional listings.*

Other

EAS compatibility: Integrated EAS hardware
will work with Counterpoint IV, V, VI, and VII
models available from Checkpoint® Systems.
Good read acknowledgement with Sensormatic.



PSC Inc.

959 Terry Street
Eugene OR 97402-9150 USA
Tel: 800 695 5700 or 541 683 5700
Fax: 541 345 7140

Specifications are subject to change without notice.

Additional information concerning this product or other PSC products
and services can be found at the PSC website: www.pscnet.com
or contact your PSC representative for more information.



PSC Worldwide Sales and Service locations

Australia Tel: 61 2 9878 8999 Fax: 61 2 9878 8688	Belgium Tel: 32 2 414 74 09 Fax: 32 2 410 11 63	Brazil Tel: 55 11 5507 7721 Fax: 55 11 5507 7696	Chile Tel: 562-339-7000 Fax: 562-339-7985	China Tel: 86 10 6857 9048 Fax: 86 10 6857 8699	China - South Tel: 86 20 8765 9955 Fax: 86 20 8765 9955	France Tel: 33 1 64 86 71 00 Fax: 33 1 64 46 72 44	Germany Tel: 49 6151 93580 Fax: 49 6151 935858
Hong Kong Tel: 852 25846210 Fax: 852 25210291	India Tel: 91 11 4621586 Fax: 91 11 4623305	Italy Tel: 39 039 629031 Fax: 39 039 6859496	Japan Tel: 81 3 3491 6761 Fax: 81 3 3491 6656	Latin America Tel: 1 305 539 0111 Fax: 1 305 539 0206	Singapore Tel: 65 435 1311 Fax: 65 226 1242	Spain Tel: 34 91 203 65 00 Fax: 34 91 203 65 01	Sweden Tel: 46 4010 84 92 Fax: 46 4010 84 91
Turkey Tel: 90 212 23691 15 Fax: 90 212 23691 16	United Kingdom Tel: 44 1923 809500 Fax: 44 1923 809505						