

QuickScan® QS6500

Linear Imager

Data Sheet



Features:

- Aggressive linear imaging performance with up to 15" / 38 cm reading on 100% UPC labels
- Supports RSS and PDF-417 for future industry compatibility
- 2005 Sunrise compliant
- Multi-interface solution supports all popular host terminal interfaces
- Flash memory for easy software upgrades
- Built tough to withstand common POS abuse for many years
- Attractive, yet durable design to complement your point-of-sale

Mechanical

Dimensions
 Height: 6.0" / 16.5cm
 Width: 2.9" / 7.4cm
 Length: 3.9" / 9.9cm
Weight: 6.4 oz / 181.4 g

Environmental

Temperature Rating
 Operating: 32° to 122° F / 0° to 50°C
 Storage: -40° to 158° F / -40° to 70° C

Humidity:
 Operating: 5 to 95% NC
 Storage/Transport: 5 to 95% NC

Vibration: Meets MIL STD-810E
Mechanical Shock: Withstands 50 drops from 5' / 1.5m to concrete
ESD Protection: Functional after multiple 25KV discharges.
Water & Dust: IEC529 Rating IP52DW

Electrical

Operating Voltage: +4.5 to 14VDC ±5%
Operating Current: 300mA @ 5VDC
Idle Current: 200mA @ 5VDC

Optical

Ambient Light Immunity
 Artificial & Sunlight: 86,000 Lux
Light Source: 630nm Visible Red Diode
Scan Rate: 450 scans/sec max
Sensor: 2048 pixel linear imager
Scan Width: 6.3" / 16.5cm @ 7" / 17.8cm from nose
Resolution: 5 mils / .13mm
Print Contrast: 30% or greater
Pitch: ±60°
Skew: ±55°
Depth of Field: Refer to Depth of Field Table below

DEPTH OF FIELD Range Comparisons		
LABEL DENSITY	RANGE*	
	1D MODELS	PDF MODELS
5 mil Linear	2.0 - 5.0" / 51 - 12.7 cm	2.0 - 4.5" / 5 - 11.4 cm
7.5 mils	1.0 - 7.0" / 2.5 - 17.8 cm	1.0 - 6.0" / 2.5 - 16.2 cm
10 mils	0 - 12" / 0 - 30.5 cm	0 - 10.5" / 0 - 26.7 cm
13 mils / 100% UPC	0 - 15" / 0 to 38 cm	0 - 13" / 0 - 33 cm
20 mils	Up to 24" / 61.0 cm	Up to 21" / 53.3 cm
40 mils	Up to 40" / 101.6 cm	Up to 35" / 89 cm

* Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

Decoding Capability

- ID Versions**
- UPCA, E / EAN 8, 13 / JAN 8, 13
 - Add-ons (sub 2 or P2, sub 5 or P5 & C128)
 - RSS-14, Expanded, Stacked, Limited
 - ISBN / Bookland EAN
 - Code 39 (with full ASCII)
 - Pharmacode 39
 - Code 128
 - Code 93
 - Interleaved 2 of 5
 - Standard 2 of 5
 - IATA
 - Code 16K
 - Code 11
 - Codabar/NW7
 - UK/Plessey
 - MSI/Plessey
- PDF Models support these additional symbologies:**
- RSS Composites
 - PDF-417
 - Micro-PDF

Communications

- RS-232
- Keyboard Wedge
- IBM 46XX
- IBM USB
- USB

Safety & Regulatory

Electrical: Complies to EN60950, CSA60950, UL60950
Emissions: Complies to FCC-A, EN 55022-B, BSMI13438, AS/NZS 3548, VCCI-B, ICES-003
Laser Classification: IEC 60825 Class I LED



PSC Inc.
 959 Terry Street
 Eugene OR 97402-9150 USA
 Tel: 800 695 5700 or 541 683 5700
 Fax: 541 345 7140
www.psc.com



Copyright © PSC Inc. 2005. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from PSC. PSC Inc. of Eugene, Oregon, USA is ISO registered by NQA. PSC, the PSC logo, and QuickScan are registered trademarks of PSC Inc. All other brand and product names are trademarks of their respective owners. Additional information concerning this product or other PSC products and services can be found at the PSC web site: www.psc.com. Product specifications are subject to change without notice.

