



BLK-CCP141VH

High Resolution PTZ Camera

KEY FEATURES

- 1/4" Sony Super HAD image sensor delivers high quality images with 520 color lines of resolution (570 lines B&W)
- Built-in 10x optical auto-focus zoom lens (f2.8-38mm) and 10x digital zoom support allows you to narrow your field of view to look more closely at a targeted area, while saving on storage space
- True day/night improves low light sensitivity, delivers a sharper image in low light conditions, and enables the camera to see in the dark with the help of external IR illuminators
- Advanced features include UTP, DNR, OSD and Motion Detection and auto-surveillance functions include preset, tours, pattern, zone masking, alarms and auto-flip

Save valuable time and money with this feature-packed mini speed dome camera

The BLK-CCP141VH is a 10x zoom mini speed dome camera, featuring a Sony Super HAD chipset that delivers a crisp 520 lines color resolution and 570 lines black-and-white resolution. This camera offers several advanced features, including a built-in 10x optical auto-focus zoom lens (f2.8-38mm) and 10x digital zoom support which allows you to adjust your camera to achieve the exact field of view you need. It also includes built-in image stabilization to reduce the effects of small movements or vibration of your video camera, and true day/night which improves low light sensitivity. Other features include UTP, DNR, OSD, DSS, and built-in Motion Detection for enhanced performance and greater flexibility.

Our DIGIOP PTZ dome camera designs are based on direct feedback from our customers to deliver the ultimate in simplicity and convenience, saving you valuable time and money. All PTZ dome cameras come standard with auto surveillance functions, including support for up to 63 programmable preset positions, 8 programmable tour functions, up to 4 memorized user control patterns (speed, position and lens control), up to 4 zones of programmable privacy masking, and a digital auto-flip function with 360° endless panning and 0° ~ 180° tilt angle.

All DIGIOP cameras come with lifetime technical support.

BLK-CCP141VH

High Resolution PTZ Camera

Core Features & Benefits

Chipset – Sony 1/4" Super HAD Color CCD delivers up to 570 lines of resolution with a minimum illumination of 0.02 lux.

Lens – Precision 3.8-38mm lens.

Warranty – 3-year warranty and 30-day money-back guarantee.

Available Options

The following options and accessories are available for this camera:



BLK-CCP141VH-CMO Outdoor housing and ceiling mount bracket for the BLK-CCP141VH PTZ camera



BLK-CCP141VH-WMO Outdoor housing and wall mount bracket for BLK-CCP141VH



BLK-PTZJOY3 Professional 3-axis joystick controller for all DIGIOP PTZ cameras

Specifications

Image Sensor	1/4" Sony Super HAD CCD
Effective pixels	NTSC: 768(H) x 494(V)
Horizontal Resolution	520TVL (color), 570TVL (BW)
Scanning System	2:1 Interlace
Lens	10X, f3.8 - 38.0mm (F2.8)
Minimum Illumination	0.7 lux @ F2.8 (50 IRE) : Color 0.02 lux @ F2.8 (50 IRE) : B/W"
Day/Night Function	Color / Auto1 / Auto2 / B/W (ICR filter change)
S/N Ratio	50dB (AGC off, Weight on)
Camera Control & Setup	On Screen Display
Sync	Internal/Line lock
Electronic Shutter Speed	Auto / Manual selectable (1/60 ~ 1/120,000)
Digital Noise Reduction	OFF / LOW / MIDDLE / HIGH
White Balance	ATW / AWC / Manual selectable (1800°K ~ 10,500°K)
Communication	RS-485 (Pelco P, D)
Function	63 Presets, 8 Tours, 4 Scan, 4 Area, 4 Pattern, 2 Alarm, Autoscan
Rotation Angle	Pan : 360° Endless / Tilt : 0° ~ 180° (Digital Flip)
Pan / Speed	Manual : 100° / sec, Turbo : 180° / sec, Preset : 360° / sec
Flip	Digital Flip Support
Focus Control	Auto / Manual / One push selectable
Video Output	BNC 1.0Vp-p, 75ohm load, 2nd BNC standard
Operating Temp	-10°C ~ +55°C
Power Requirement	550mA(24VAC)
Mounting Options	Surface & flush (standard)
Dimensions	112 (Ø) x 145 (D) mm