

Specifications

Eaton SUINT1000LCD2U

SmartOnline 1000VA 900W 208/230V
Double-Conversion UPS - 8 Outlets,
Extended Run, Network Card Option, LCD,
USB, DB9, 2U Rack/Tower

General specifications

PRODUCT NAME	Eaton Tripp Lite series SmartOnline UPS
CATALOG NUMBER	SUINT1000LCD2U
UPC	037332185648
PRODUCT LENGTH/DEPTH	17.72 in
PRODUCT HEIGHT	3.41 in
PRODUCT WIDTH	17.33 in
PRODUCT WEIGHT	36.38 lb
WARRANTY	2 year limited
COMPLIANCES	ENERGY STAR certified RoHS CE Marked FCC Compliant REACH
CERTIFICATIONS	UL 1778 NOM CSA certified CSA 22.2 cTUVus
GLOBAL CATALOG	SUINT1000LCD2U

Battery

BATTERY REPLACEMENT

744-A3296 *Note: 744-A3296 is the replacement battery for the SUINT1000LCD2U 2025 UPS design update featured on this page. For the replacement battery in the previous design of SUINT1000LCD2U, please see part number RBC24S

RUNTIME AT FULL LOAD	7.3 min. (900W)
-----------------------------	-----------------

RUNTIME AT HALF LOAD	17.9 min
-----------------------------	----------

Electrical input

INPUT NOMINAL VOLTAGE	200 VAC/208 VAC/220 VAC/230 VAC/240 VAC
------------------------------	---

INPUT POWER FACTOR	.99
---------------------------	-----

AC SUPPRESSION JOULE RATING	296
------------------------------------	-----

Additional specifications

FORM FACTOR	Rackmount
--------------------	-----------

RACK SIZE	2U
------------------	----

SWITCH CONFIGURATION	RPO / ROO
-----------------------------	-----------

PHASE (INPUT)	Single-phase
----------------------	--------------

Electrical output

RECEPTACLE

- Two switchable 2-outlet load banks
- C13

TOPOLOGY	Online/Double-conversion
-----------------	--------------------------

OUTPUT POWER FACTOR	0.9
----------------------------	-----

OUTPUT CAPACITY DETAILS	220/230/240V: 1000VA / 1000W; 208V(default)/200V: 1000VA / 900W
--------------------------------	--

Environmental

RELATIVE HUMIDITY	0-96% non-condensing
--------------------------	----------------------

STORAGE TEMPERATURE	With battery: 32° to 104°F (0° to 40°C); without battery: -13° to 131°F (-25° to 55°C)
----------------------------	--

Resources

BROCHURES	SmartOnline 700-3000VA Brochure
------------------	---

DRAWINGS	SUINT1000LCD2U SUINT1500LCD2U 2D Drawing
-----------------	---

DRAWINGS	Single-Phase UPS Systems Visio Stencil Single-Phase UPS Systems Visio Stencil Preview
-----------------	--

IMAGES	SUINT1000LCD2U Feature Focus
---------------	--

MANUALS AND USER GUIDES	SmartOnline 750-3000VA 2U Rack Tower UPS and EBM User Guide
--------------------------------	---

MANUALS AND USER GUIDES	PowerAlert External Battery Pack Utility (PAEBPU) – UPS Compatibility Chart
--------------------------------	---

MANUALS AND USER GUIDES	PowerAlert Device Manager (PADM) 20.0.0 Command Line Interface User's Guide (English)
--------------------------------	---

MATERIAL SAFETY DATA SHEET (MSDS)	Eaton Valve Regulated Lead-acid Battery Safety Data Sheet
MULTIMEDIA	SmartOnline 1-3kVA Video
SERVICE AND TROUBLESHOOTING	Tripp Lite series UPS service guide: warranty upgrade, startup, and preventative maintenance
SPECIFICATIONS AND DATASHEETS	SUINT1000LCD2U Runtime Graph
TECHNICAL DATA SHEETS	Runtime Chart for UPS Model SUINT1000LCD2U
WARRANTY GUIDES	Tripp Lite series SmartOnline 2-year limited warranty

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.