



Panasonic
ideas for life



OUR HIGH PERFORMANCE ENVO POS WORKSTATION MOUNTS ALMOST ANYWHERE.

With virtually unlimited installation options, the Stingray Envo JS-960 is compact, highly modular and easily serviceable, while offering an array of performance capabilities. In addition to the standard workstation configuration, the 15" LCD can be wall or pole mounted and angled for easy viewing. Envo has a highly durable aluminum alloy chassis, and its open platform runs virtually any operating system or software with ENERGY STAR®-qualified efficiency. Delivering easy-to-operate POS systems with a lower TCO is how we're engineering a better world.



ENVO WORKSTATION ADVANTAGES

- Built with a VESA mount, enabling placement almost anywhere
- Modular design makes troubleshooting and servicing easy
- Open platform runs virtually any software
- ENERGY STAR® qualified
- Various rear screens available – two-line order confirmation and static POP, 12" or 15" interactive order confirmation/POP
- Supports two hard drives with RAID capability
- Two powered USB ports enable printers or other equipment to run off the workstation
- LED backlight allows easier text viewing, requires less warm-up time and doesn't yellow over time
- Optional capacitive or resistive touch screens and biometric readers

1.877.726.2767
panasonic.com/envo

SOLUTIONS FOR FOOD SERVICES

STINGRAY ENVO UPRIGHT JS-960	<ul style="list-style-type: none"> ■ Processor Intel P4500 dual core CPU (1.86Ghz) Intel i5-520M (2.4Ghz) ■ Chipset Intel HM55 or QM57 ■ Screen 15" TFT, LED backlit, 1024x768 ■ LCD brightness 450 nit (without touch panel) ■ Touch panel Capacitive or Resistive ■ System memory 2GB SO-DIMM, DDR3, up to 8GB, 2 slots ■ Video memory 256MB max (shared with system memory) ■ HDD 2.5" 250GB SATA HDD minimum ■ LAN (Ethernet) 10BASE-T/100BASE-TX/1000BASE-T ■ 2nd display interface DVI - I ■ USB ports Enabled or disabled in BIOS Total 10 (HM55) or 9 (QM57) USB ports 5 (HM55) or 4 (QM57) ports on IO panel (1 x 12V powered, 1 x 24V powered) 2 ports on the bottom of the main unit 1 port inside display unit 2 ports inside display unit (dedicated) ■ COM ports 2 ports (HM55) or 3 ports (QM57) ■ Parallel port 1 port ■ Audio Line out/mic in ■ Speaker Built-in stereo speaker 1w x 1w ■ Cash drawer 1 x RJ12 (controls 2 drawers), 1 x Port 6 Pin DIN ■ System management Wake on LAN, PXE ■ Power management Integrated Power Supply ■ Power supply AC100V - 240V ■ Supported OS POSReady 2009 POSReady 7 Windows 7 Windows Embedded Standard 7 WEPOS 1.1 Windows XP Pro SP3 Windows XP Embedded Linux kernel2.6 ■ Mounting No ■ Indicator LED status indicator (LAN, PWR, HDD) ■ Dimension 14.3"W x 15.2"D x 16.3"H (364W x 386D x 412H mm) ■ Weight Approx. 10.3 kg (22.7 lbs.) ■ Operating temperature +5C to +40C (41F to 104F) ■ Humidity 15%RH to 85%RH (No condensation)
-------------------------------------	---

STINGRAY ENVO LOW PROFILE JS-960	<ul style="list-style-type: none"> ■ Processor Intel P4500 dual core CPU (1.86Ghz) Intel i5-520M (2.4Ghz) ■ Chipset Intel HM55 or QM57 ■ Screen 15" TFT, LED backlit, 1024x768 ■ LCD brightness 450 nit (without touch panel) ■ Touch panel Capacitive or Resistive ■ System memory 2GB SO-DIMM, DDR3, up to 8GB, 2 slots ■ Video memory 256MB max (shared with system memory) ■ HDD 2.5" 250GB SATA HDD minimum ■ LAN (Ethernet) 10BASE-T/100BASE-TX/1000BASE-T ■ 2nd display inter face DVI - I ■ USB ports Enabled or disabled in BIOS Total 10 (HM55) or 9 (QM57) USB ports 5 (HM55) or 4 (QM57) ports on IO panel (1 x 12V powered, 1 x 24V powered) 2 ports on the bottom of the main unit 1 port inside display unit 2 ports inside display unit (dedicated) ■ COM ports 2 ports (HM55) or 3 ports (QM57) ■ Parallel port 1 port ■ Audio Line out/mic in ■ Speaker Built-in stereo speaker 1w x 1w ■ Cash drawer 1 x RJ12 (controls 2 drawers), 1 x Port 6 Pin DIN ■ System management Wake on LAN, PXE ■ Power management External AC adapter ■ Power supply External AC adapter AC100V - 240V ■ Supported OS POSReady 2009 POSReady 7 Windows 7 Windows Embedded Standard 7 WEPOS 1.1 Windows XP Pro SP3 Windows XP Embedded Linux kernel2.6 ■ Mounting VESA100 ■ Indicator LED status indicator (LAN, PWR, HDD) ■ Dimension Main unit only 14.3"W x 5.3"D x 12.9"H (364W x 134D x 328H mm) ■ Weight Approx. 5.6kg (12.3 lbs.) ■ Operating temperature +5C to +40C (41F to 104F) ■ Humidity 15%RH to 85%RH (No condensation)
---	---

OPTIONS	<ul style="list-style-type: none"> ■ Customer display 2 line X 20char VFD, 1 12.1" Integrated LCD, 1 15" Semi-Integrated LCD ■ MS Integrated 3-track ■ Fingerprint reader Biometric fingerprint reader ■ 2nd HDD Yes ■ SSD 2.5" SATA SSD ■ WiFi 802.11 a/b/g/n USB module
----------------	---

OPTIONS	<ul style="list-style-type: none"> ■ Customer display 2 line X 20char VFD, 1 12.1" Integrated LCD, 1 15" Semi-Integrated LCD ■ MSR Integrated 3-track ■ Fingerprint reader Biometric fingerprint reader ■ 2nd HDD No ■ SSD 2.5" SATA SSD ■ WiFi 802.11 a/b/g/n USB modul
----------------	--

1.877.726.2767
panasonic.com/envo

