



Summit 200-24™ & Summit 200-48™

Performance, Manageability and Value for the Ideal Edge Layer 3 Switch Solution

The Summit 200 switch family redefines edge switch connectivity by delivering the price competitiveness and ease of connectivity of a traditional Layer 2 switch with the advanced features, manageability, and performance normally found in much more expensive Layer 3 switches. Even the most demanding edge customers can now have it all: high performance, manageability and advanced Layer 3 switching services in a surprisingly compact and low cost package.

Based on award-winning ExtremeWare® Layer 3 software, the Summit 200 delivers 24- or 48-ports of 10/100 Ethernet with four physical Gigabit Ethernet uplinks (two active and two redundant). Every port delivers a vast array of ExtremeWare Layer 2 and Layer 3 features; everything from OSPF routing and advanced Quality of Service (QoS) classification to the latest advancements in security, such as Network Login. Once again, Extreme Networks® demonstrates why it is the leader in Layer 3 switching.

Summit 200 Highlights

- **Scalability:** Higher port density in 1 RU footprint allows for maximum use of rack space.
- **Performance:** non-blocking architecture to support the most demanding applications today and in the future.
- **Availability:** redundant physical uplinks, dual-homed configurations, and sub-second (50 msec) EAPS failover for the best availability on every port.
- **Manageability:** true end-to-end management resulting in lower operational costs, less training, while maximizing network uptime.
- **Security:** 802.1X (rel.2), Network Login, Layers 2-4 Access Controls Lists, SSH2, TACACS+, RADIUS, and denial of service protection for comprehensive security at the edge of your network.
- **ExtremeWare Layer 3 features:** years of development enable ExtremeWare to deliver the most comprehensive Layer 3 advanced software solution set at the edge allowing customers to easily expand and add new services to their network without major changes.

Maximum 10/100 Performance with Minimum Cost of Ownership

The Summit 200 delivers a dramatic increase in 10/100 Ethernet scalability while at the same time reducing the cost per Layer 3 port to unheard of levels. Requiring only 1.75" of rack space (1 RU), the Summit 200 supports up to 48 ports of RJ-45 copper 10/100 Ethernet and four Gigabit Ethernet ports (two 1000BASE-T RJ-45 copper ports and two fiber gigabit ports). Summit 200 gigabit uplink ports provide the added flexibility of port redundancy between copper and fiber ports, enabling backup links to the active uplinks with sub-second (50 msec) failover capability. And with Summit 200's non-blocking architecture you'll get full performance to the edge of every user at the network.

More 10/100 density and line rate performance sometimes means higher price, but not with the Summit 200! The ground-breaking design of this new platform enables Extreme Networks to price Layer 3 services on the Summit 200 at less than the competition's Layer 2 price. Customers get more density, higher performance, and a lower cost from Extreme Networks and the Summit 200.

Intelligence at the Edge – Where You Need It

Customers need both Layer 2 and Layer 3 intelligent services at the edge to ensure maximum network efficiency, and the Summit 200 delivers the best Layer 2-3 feature set at the edge. Intelligence supports security to prevent unauthorized access, high availability to ensure network uptime, common manageability to reduce expenses—the very features that customers require at the edge of the network.

Of course, the Summit 200 supports traditional Layer 2 services like QoS classification, dynamic VLANs, Extreme Automatic Protection Switching (EAPS), and Access Control Lists. But with ExtremeWare, the Summit 200 also supports advanced Layer 3 services like RIP, OSPF, Network Address Translation, and Layer 2-4 ACLs. The Summit 200 is the only edge switch on the market capable of supporting ExtremeWare Layer 2 and advanced Layer 3 features yet priced lower than many “entry level” Layer 2 switches. End users can now enjoy new services like better security, faster forwarding and routing, and more uptime because the Summit 200 supports ExtremeWare Layer 2 and Layer 3 services today!

Edge, Aggregation, and Core End-to-End Solution

The Summit 200 is fully integrated into Extreme’s edge, aggregation, and core end-to-end solution. ExtremeWare Layer 2 and Layer 3 features implemented in the Summit 200 are shared with all other Extreme platforms in the Summit® product line as well as with Alpine™ and BlackDiamond® switches. This common code base makes it easy to configure features like Access Control Lists, automatic protection switching, etc. commonly throughout the network. The Summit 200 also uses the same command line interface (CLI), EPICenter™ graphical management interface and the same management commands as other Extreme Networks switches so training time and expense are reduced as management expertise can be shared over an entire network solution. Integration of the Summit 200 into Extreme’s end-to-end solution will reduce the cost of networking and significantly improve the overall efficiency of the network.

Summit 200 Feature Set Summary

Hardware Features

- 24 and 48 10/100 auto-negotiating Ethernet ports in a 1 RU footprint allow more network connections per inch of rack space
- 2 10/100/1000BASE-T copper ports and 2 mini-GBIC ports deliver two active gigabit uplinks for greater throughput and two redundant uplinks
- Single AC power supply

ExtremeWare Software Features

- Security features, including Network Login, SSH2, 802.1x (rel.2), Access Control Lists (ACLs), Denial of Service (DoS), RADIUS, TACACS+, and VLANs
- Ethernet Automatic Protection Switching-edge (EAPS-edge)
- Edge-OSPF
- Multicast-edge (rel.2)
- ESRP-aware

Performance Features

- Non-blocking architecture
- 13.6 Gbps switch fabric (Summit 200-48), 8.8 Gbps switch fabric on the Summit 200-24 enabling all 10/100 ports to operate at line rate
- Flow-based central rate limiting that can be applied to any classified packet flow
- 255 VLANs and 8,191 MAC or Layer 2 addresses
- 4 hardware queues per port
- 4 Gigabit Ethernet uplink ports, 2 active and 2 redundant with Layer 1 failover
- ACLs for optimal security and diverse traffic classification

Management Features

- Serial management port on the front panel for ease of installation
- Extensive management through SNMP, RMON and command line interface
- Secure remote management with strong encryption using SSH2



Summit 200 Product Specifications

Switch Fabric

Bandwidth, Gbps: non-blocking
13.6 Gbps (Summit 200-48),
8.8 Gbps (Summit 200-24)

Forwarding Rate

10.15 million packets/second (Summit 200-48)
6.55 million packets/second (Summit 200-24)

Max packet Size: 1522

Ports

Number of 10/100: 48 or 24
Number of Gigabit: 2 active, 2 redundant
1000BASE-T: 2 physical
Mini-GBIC: 2 physical
Max number of active Gigabit ports: 2

General

Number of QoS queues/port: 4
Number of VLANs: 255
VLAN Types: Port, IEEE 802.1Q, and
MAC-based
Number of ACL Rules/lines: 1014
(can be applied to either ingress or egress)

Forwarding Tables:

Number of Layer 2 Addresses: 8K
Number of Layer 3 Addresses: 2K
Layer 3 Routing table size: 8K

Rate Limiting:

Flow-based Bandwidth policing/rate
limiting : pool of 315 rate limiters that
can be applied to any classified ACL
flow (including ingress or egress flows)
Rate Limiting Granularity: 1Mb/s on
10/100BASE-T ports. 8Mb/s on
1000BASE-T ports

Physical and Environmental

Dimensions

Height, Inches/Cm: 1.75 Inches / 4.45 Cm
Width, Inches/Cm: 17.32 Inches / 44 Cm
Depth, Inches/Cm:
Summit 200-48: 12.2 Inches / 31 Cm
Summit 200-24: 8.1 Inches / 20.85 Cm

Weight, Lbs/Kg:

Summit 200-48: 9.7 lbs/4.4Kg
Summit 200-24: 5.72 lbs/2.6Kg

Operating Temperature Range,

Degrees Celsius/Fahrenheit: 0° to 40° C
(32° to 104° F)

Storage Temperature Range,

Degrees/Degrees Celsius: -40° to +70° C
(-40° to 158° F)

Humidity Range: 10-95% (RH)

non-condensing

Power

Min Voltage/Associated Current:

Summit 200-48: 100VAC / 0.640A
Summit 200-24: 100VAC / 0.414A

Max Voltage/Associated Current:

Summit 200-48: 240VAC / 0.328A
Summit 200-24: 240VAC / 0.223A

Heat Dissipation, Watts/BTU:

Summit 200-48: 48W / 164 BTU/hr
Summit 200-24: 24.1W / 82 BTU/hr

Regulatory

Safety

North America

cULus Listed device – UL 60950 3rd
Edition (US Safety) – CAN/CSA-C22.2
No. 60950-00 (Canadian Safety)

Europe

Low Voltage Directive (LVD)
– TUV-R GS Mark by German Notified
Body– EN60950:2000 (European Safety)

International

CB Scheme – IEC60950: 2000 with all
country deviations (International Safety)
Country · Mexico NOM/NYCE
(Product Safety & EMC Approval)
Specific · Australia/New Zealand AS/NZS
3260 (ACA DoC, Safety of ITE)
· Argentina S-Mark
· GOST (Russia)

Laser Safety

North

FCC 21 CFR subpart (J) (Safety of
Laser Products)

America

CDRH Letter of Approval (US
FDA Approval)

Europe

EN60825-2 (European Safety of Lasers)

EMI/EMC

North

FCC 47 CFR Part 15 Class A
(US Emissions)

America

ICES-003 Class A (Canada Emissions)

Europe 89/336/EEC EMC Directive

ETSI/EN 300 386:2001 (EU

Telecommunication Emissions

& Immunity)

EN55022:1998 Class A

(Europe Emissions)

EN55024:1998 includes IEC/EN

61000-2,3,4,5,6,11 (Europe Immunity)

EN 61000-3-2, -3 (Europe Harmonics
and Flicker)

International

IEC/CISPR 22:1997 Class A

(International Emissions)

IEC/CISPR 24:1998

(International Immunity)

IEC/EN 61000-4-2

Electrostatic Discharge

IEC/EN 61000-4-3 Radiated Immunity

IEC/EN 61000-4-4 Transient Bursts

IEC/EN 61000-4-5 Surge

IEC/EN 61000-4-6 Conducted Immunity

IEC/EN 61000-4-11 Power Dips

& Interruptions

Country

Japan Class A (VCCI Registration,
Emissions)

Specific

Australia/New Zealand AS/NZS 3548
(ACA DoC, Emissions)

Korean MIC Mark (MIC Approval,
Emissions & Immunity)

Mexico NOM/NYCE (Product Safety

& EMC Approval)

GOST (Russia)

Taiwan CNS 13438:1997 Class A

(BSMI Approval, Emissions)

Environmental

Standard:

EN 300 019-2-1 (2000-09) - Storage

Class 1.2 - Packaged

EN 300 019-2-2 (1999-09) -

Transportation Class 2.3 - Packaged

EN 300 019-2-2 (1999-09) - Stationary

Use at Weather Protected locations,

Class 3.1e - Operational

EN 300 753 (1997-10) - Acoustic Noise -

Operational

ASTM D5276 * - Drop – Packaged

ASTM D3332 * - Shock - Unpackaged

ASTM D3580 * - Random Vibration –

Unpackaged

ASTM D6179 * - Tilt – Packaged

*Additional testing requested by Extreme Networks

Acoustic

Summit 200-48: 51.6 dBA - Sound Pressure

Summit 200-24: 51.7 dBA - Sound Pressure

Reliability

MTBF

Calculated MTBF:

Summit 200-48: 123,000 hours

Summit 200-24: 150,000 hours

Method: Bellcore TR-332 Operating

@ 40° C

Warranty

Limited Lifetime Warranty

ExtremeWare 6.2e Supported

Protocols

General Routing and Switching:

RFC 1812 IPv4 Router Requirements

RFC 1519 CIDR

RFC 1256 IPv4 Router Discovery (IRDP)

RFC 783 TFTP

RFC 951, 1542 BootP

RFC 2131 BOOTP/DHCP relay agent

and DHCP server

RFC 1591 DNS (client operation)

RFC 1122 Host Requirements

RFC 768 UDP

RFC 791 IP

RFC 792 ICMP

RFC 793 TCP

RFC 826 ARP

ESRP-aware (Extreme Standby

Router Protocol)

IEEE 802.1D - 1998 Spanning

Tree Protocol

IEEE 802.1Q - 1998 Virtual Bridged

Local Area Networks

EAPS-Edge mode (Ethernet Automatic

Protection Switching, master and member

of one ring)

Quality of Service
 IEEE 802.1D -1998 (802.1p) Packet Priority
 RFC 2474 DiffServ Precedence,
 including 4 queues/port

Ingress Rate Limiting
 Layer 1-4 Policy-Based Mapping
 Policy-Based Mapping/Overwriting of
 DiffServ code points, .1p priority
 DLCS (Dynamic Link Context System,
 WINS snooping)

VLANs
 IEEE 802.1Q VLAN Tagging
 IEEE 802.3ad static configuration
 Port-based VLANs

RIP
 RFC 1058 RIP v1
 RFC 2453 RIP v2

OSPF
 RFC 2328 OSPF v2 (including MD5
 authentication) Edge-mode (up to 4
 adjacencies, cannot be designated or
 backup router)
 RFC 1587 OSPF NSSA Option
 RFC 1765 OSPF Database Overflow
 RFC 2370 OSPF Opaque LSA Option

IP Multicast
 RFC 1112 IGMP v1
 RFC 2236 IGMP v2
 IGMP Snooping with Configurable
 Router Registration Forwarding
 PIM SM (tentative availability)

Management - SNMP & MIBs
 RFC 1155 Structure of Mgmt
 Information (SMIv1)
 RFC 1157 SNMPv1
 RFC 1212, RFC 1213, RFC 1215 MIB-II
 & TRAPs

RFC 1901 – 1907 SNMP Version 2c,
 SMIv2 and Revised MIB-II
 RFC 1908 Coexistence between SNMP
 Version 1 and Version 2c
 RFC 1757 RMON 4 groups: Stats,
 History, Alarms and Events
 RFC 2021 RMON2
 (probe configuration)
 RFC 2668 802.3 MAU MIB
 RFC 1643 Ethernet MIB
 RFC 1650 Etherlike-MIB
 RFC 1573 Evolution of Interface
 RFC 1493 Bridge MIB
 RFC 1354 IPv4 Forwarding Table MIB
 RFC 2037 Entity MIB
 RFC 2233 Interface MIB (receive address
 group not supported)
 RFC 2096 IP Forwarding
 RFC 1724 RIPv2 MIB
 RFC 1850 OSPFv2 MIB
 ExtremeWare vendor MIB (includes
 MAC FDB, IP FDB, QoS policy and
 VLAN config)

Management - Other
 RFC 854 Telnet
 Secure Shell (SSHv2) and
 Telnet management,
 Telnet clients
 Configuration logging
 Multiple Images, Multiple Configs
 BSD System Logging Protocol
 (SYSLOG), with Multiple Syslog Servers
 999 Local Messages (criticals stored
 across reboots)
 RFC 2030 SNTP, Simple Network
 Time Protocol v4

Security
 Routing protocol authentication
 (see above)
 Secure Shell (SSHv2) with
 encryption/authentication

RFC 1492 TACACS+
 RFC 2138 RADIUS Authentication
 RFC 2139 RADIUS Accounting
 RADIUS Per-command Authentication
 Access Profiles on All Routing Protocols
 Access Profiles on All Management
 Methods
 Network Login (including DHCP /
 RADIUS integration)
 Network Address Translation (NAT)
 Layer 2/3/4 Access Control Lists (ACLs)

Denial of Service Protection
 Wire-speed ACLs
 Rate Limiting by ACLs

Security Against Common
 Network Attacks
CERT (<http://www.cert.org>)
 CA-2002-03: SNMP vulnerabilities
 CA-97.28: Teardrop_Land -Teardrop and
 "LAND " attack
 IP Options Attack
 CA-98-13: tcp-denial-of-service
 CA-98.01: smurf
 CA-96.26: ping
 CA-96.21: tcp_syn_flooding
 CA-96.01: UDP_service_denial
 CA-95.01: IP_Spoofing_Attacks_
 and_Hijacked_Terminal_Connections
Host Attacks (<http://www.rootshell.com>)
 Syndrop
 Nestate
 Latierra
 Newtear
 Bonk
 Winnuke
 Raped
 Simping
 Sping
 Ascend
 Stream

Ordering Information

Part Number	Name	Description
13240	Summit 200-24	Summit 200-24 with ExtremeWare edge software license
15040	Summit 200-48	Summit 200-48 with ExtremeWare edge software license
13243	Summit 200-24 Voucher	Advanced edge software license voucher for Summit 200-24
15042	Summit 200-48 Voucher	Advanced edge software license voucher for Summit 200-48

Accessories

Part Number	Name	Description
10051	SX mini-GBIC	mini-GBIC, SFP, 1000BASE-SX
10052	LX mini-GBIC	mini-GBIC, SFP, 1000BASE-LX
10053	ZX mini-GBIC	mini-GBIC, SFP, 1000BASE-ZX

For more product information from Extreme Networks, please call 1.888.257.3000. 3585 Monroe Street, Santa Clara, CA 95051-1450 Phone 408.579.2800
 Fax 408.579.3000 Email info@extremenetworks.com Web www.extremenetworks.com



© 2003 Extreme Networks, Inc. All rights reserved. Extreme Networks, BlackDiamond, Summit, Summit71, ExtremeWare, ServiceWatch, Extreme Ethernet Everywhere, Ethernet Everywhere, Extreme Velocity, Extreme Turbodriven and the color purple are registered trademarks of Extreme Networks, Inc. in certain jurisdictions. Alpine, ExtremeWare Vista, Extreme Standby Router Protocol, ESRP, Summit11, Summit14, Summit14/FX, Summit151, Summit124, Summit24e2, Summit24e3, Summit48, Summit481, SummitLink, SummitGbX, SummitRPS, SummitPx1, PXSilicon, EPICenter, vMAN, the BlackDiamond logo, the Alpine logo and the Extreme Networks logo are trademarks of Extreme Networks, Inc., which may be registered or pending registration in certain jurisdictions. ExtremeWorks, the Extreme Turbodriven logo and the Go Purple-Extreme Solution Partner logo are service marks of Extreme Networks, Inc., which may be registered or pending registration in certain jurisdictions. All other registered trademarks, trademarks and service marks are property of their respective owners. Specifications are subject to change without notice. L-DS-SUM200-308