





The **Guardian** is the latest innovation in vehicle-mount computing from AML. The combination of high-performance computing power and rugged design make the **Guardian** ideal for tough environments that require 24-7 reliability. Its small form-factor makes for better driver visibility and the optional keyboard caters to those applications with heavy data entry requirements. Adding to its versatility, the **Guardian** can also be used in fixed-mount applications, going where conventional PCs can't go.

Key Features:

Windows® Embedded Compact 7 OS

7" LCD Display w/ touch screen

802.11 g/b/n Wi-Fi

Process and Protect Your Data From a Forklift or Table-Top

With its compact size and +12V operating voltage, the **Guardian** is as much at home mounted in a vehicle or on a forklift, as it is in a warehouse or manufacturing plant. For non-hand-carry applications, the **Guardian** redefines ruggedness and versatility.

Applications:

- Inventory Control
- Asset Trackina
- Shipping/Receiving
- Check-In/Out
- Order Picking
- Work-in-Process



Physical Specs

Dimensions 231mm W x 159mm H x 42.75mm D; 9.09" W x 6.26" H x 1.68" D

Weight 1.13kg / 39.86 oz.

Display 7" LCD, 800x480 pixel resolution with integrated

resistive touch screen.

Power 12V (6~32V) DC input, 8W

Buttons/Keys Eight (8) push buttons with OS level functions:

Home, Brightness up, Brightness Down, Power, Menu, Panic, Volume up, Volume down

I/O Ports 2 x RS232;

1 x RS422;

1 x CAN Bus;

1 x USB Host;

1 x OTG;

1x LAN;

1 x SDHC;

1 x GPIO;

Microphone Jack

Speaker 2 x 2W

Performance Specs

Processor Freescale i.MX53 ARM Cortex-A8, processor

running up to 1GHz

Operating Platform Windows® Embedded Compact 7

Memory (RAM) Low power mobile DDR3 memory 512MB

Internal Storage iNAND memory 4GB

External Storage SD/SDHC card support (upto 32GB)

Wireless Data Communications

WLAN 802.11b/g/n Bluetooth Version 3.0

Mounting

Mounting VESA 50mm standard mount pattern



Optional Peripherals & Accessories

RAM™ Keyboard Mount



RAM™ Mount

Omni-Directional Scanner





Environmental Specs

Operating Temp -20° to ~60°C / -4° to ~140°F

Storage Temp -30° to $\sim 70^{\circ}$ C / -22° to $\sim 158^{\circ}$ F

Humidity 0 to 95% Sealing IP64

Specifications are subject to change without notice. All names and products are the trademarks or registered trademarks of their respective organizations.

Windows is a registered trademark of Microsoft Corporation in the United States and other countries.



Corporate Headquarters 2190 Regal Parkway Euless, Texas 76040

Sales & Customer Service Tel: 800-648-4452 Fax: 817-685-6232 Email: sales@amltd.com www.amltd.com Local: 817-571-9015 Fax: 817-571-6176

Technical Support Tel: 877-842-3990 Fax: 817-685-6232 Email: support@amltd.com

