

# **3800** Handheld Industrial Linear Imager



#### **Features**

Superior Read Range – imaging technology now extends the performance range out to 82 inches (208 cm) on linear codes. Long range reading performance eliminates the need to reach and climb to scan codes.

Fast and Aggressive Decode – Even on poorly printed or damaged codes, the 270 scans per second digital image logic is over 6 times faster than other technologies. Spend less time trying to re-scan poor codes and speed up the work process.

Rugged Packaging – An impact absorbing, shock resistant housing withstands fifty 6.5 foot (2 meter) drops, and is sealed to prevent dust, moisture, and other contaminants from entering the scanner. Designed to survive the most demanding industrial applications.

Durable – There are no moving parts to wear out and Hand Held Products backs this with an industry-leading 3 year warranty. Reliable performance year after year with no downtime.

Easy to Use – True point and shoot handheld ergonomics easily fits oversized gloved hands. Intuitive aiming means operators will become productive quickly.

The 3800i handheld industrial image readers are the first industrial class readers to bring you Hand Held Products industry-leading image technology. This technology allows you to read bar codes at ranges up to 82 inches (208 cm). In real world applications, this extended read range means less climbing and reaching, and more operator productivity.

Based on the proprietary image technology, the 3800i picks up your bar code image and processes its content 270 times per second. In a fraction of a second, the Hand Held Products digital image processor quickly and easily determines the data content and sends it to your host computer. This proprietary technology quickly and securely identifies poor quality symbols, and still delivers snappy performance.

We are so confident the 3800i image reader will withstand your industrial applications that we have backed it by a solid warranty. Every 3800i comes to you with a 3 year warranty against defects. Shock absorbing rubber overmold on the case and a sealed optics module ensure this device will survive dozens of 6.5 foot (2 meter) drops to concrete. Although we do not expect you to treat your reader this way, we know it will survive many years of accidental abuse.

Your industrial applications often take you into environments that challenge many devices. Your loading dock has extreme temperature variations, dirt, dust, and rain that will stress many bar code scanners. The 3800i is environmentally sealed to an IP54 rating, which prevents dust and water from entering the units and degrading performance. Sometimes you need to use this device outdoors during winter or other freezing temperature conditions. This imager withstands applications that subject it to constant -22°F (-30° C) temperatures and still survives.

For reading in applications that exhibit high ambient light, the 3800i can be ordered with an aiming beam, which offers true point and shoot performance without moving laser optics. This option allows the operator to reliably find and scan the code.

Contact your Hand Held Products representative at any of the locations listed on the back or visit us at **www.handheld.com**. See for yourself how Hand Held Products 3800i measures up!

### 3800i Specifications

#### Performance

Illumination:				_	f // 0000'
	630 nM Visible Red LED Ranges for the 3800i				
Receiving Device:	3648 element linear imager			Narrow Width	Depth of Field (300 Lux
Reading Width:	15 mil. code, 15 in. (38.1 cm) from nose, 10 in. (25.4 cm) wide				Lighting)
Resolution:	7.5 mil. at 9 in. (22.9 cm) distance			7.5 mil	6.5 - 15 in. (16.5 - 38 cm
Skew Angle:	<u>+</u> 65°			100% UPC 15 mil	2.5 - 28 in. (6.4 - 71 cm) 2.5 - 31 in. (6.4 - 78.7 cm
Pitch Angle:	<u>+</u> 65°			20 mil	1.5 - 42 in. (3.8 - 107 cm
Horizontal Velocity:	2 in. (5.1 cm) per second 55 mil 4.0 - 82 in. (10				
Minimum Symbol Contrast:	20%				
Scan Rate:	Up to 270 scans per second				
Decode Rate:	270 decodes per second				
Mechanical/Electrical					
Dimensions Length: Height Width: Weight:	without aimer 5.3 in. (13.5 cm) 6.4 in. (16.3 cm) 3.2 in. (8.1 cm) 7.5 oz. (213 g)		<u>with aimer</u> 5.3 in. (13.5 cm) 6.5 in. (16.5 cm) 3.2 in. (8.1 cm) 8.4 oz. (238 g)		
Housing:	UL 94V0 grade				
Power Requirements:	4.5 - 14Vdc at scanner				
Current Draw (maximum):	<u>Input</u> 5V 12V	<u>Scanning</u> 235mA 142mA	Idle 68mA 49mA		
Power Supply					
Noise Rejection:	Maximur	m 100mV pea	k to peak, 10 to 100 kHz		
Environmental					
cnvironmentai					
Temperature Operating:		+122ºF (-30ºC +140ºF (-40ºC			
Temperature Operating: Storage:	-40°F to	+140°F (-40°C	C to +60°C)		
Temperature Operating: Storage: Humidity:	-40°F to 0 to 95%	+140ºF (-40ºC 6, non-conden	C to +60°C) ⊎sing		
Temperature Operating: Storage: Humidity: Sealing:	-40°F to 0 to 95% IP54 (wa	+140°F (-40°C 5, non-conden ater and dust	C to +60°C) nsing resistant)		
Temperature Operating: Storage: Humidity: Sealing: Mechanical Shock:	-40°F to 0 to 95% IP54 (wa Operatio	+140°F (-40°C 6, non-conden ater and dust anal after 50 d	C to +60°C) ⊎sing		
Temperature Operating: Storage: Humidity: Sealing: Mechanical Shock: Ambient Illumination:	-40°F to 0 to 95% IP54 (wa Operatio 0 - 70,00	+140°F (-40°C 5, non-conden ater and dust nal after 50 d 00 lux	c to +60°C) Ising resistant) Irops from 6.5 ft. (2 m) to concrete		
Temperature Operating: Storage: Humidity: Sealing: Mechanical Shock: Ambient Illumination: ESD Protection:	-40°F to 0 to 95% IP54 (wa Operatio 0 - 70,00 Function	+140°F (-40°C 6, non-conder ater and dust anal after 50 d 20 lux al after 15kV	c to +60°C) nsing resistant) Irops from 6.5 ft. (2 m) to concrete discharge		
Temperature Operating: Storage: Humidity: Sealing: Mechanical Shock: Ambient Illumination:	-40°F to - 0 to 95% IP54 (wa Operatio 0 - 70,00 Function Class 1 u Class 2 u	+140°F (-40°C 6, non-conder ater and dust anal after 50 d 00 lux al after 15kV under EN6082 under 21 CFR	c to +60°C) nsing resistant) Irops from 6.5 ft. (2 m) to concrete discharge		
Temperature Operating: Storage: Humidity: Sealing: Mechanical Shock: Ambient Illumination: ESD Protection: LED Classification: Laser Classification	-40°F to 0 to 95% IP54 (wa Operatio 0 - 70,00 Function Class 1 u Class 2 u 1mW ma	+140°F (-40°C 6, non-conder ater and dust anal after 50 d 20 lux al after 15kV under EN6082 under 21 CFR ax output, 650	c to +60°C) nsing resistant) Irops from 6.5 ft. (2 m) to concrete discharge 25-01		
Temperature Operating: Storage: Humidity: Sealing: Mechanical Shock: Ambient Illumination: ESD Protection: LED Classification: Laser Classification Aimer Beam only:	-40°F to 0 to 95% IP54 (wa Operatio 0 - 70,00 Function Class 1 to Class 2 to 1mW ma	+140°F (-40°C 6, non-conder ater and dust anal after 50 d 00 lux al after 15kV under EN6082 under 21 CFR ax output, 650 ads 5G peak f	C to +60°C) Ising resistant) Irops from 6.5 ft. (2 m) to concrete discharge 25-01 C 1040.10 and 1040.11 nM, EN60825-1: 1994+A11+A2	ed, TÜV	
Temperature Operating: Storage: Humidity: Sealing: Mechanical Shock: Ambient Illumination: ESD Protection: LED Classification: Laser Classification Aimer Beam only: Vibration:	-40°F to 0 to 95% IP54 (wa Operatio 0 - 70,00 Function Class 1 u Class 2 u 1mW ma Withstan FCC Cla	+140°F (-40°C 6, non-conder ater and dust anal after 50 d 00 lux al after 15kV under EN6082 under 21 CFR ax output, 650 nds 5G peak f ass B, CE EM0	C to +60°C) using resistant) Irops from 6.5 ft. (2 m) to concrete discharge 25-01 C 1040.10 and 1040.11 nM, EN60825-1: 1994+A11+A2 rom 22 to 300 Hz		
Temperature Operating: Storage: Humidity: Sealing: Mechanical Shock: Ambient Illumination: ESD Protection: LED Classification: Laser Classification Aimer Beam only: Vibration: Agency:	-40°F to 0 to 95% IP54 (wa Operatio 0 - 70,00 Function Class 1 u Class 2 u 1mW ma Withstan FCC Cla per MIL-I Codabar	+140°F (-40°C 6, non-conder ater and dust unal after 50 d 00 lux al after 15kV under EN6082 under 21 CFR ax output, 650 ads 5G peak f iss B, CE EM0 HDBK-217F (	C to +60°C) Ising resistant) Irops from 6.5 ft. (2 m) to concrete discharge 25-01 1040.10 and 1040.11 nM, EN60825-1: 1994+A11+A2 rom 22 to 300 Hz C Class B, CE Low Voltage Directive, UL, cUL liste	ner, 91,000 hours with aimer	3, Code 128, UPC, EAN/JAN,
Temperature Operating: Storage: Humidity: Sealing: Mechanical Shock: Ambient Illumination: ESD Protection: LED Classification: Laser Classification Aimer Beam only: Vibration: Agency: MTBF:	-40°F to - 0 to 95% IP54 (wa Operatio 0 - 70,00 Function Class 1 to Class 2 to 1mW ma Withstan FCC Cla per MIL- Codabar China Po All popul TTL leve	+140°F (-40°C 6, non-conder ater and dust unal after 50 d 00 lux al after 15kV under 21 CFR ax output, 650 ds 5G peak f ass B, CE EM0 HDBK-217F (C r; Code 39 inc ost, RSS. lar PCs and ta 4 RS-232, TTI on-decoded la	C to +60°C) Ising resistant) Irops from 6.5 ft. (2 m) to concrete discharge 25-01 C 1040.10 and 1040.11 nM, EN60825-1: 1994+A11+A2 rom 22 to 300 Hz C Class B, CE Low Voltage Directive, UL, cUL liste Ground Benign exceeds 100,000 hours without air	ner, 91,000 hours with aimer atrix 2 of 5, Code 11, Code 9	3, Code 128, UPC, EAN/JAN,



## Worldwide Offices

World wide Offices Offices Serving North America Skaneateles Falls, NY Tel: +1 315 685 8945 or, in North America: +1 800 582 4263 napresales@handheld.com Charlotte, NC Tel: +1 704 998 3998 or, in North America: +1 800 582 4263 napresales@handheld.com

### Offices Serving Europe, Middle East, and Africa

Middle East, and Africa Europe Tel: +31 (0) 40 29 01 600 eupresales@handheld.com United Kingdom Tel: +44 (0) 1 925 240055 eupresales@handheld.com Italy Tel: +39 (0) 2 67 100752 eupresales@handheld.com

France Tel: +33 (0) 1 41 158220 eupresales@handheld.com Germany Tel: +49 (0) 7 477 151377 eupresales@handheld.com Spain Tel: +34 93 228 78 68 eupresales@handheld.com

Offices Serving Asia and the Pacific Rim Hong Kong Tel: +852 2511 3050 appresales@handheld.com Japan Tel: +813 5770 6312 appresales@handheld.com Shanghai Tel: +86 21 6361 3818 appresales@handheld.com

Offices Serving Latin America Naples, Florida Tel: +1 239 263 7600 lapresales@handheld.com lapresales @ handheld.com São Paulo Tel: +55 11 2178 0500 lapresales @ handheld.com *Rio De Janeiro* Tel: +55 21 2178 0500 lapresales @ handheld.com *Mexico* Tel: +52 55 5203 2100 lapresales @ handheld.com

Web Site Address www.handheld.com Hand Held Products, Inc., ("Hand Held Products") <sup>©</sup> 1999-2006. All rights reserved. Printed in the U.S.A. Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.