



The NEW HT682

High Performance, High Value

The new HT682 handheld computer is faster, stronger, and more powerful than ever before. Unitech is proud to build off the success of the previous HT680 handheld by upgrading the device with all new features. It's equipped with extra memory, a lightning-fast processor, and Windows CE 6.0 Pro to automate your data collection applications quickly and efficiently.

The new HT682 is protected with an IP65 environmental seal, enabling it to withstand even the roughest of working environments. Dust, moisture, and even water spills are no match for the HT682, decreasing overall downtime. By keeping your workflow uninterrupted, the HT682 offers an outstanding return on your investment and reduces total cost of ownership more than ever before.



Target Markets & Applications

Target Markets & Applications		
Retail	Restocking Price Management Returns Processing	Obtain visibility into available stock Improve customer satisfaction
Manufacturing	Tool Crib Asset Tracking Work-in-Process (WIP)	Speed material flow Reduce production downtime
Light Warehousing	Receiving Pick/Pack/Ship	Keep visibility of in-bound and out-bound packages Reduce inventory loss
Transportation	Proof-of-Delivery Returns	Increase driver productivity Improve visibility into inventory requirements

HT682 vs The Competition

	OS: Windows CE 6.0	6-Foot Drop Spec	IP65 Environmental Seal	Standard 512MB Memory
Unitech HT682	X	X	X	X
Datalogic Skorpion X3	X			
Honeywell 6100 Dolphin				
Motorola MC3100	X			

All trademarks are copyright of their respective owners.

Specifications

System		Audio	Mono Speaker, 90db@ 4-Inch Distance
CPU	TI OMAP AM3703, 800MHz		
Memory	SD RAM: 512MB Flash ROM: 512MB	Enclosure	
OS	Windows CE 6.0 Pro	Weight	11 Ounces (With Battery)
		Dimensions	6.69" H x 2.1" W x 1.18" D
Display	2.8" QVGA, Color Transflective TFT with Touch Screen & Backlight	Environmental	
		Operating temperature	14°F to 122°F
Keypad	22 Keys, Including 4 Direction, Function, and Numeric Keys.	Storage temperature	-4°F to 140°F
		Relative humidity	5% ~ 95% (Non-Condensing)
Indicator	LEDs, Vibrator	Drop tested	6-Foot
		Environmental sealing	IP65
Expansion Slot		Software	Microsoft Visual Studio 2005 / 2008 Unitech Handheld Terminal SDK
Micro SD	Supports SDHC up to 32GB	Accessories	Gun Grip Leather Case Single Slot USB Cradle 4-Slot Battery Charger 2200mAH Standard Battery 4000mAH Extension Battery USB Communication and Charging Cable Power Adaptor with Universal Plugs
Symbologies		Regulatory Approvals	CE, NCC, FCC, BSMI, VCCI, CCC, RoHS Compliance
1D Laser	UPC-A/E, EAN-8/13, Codabar, Code 39, Code 39 full ASCII, Code 93, Code 32, Interleaved & Std. 2 of 5, EAN 128, Code 11, Delta, MSI/Plessey, Code 128, Toshiba, RSS Expanded, RSS Limited, RSS14.	Available Model	HT682-9460UADG Laser, WiFi, Bluetooth, CE 6.0 Pro, Battery, USB Cable, Power Adaptor
Communication			
USB	USB V2.0 Host & Client		
WLAN	CCX V4 Certified Summit Radio 802.11 B/G/N WEP, WPA, WPA2, WEP, TKIP, RC4 Algorithm, AES, Rijndael Algorithm, Static (40-bit and 128-bit lengths), Pre-Shared (PSK), Dynamic EAP-FAST, EAP-TLS, EAP-TTLS, PEAP-GTC		
PAN	Bluetooth 2.1 + EDR		
Power Source			
Main battery	8.14 Watt/Hour 3.7V @ 2200mAh 16.28 Watt/Hour 3.7V @ 4400mAh		
Backup battery	Backup Capability Over 72 hrs		

Certified By:

