

HAND HELD SCANNER RANGE

Sabre™ 1552 and MicroBar™ 9745

Benefits:

- Cordless design eliminates cables for safer and more reliable scanning
- Durable design withstands the harshest environments
- Comfortable and lightweight for easy use
- “Smart” battery packs with integral charger eliminate the need for a separate charger
- Up to ten scanners can interface to a single base station for lower acquisition costs
- Unlicensed radio frequency transmission for maximum application flexibility



The Sabre 1552 Cordless Scanner provides unparalleled flexibility in scanning bar code. Jobs are easier because there is no cable to damage. No cable to become entangled either. You can take the Sabre 1552 with you, to the job, up to 50 feet from a MicroBar 9745 RF Base Station—because both the 1552 and the 9745 use Intermec’s PicoLink™ wireless personal area network. PicoLink operates using an unlicensed 2.4GHz radio frequency (RF) hopping design that has global regulatory acceptance and superior interference immunity versus other narrow band RF sources.

Multiple scanners—up to ten—can interface to a single MicroBar 9745 RF Base Station. This gives users unparalleled flexibility in

locating host terminals throughout the work area. Lower acquisition costs too... fewer base stations and fewer host terminal connections are required. Users can also choose from keyboard wedge, RS 232, POS terminal or wand emulation interfaces, and standard, long range, high density and high visibility laser scan engines for additional application versatility.

The 1552 Cordless Scanner is the latest member of the Sabre family of industrial performance scanners. Users will benefit from its ability to withstand the harshest environments—windblown rain and dust, arctic to desert temperature ranges, off-road vehicle levels of vibration and multiple six-foot drops to concrete.

Sabre™ 1552 and MicroBar™ 9745

Physical Characteristics

Scanner Length: 8.9 cm (3.5")

Scanner Height: 21.6 cm (8.5")

Scanner Width: 5.6 cm (2.5")

Scanner Weight: 426 g (15 oz.) including battery

Base Station Length: 11.4 cm (4.5")

Base Station Height: 3.8 cm (1.5")

Base Station Width: 8.9 cm (3.5")

Base Station Weight: 206 g (7.2 oz.) without cable

Optics System

Visible laser diode:

650nm±10nm
(Long range, high visibility)

670nm±10nm
(standard range, high density)

USA/Canada Class II

International Class 2

Scan rate: 36±3 scans per second

Optical Parameters

Pitch: ±65° from normal

Skew: ±55° from normal

Depth of field-Standard Range*:

5 mil	8.1-14.5 cm	3.2-5.7"
7.5 mil	7.4-22.6 cm	2.9-8.9"
10 mil	6.1-34.0 cm	2.4-13.4"
15 mil	6.1-46.7 cm	2.4-18.4"
20 mil	8.9-62.2 cm	3.5-24.5"
40 mil	11.4-99.1 cm	4.5-39"
55 mil	17.8-124.5 cm	7-44"
55 mil (retroreflective)	104-150 cm	41-59"
100 mil (retroreflective)	112-226 cm	44-89"

Depth of field-Long Range*:

10 mil	27.9-98.3 cm	11-19"
15 mil	20.3-83.8 cm	8-33"
20 mil	20.3-96.5 cm	8-38"
40 mil	22.9-190.5 cm	9-75"
55 mil	22.9-203 cm	9-80"
70 mil (retroreflective)	190.5-408.9 cm	75-161"
100 mil (retroreflective)	210.8-530.9 cm	83-209"

Depth of field-High Visibility*:

5 mil	7.4-11.2 cm	2.9-4.4"
7.5 mil	4.8-18.8 cm	1.9-7.4"
10 mil	4.6-22.9 cm	1.8-9"
15 mil	3.8-35.6 cm	1.5-14"
20 mil	5.1-48.3 cm	2-19"
40 mil	10.2-78.7 cm	4-31"
55 mil	16.5-88.9 cm	6.5-35"

Depth of field-High Density*:

2 mil	1.8-3.9 cm	.7-1.8"
3 mil	3.8-7.0 cm	1.5-2.8"
5 mil	3.8-11.9 cm	1.5-4.7"
13 mil	3.8-14.7 cm	1.5-5.8"

*Depth of field measured using Code 39, ANSI Grade A

Print Contrast

Minimum 40% reflectance difference (long range). Minimum 25% reflectance difference (standard range, high visibility)

Ambient Light Immunity

Immune to direct exposure from office level lighting and sunlight

Environment

Operating Temperature:

-20° to 50°C (-22° to 122°F)

Storage Temperature:

-40° to 70°C (-40° to 168°F)

Battery Storage Temperature:

-30° to 60° C (-22° to 140°F)

Humidity:

0-95% non-condensing

Durability-Scanner:

26 six foot drops to concrete

Vibration:

Class 3 SAE off-road vehicle specification

Environmental:

Scanner sealed against windblown rain and dust (IEC 529 rated at IP54). Base station rated at IP53.

ESD:

Conforms to 15 KV rating per IEC 801-2

EMI Emissions:

Conforms to Class A FCC Part 15, RSS 210 and CISPR 22 Class B

Approvals:

UL & cUL listed, C22.2 No. 950/UL 1950, TUV Rheinland GS Licensed EN 60950, EN 60825-1, CE marked, C-Tick marked

PicoLink™ Radio

Range: Up to 15 meters (50 feet) and 20 coexisting systems consisting of 10 nodes each. (Maximum of 200 nodes)

Frequency: Unlicensed 2.4 GHz multi-point-to-point frequency hopping

Power Output: <1mW

Data Transmission: 1 Mb/s aggregate data rate

Approvals: FCC Part 15.249, ETS 300 328, RSS 210, NOM-EM-121-SCTI-1994, RCR 33

Base Station

Interface: RS-232C, IBM PC XT/AT or PS/2 Mod 30 compatible, ADI 1496, Falco 5220, Harris H180, 191, IBM 3151/316X/317X/318X/319X/347X, DEC VT220/320/420 DEC PC 510/520/525 Olivetti M19, M200, M240, M250, M380, P500, Silicon Graphics Indy, Indigo II, Televideo 990, Wyse 30, 60, 85/185, 120, 150, 160, 325, 370, Apple MAC ADB, laptop computers, Zenith Cruise Pad

Input Devices: Accepts separate input device through auxiliary port

Power: 4.5 to 14.5 VDC

Data Formatting: Nine complete data editing groups



Battery Packs

600 mAh 90-135 VAC, 50Hz/60Hz, NiCad with integral charger and 8 hour charge time

800 mAh 90-135 VAC, 50Hz/60Hz NiMH with integral charger and 4 hour charge time

Accessories

2-bay and 6-bay charge strips for battery packs available, vehicle mount holder for scanner, wall mount holder for scanner, belt clip for base station, wall mount clip for base station, holster and belt



Where Information Gets Down To Business™

Internet • www.intermec.com E-mail • info@intermec.com Telephone • 800-347-2636 (toll free in N. Am.) Service and Support • 800-755-5505 (toll free in N. Am.)

North America ▶ Headquarters • 6001 36th Avenue West, Everett, WA 98203-9280, tel: 800-347-2636 (toll free in N. Am.), fax: 661-775-4440
Norand Mobile Systems Division • 550 2nd Street S.E., Cedar Rapids IA 52401, tel: 800-452-2757 (toll free in N. Am.), fax: 319-369-3453
Amtech Systems Division • 19111 Dallas Parkway, Suite 300, Dallas, TX 75287-3106, tel: 800-923-4824 (toll free in N. Am.), fax: 972-733-6699
Label Products & Supplies • tel: 800-227-9947 (toll free), 513-874-5882 (direct), fax: 800-227-1707 (toll free), 513-874-8487 (direct)

Europe / Middle East & Africa ▶ Sovereign House, Vastern Road, Reading, Berkshire, RG1 8BT United Kingdom, tel: 44-118-987-9400, fax: 44-118-987-9401

Asia Pacific/ Latin America ▶ Hong Kong • 26-12 Shell Tower, Times Square, 1 Matheson Street, Causeway Bay, tel 852-2574-9777, fax 852-2574-9725
Singapore • #25-16 International Plaza, 10 Anson Road, 079903, tel: 65-324-8391, fax: 65-324-8393
Australia • 15 Stamford Road, Oakleigh Victoria 3166, tel: 61-3-9563-0000, fax: 61-3-9563-4000
South America and Mexico • 2572 White Road, Irvine, CA 92614, tel: 949-975-1905 Ext. 1939, fax: 949-975-1827

Worldwide Fax Document Retrieval Service • tel: 800-755-5505 (toll free in North America), 650-556-8447 (direct)

Copyright © 1999 Intermec Technologies Corporation. All rights reserved. All trademarks are the property of their respective owners. Contents subject to change. Printed in the U.S.A. #608524B 8/99

