

HAND HELD SCANNER

ScanPlus 1800 Vista™

Benefits:

- **Exceptional reading performances: very fast, for contact and non contact applications (up to 49.2 cm/19.4")**
- **Read long, damaged, poorly printed barcodes and extremely small bar widths (0.05mm, (2mils))**
- **Long life time and high reliability**
- **Light weight, bright and sharp scan line for easy use**
- **Harmless illumination for a safer working environment**
- **Cost efficient for contact and non-contact scanning**



Combining the benefits of CCD & Laser technologies, the ScanPlus 1800 Vista is the ultimate user's choice. New Intermec developments in decoding and scanning resulted in:

Unique reading performances - The S1800VT succeeds in reading barcodes at 49.2 cm (19.4") distance with a scan rate of up to 225 scan/sec. Snappy response and easy aiming makes it very comfortable to use.

Also, it can read any type of codes, whether they are poorly printed, damaged, 18cm (7") long, or if they incorporate code 39 with a barcode width of 0.05mm/0.2mil (unique in the market place). It is operational in any lighting conditions, from total darkness to full exposition to sun light (100,000 lux).

Comfortable to use - The S1800VT inherits the ergonomics and light shape of the ScanPlus 1800 family. Aiming is very easy thanks to the sharp and bright scanning line (specific LED system).

Reliability - The S1800VT incorporates no moving parts. For this reason, it has a longer life than any laser scanner. It withstands multiple drops to concrete from 1m (3.2') and can be used in a wide temperature range.

Flexibility - ScanPlus 1800 Vista is compatible for contact and non contact applications. Also, it is compatible with more than 400 host interfaces, including OLEpos and USB. All standard 1D symbologies are available, as well as PDF 417. Future upgrades or special applications are easily implemented using flash memory.

Safe to use - Laser scanners can be harmful if the user looks accidentally into the beam. For ScanPlus 1800 Vista, the illumination is produced by LEDs that are absolutely safe for the user.

Cost efficient solution - Unique reading performances, snappy, extended reading distance, reliability, flexibility, safety, ergonomics, easy set up... All these benefits gathered at an extremely competitive price. In fact, the S1800VT is the answer for most of the applications and for all budgets. As any member of the ScanPlus 1800 range, the S1800 VT is compatible with EasySet™ set up software for the fastest on line or off line configuration.

ScanPlus 1800 Vista™

General Description

A high performance and compact CCD handheld scanner for non-contact applications. Designed for Retail, Health Care, Office & light Industrial environments.

Scanning performances

Scanrate: S1800 VT: 225scan/s

Min. x dimension: down to 0.05mm (2 mil) (Intermec decoding technology)

Depth of field : from 0cm to 49.2cm (19.4")

Bar width		Max. distance*		Max. distance on code 39 **	
mm	mil	cm	inch	cm	inch
0.1	4	16.2	6.4	23.0	9.0
0.2	8	23.0	9.0	26.4	10.4
0.3	12	26.2	10.3	36.0	14.17
0.5	20	34.5	13.6	49.2	19.4
1	40	49.2	19.4	49.2	19.4

* From scan-engine

** Advanced Intermec decoding technology used

Bar code width: up to 18cm (7") on 0.3mm/12mil resolution code

Print Contrast: down to 25%

Scan Angle: 48°

Skew: +- 35°

Pitch: +- 35°

Bar Codes Supported

UPC (E&A); EAN; Code 39; Intervealed Matrix, Industrial & Standard 2 of 5; Code 128, UCC EAN 128, Codabar, Code 93, ISBN, MSI, Plessey, Telepen,

Host interfaces:

USB, OLEpos, Wand & Laser emulation, single/dual RS232, IBM 46xx, OCIA, HP700/xx, PC AT/PS2 wedge to over 400 terminals & PC. Extensive interface information on application.

Operator feedback

Green good read LED. Adjustable beeper.

Design Features

Processor: Custom chip (ASIC inc. DSP processor) for fast signal processing and decoding. Flash memory.

Optics: 645 nm visible red Top LED. Bright & sharp scanning line.

Environmental Characteristics

Operating Temperature:

0 - 50°C (32 - 122°F)

Storage Temperature:

-25 - 70°C (-11 - 160°F)

Relative humidity: 5% to 95% (non condensing)

Shock: withstands multiple 1m (3.2') drops to concrete

Ambient illumination: works in any lighting condition, from 0 to 100,000 lux.

Electrical characteristics

S1800 VT: 140mA (average) and 40mA (stand by)

Physical Characteristics

Length: 180mm (7")

Width at handle: 33mm (1.3')

Width at head: 64mm (2.5")

Standard cable: 1.8m (70")

Weight without cable: 140g

Case: High-impact ABS self-extinguishing plastic. Rubber end cap and boot.

Special Features

Firmware updates via flash memory, programmable data format (code identification, preambles & postambles, intercharacters & intermessage delays, variable time-out, and many others).

Configuration

Fast & easy set up with EasySet™ Windows software

Accessories

Desk/vertical holder

Raised hands-free stand (option)

Regulatory approvals

UL Listed, TÜV-GS, NOM certified.

Complies with FCC rules part 15, CE mark, Australian C-TIC, Canadian ICES 003.

Internet • www.intermec.com **Sales** • 800.347.2636 (toll free in North America) **Service and Support** • 800.755.5505 (toll free in North America)

North America
 Corporate Headquarters • 6001 36th Avenue West, Everett, Washington 98203, tel: 425.348.2600, fax: 425.355.9551
 Systems & Solutions • 550 2nd Street S.E., Cedar Rapids, Iowa 52401, tel: 319.369.3100, fax: 319.369.3453
 Media Supplies • 9290 Le Saint Drive, Fairfield, Ohio 45014, tel: 513.874.5882, fax: 513.874.9018

Europe/Middle East & Africa
 Headquarters • Sovereign House, Vastern Road, Reading Berkshire RG1 8BT, United Kingdom, tel: +44.118.987.9400, fax: +44.118.987.9401
 Gothenburg • Idrottsvägen 10, P.O. Box 123, SE-431 22 Mölndal, Sweden, tel: +46.31.869500, fax: +46.31.869595

Asian Pacific/Latin America
 Hong Kong • 26-12 Shell Tower, Times Square, 1 Matheson Street, Causeway Bay, Hong Kong, tel: 852.2574.9777, fax: 852.2574.9725
 Singapore • 25-16 International Plaza, 10 Anson Road, 079903, tel: 65-324.8391, fax: 65-324.8393
 Australia • 15 Stamford Road, Oakleigh, Victoria 3166, tel: 61.3.9563.0000, fax: 61.3.9563.4000
 South America and Mexico • 2572 White Road, Irvine, California 92614, tel: 949.975.1905, fax: 949.975.1913

Worldwide Fax Document Retrieval Service • 800.755.5505 (North America Only) • tel: 650.637.2603

Copyright © 2000 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 609058 6/00

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.