

## Product Profile

- Available in multiple configurations
- Wall mount configuration for step van and settlement room applications
- Easy loading of up to 3-ply paper from internal or external paper trays
- 512k flash memory can store DBCS fonts such as Korean and Chinese
- Optional HHC holders and docks for Intermec® 6000, 600, 700 Series mobile computers
- Fast two-page-per-minute print time helps get the work done fast
- Easy Flexibility



### 6 8 2 0 P R I N T E R

The Intermec® 6820 printer produces high-quality customer invoices, receipts, load reports, transfers and other documents for route accounting applications. Data input is provided by the Intermec 6000 Series mobile computers via holders and vehicle docks.

#### Portable

The Intermec 6820 portable printer provides flexibility and mobility. It features a handle for easy carrying and a compact tray which holds enough paper for an entire day. A seat-mount strap is available to secure the printer in vehicles with bench seats. An optional, soft-sided carrying case provides a sealed compartment inside the case cover for storage of invoices.

#### Fixed Mount

The fixed mount model is ideal for applications where mounting the printer in a vehicle is preferred. The mobile computer holder can be mounted either

to the side of the printer or remote from the printer, whichever is most convenient. Although the printer is safely mounted to the vehicle, a quick release feature allows one-step removal of the printer for swapping from one vehicle to another.

#### Wall Mount

The wall mount printer can be mounted on rugged vertical surfaces in trucks and settlement rooms. It is ideal for installations where space is limited. A quick release allows one-step removal for swapping from one vehicle to another. Optional paper trays hold paper for multiple route days. All configurations work with existing software applications for the Intermec 4820 printer.

**Portable (245-190-200)**

Optional handle, AC foot, 61xx or 62xx terminal holder top mount.

**Physical Characteristics**

**Standard:** Handle, 62xx holder top mount or fill plate

**Length:** 38.1cm (15")

**Width:** 41.9cm (16.5")

**Depth:** 13cm (5.13")

**Weight:** 5.67kg (12.25 lbs.)

**Portable with AC Foot (245-190-201)****Physical Characteristics**

**Length:** 38.1cm (15")

**Width:** 48.3cm (19")

**Depth:** 13cm (5.13")

**Weight:** 5.67kg (12.25 lbs.)

**Custom:** Handle, 61xx holder top mount

**Length:** 42.6cm (16.75")

**Width:** 48.3cm (19")

**Depth:** 20.3cm (8")

**Weight:** 5.80kg (12.75 lbs.)

**Wall Mount (245-190-204)****Physical Characteristics**

**Length:** 26.7cm (10.5")

**Width:** 33.7cm (13.25")

**Depth:** 11.4cm (4.5")

**Weight:** 6.42kg (14.15 lbs.)

**Fixed Mount (245-190-202)**

- Base is 32.5cm (12.75") x 35.5cm (14"). The upper portion may include either the 61xx or 62xx terminal holder.

- Refer to the 6820 printer user's guide (961-019-013) for specific configurations for the following:

- Custom with 61xx terminal holder side mount

- Custom with 61xx or 62xx terminal holder top mount

**Physical Characteristics**

**Length:** 36.8cm (14.5")

**Width:** 47cm (18.5")

**Depth:** 20.3cm (8")

**Weight:** 6.55kg (14.4 lbs.)

**Fixed Mount (245-190-203)**

62XX hhc terminal holder side mount

**Physical Characteristics**

**Length:** 36.8cm (14.5")

**Width:** 47cm (18.5")

**Depth:** 20.3cm (8")

**Weight:** 6.55kg (14.41 lbs.)

**Fixed Mount (245-190-400)****Physical Characteristics**

**Length:** 42.6cm (16.75")

**Width:** 42.5cm (16.75")

**Depth:** 19.1cm (7.5")

**Weight:** 6.55kg (14.41 lbs.)

**Portable (245-190-401)****Physical Characteristics**

**Length:** 42.6cm (16.75")

**Width:** 41.9cm (16.5")

**Depth:** 20.3cm (8")

**Weight:** 5.8kg (12.75 lbs.)

**Portable (245-190-402)****Physical Characteristics**

**Length:** 42.6cm (16.75")

**Width:** 41.9cm (16.5")

**Depth:** 20.3cm (8")

**Weight:** 5.8kg (12.75 lbs.)

**Environment****DC Operating Temperature:**

-20° to 60°C (-4° to 140°F)

**AC Operating Temperature:**

-20° to 45°C (-4° to 113°F)

**Storage Temperature:**

-30° to 70°C (-22° to 158°F)

**Power**

**Vehicle:** low amperage draw; protection from voltage irregularities

**Lead Acid Battery:** 12-volt standard cam-corder type. Full charge will print dozens of tickets. Time to recharge is one hour.

**AC Adapter:** 115/230 volt

**Printer Mechanism**

**Characteristics:** Dot matrix, Bi-directional, Graphics capable

**Print speed:** 2 pages per minute

**Type styles:** char/line: Normal 80, Bold 40, Condensed 136, Bold condensed 68

**Paper**

1 to 3-ply fan fold, 7.5" to 8.5" x 11", Carbonless, NCR paper with adhesive tacking on left border

**Ribbon**

- One color cartridge, black, one million character life
- One color cartridge, purple, one million character life

**Regulatory Approvals**

FCC Class B, CE mark

**Note**

Some approvals and features may vary by country and may change without notice. Specs may vary based upon the specific configuration or features selected. Please check with your local Intermec sales office for further information.

**North America**

Corporate Headquarters  
6001 36<sup>th</sup> Avenue West  
Everett, Washington 98203  
tel: 425.348.2600  
fax: 425.355.9551

**Systems & Solutions**

550 2<sup>nd</sup> Street S.E.  
Cedar Rapids, Iowa 52401  
tel: 319.369.3100  
fax: 319.369.3453

**Media Supplies**

9290 Le Saint Drive  
Fairfield, Ohio 45014  
tel: 513.874.5882  
fax: 513.874.8487

**Europe/  
Middle East & Africa**

Headquarters  
Sovereign House  
Vastern Road  
Reading, Berkshire RG1 8BT  
United Kingdom  
tel: +44.118.987.9400  
fax: +44.118.987.9401

**Gothenburg**

Idrottsvägen 10  
P.O. Box 123  
SE-431 22 Mölndal  
Sweden  
tel: +46.31.869500  
fax: +46.31.869595

**Asia Pacific/  
Latin America**

Hong Kong  
26-12 Shell Tower  
Times Square  
1 Matheson Street  
Causeway Bay  
Hong Kong  
tel: 852.2574.9777  
fax: 852.2574.9725

**Singapore**

25-16 International Plaza  
10 Anson Road, 079903  
tel: 65.324.8391  
fax: 65.324.8393

**Australia**

Level 7, 200 Pacific Highway  
Crows Nest NSW 2065  
Australia  
tel: 61.2.9901.2065  
fax: 61.2.9954.6300

**South America and Mexico**

2572 White Road  
Irvine, California 92614  
tel: 949.975.1905  
fax: 949.975.1913

**Worldwide**

**Fax Document Retrieval Service**  
800.755.5505  
(North America Only)  
tel: 650.556.8447

**Internet**

www.intermec.com

**Sales**

800.347.2636  
(toll free in N.A.)  
425.348.2726

**Service and Support**

800.755.5505  
(toll free in N.A.)  
425.356.1799

Copyright © 2001 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 608961-01C 05/01

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.