

## Product profile

# PB<sub>2</sub>/PB<sub>3</sub>

## Commercial Mobile Receipt Printers



- Compact and lightweight for all-day use
- Compatible with popular Intermec CN3 Series, 700 Series and CK3 mobile computers
- Long life, field replaceable batteries
- Choice of Bluetooth®, WLAN, or IrDA communications, plus standard Serial
- On-board memory supports resident fonts, logos, graphics
- Optional magnetic stripe reader
- Optional environmental case for adverse conditions

Comfortable enough to wear all day, the lightweight and compact Intermec PB2/PB3 two- and three-inch commercial receipt printers meet the needs of the mobile workforce in DSD/route accounting, retail queue busting and field service applications. Long-lasting, field replaceable batteries and weather-resistant construction ensure the PB2/PB3 delivers dependable, all-day service, whenever and wherever required.

The ideal companion to Intermec world-class mobile computers and scanners, the PB2/PB3 printer interfaces seamlessly via Bluetooth® or 802.11g with the CN3 and 700 Series handheld computers, as well as with the new Intermec CK3. The PB2/PB3 also has the ability to print from a wide range of handheld devices and smart phones to produce receipts on demand. Available with optional card reader, the PB2/PB3 gives workers the flexibility to accept payments via their mobile computer or their printer. Either way, the combination supports increased productivity and customer satisfaction, enabling workers to process payments on the go and generate receipts immediately.

The PB2/PB3 and its accessories are designed for easy mobility. The most compact and lightweight of Intermec's

mobile printers, the PB2/PB3 can be comfortably worn all day, using the included belt clip or optional shoulder strap for convenient, hands-free operation. For added protection in outdoor applications such as issuing electronic citations and processing car rental returns, the PB2/PB3 offers an optional IP54-rated environmental case that provides extra weather resistance without affecting mobility.

With multiple connectivity options and robust, field-replaceable batteries, the PB2/PB3 is always ready to work. Batteries can be charged independently of the printer unit, maximizing uptime and convenience. And the PB2/PB3 comes with secure Bluetooth, 802.11 or IrDA wireless connectivity, as well as standard serial communication.

Priced affordably to enable efficient, cost-effective receipt printing where and when it's needed, the PB2/PB3 commercial receipt printers help companies increase the return on their mobility investment. The PB2/PB3 printers are part of a complete hardware solution from Intermec, that also includes Intermec receipt media and Medallion Support services, as well as a full range of AIDC products.

## Physical Characteristics

	PB2	PB3
<b>Width</b>	103.23 mm (4.06 in)	127.20 mm (5.01 in)
<b>Height</b>	60.96 mm (2.40 in)	57.69 mm (2.27 in)
<b>Length</b>	138.58 mm (5.46 in)	156.10 mm (6.14 in)
<b>Weight – printer only</b>		
	314 g (11.1 oz)	422 g (14.9 oz)
<b>Weight – with battery &amp; media roll</b>		
	472 g (16.7 oz)	583 g (20.6 oz)

## Environmental

**Operating temperature:** -10°C to 45°C (14°F to 113°F)

**Storage temperature:** -20°C to 60°C

(-4°F to 140°F) without battery

**Operating humidity:** 20% to 85% non-condensing

**Storage humidity:** 5% to 95% non-condensing

**Rain & Dust Resistance:** IP54 with optional environmental case

**Drop spec:** Survives 1.5m (5 ft.) drop to concrete (PB2); 1 m (3.3 ft.) (PB3)

## Power

**Battery:** Rechargeable 7.4V Li-Ion, 2200mAh.

Battery rechargeable up to 8.5V.

**Recharging:** approximately 180 minutes

**Charging temperature:** 10°C to 25°C (68°F to 77°F)

**Battery storage temperature:** 4°C to 40°C (40°F to 104°F)

**Endurance per fully charged battery at**

**25% print density:** 10% print density: PB2:

127m (415 ft); PB3: 108m (354 ft).

**AC Adapter:** 100 to 240 VAC @0.4A; meets CEC EPS

## Memory

**RAM:** 1MB

**Flash:** 4MB

## Standard Communications

RS-232 Serial

## Optional Communications

Bluetooth® (v2.0, Class II)

IrDA

802.11g

## Wireless Security

**Authentication and Encryption Options:**

WPA-PSK/WPA2-PSK; LEAP; WEP 64/WEP 128; TKIP and AES/CCMP

## Optional Card Reader

Magnetic Stripe Reader (MSR) 3 track - ANSI/ISO 7810, 7811 standards

## Print Speed and Resolution

203 dpi (8 dots/mm)

**PB2:** up to 2+ ips (56mm/s at 7.2V;

25C and 64 dots fired) at 8.5V

**PB3:** up to 2 ips (50mm/s at 7.2V;

25C and 64 dots fired) at 8.5V

## Print Technology

**Printhead:** Direct thermal

**Maximum print width:**

**PB2:** 48mm (1.89 in); **PB3:** 72mm (2.83 in)

## Media

**Type:** Receipt media

**Width:** **PB2:** 57mm (2.25 in); **PB3:** 79mm (3.125 in)

**Media length:** Continuous

**Thickness:** up to 4 mil

**Core ID:** 10mm (0.4 in)

**Capacity:** PB2: 18m (60 ft); PB3: 13m (44 ft)

## Software

Programming Language

ESC-P command sets (Line Print and Easy Print modes)

## Character Sets

**Standard:** English and Latin

**Optional:** Arabic, Simplified Chinese, Traditional

Chinese, Cyrillic, Greek, Hebrew, and Polish

**Resident font sizes:** PB2: 24, 32, 38, 40, 48 characters

per line; PB3: 36, 48, 57, 63, 72 characters per line

## Graphics

Supports user-defined fonts, graphics, formats and layouts, including custom logos

## Barcode Symbolologies

**1D:** Codabar, Code 39, Code 128 Subset A-C, UCC/

EAN-128, Interleaved 2 of 5, UPC/EAN/JAN

**2D:** PDF417

## User Interface

**Three Multi-function Status LEDs:** Power on,

Bluetooth® or 802.11g radio on, low battery,

battery charging, card reader ready (for

MSR options), print error, paper out.

## Ships with

Printer, battery, universal AC adapter,

belt clip, one roll of media, printhead

cleaning pen, quick start users guide

## Accessories

Universal AC charger with four socket adapter

plugs, belt clip, shoulder strap, IP54 protective

environmental case, card reader cleaning cards,

printhead cleaning pen, battery, two-bay battery

charger, cigarette lighter adapter/12V vehicle

battery charger, serial cable, developers kit.

## Warranty

One year; additional Medallion

service packages available

## North America

### Corporate Headquarters

6001 36th Avenue West

Everett, Washington 98203

Phone: (425) 348-2600

Fax: (425) 355-9551

### South America & Mexico

#### Headquarters Office

Newport Beach, California

Phone: (949) 955-0785

Fax: (949) 756-8782

## Europe/Middle East &

### Africa Headquarters Office

Reading, United Kingdom

Phone: +44 118 923 0800

Fax: +44 118 923 0801

### Asia Pacific

#### Headquarters Office

Singapore

Phone: +65 6303 2100

Fax: +65 6303 2199

## Internet

[www.intermec.com](http://www.intermec.com)

Worldwide Locations:

[www.intermec.com/locations](http://www.intermec.com/locations)

## Sales

Toll Free NA: (800) 934-3163

Toll in NA: (425) 348-2726

Freephone ROW: 00 800 4488 8844

Toll ROW: +44 134 435 0296

## OEM Sales

Phone: (425) 348-2762

## Media Sales

Phone: (513) 874-5882

## Customer Service and Support

Toll Free NA: (800) 755-5505

Toll in NA: (425) 356-1799

Copyright © 2008 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611906-01B 10/08

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

